



MATADOR™



Before using the BBQ, remove any packaging material within and around the BBQ supplied for protection during transit.

TITAN 6

6 BURNER OUTDOOR BBQ KITCHEN

Retain manual for future reference.

CONTENTS

FEATURES & BENEFITS	3
IMPORTANT INFORMATION & SAFETY	4
SAFETY	5
DO'S AND DON'TS	6
INSTALLATION & ASSEMBLY	7
POSITIONING THE BARBECUE	8
PORTABLE GAS CYLINDERS	9
LEAK TEST	10
USING THE BARBECUE	11
MAINTAINING YOUR BARBECUE	12
TROUBLESHOOTING	13
CONNECTING NATURAL GAS	14
REPLACING LIGHT BULB	15
PARTS DIAGRAM	16
ASSEMBLY INSTRUCTIONS	17
OPTIONAL MATADOR FRIDGE	42
ROTISSERIE INSTRUCTIONS	45
LIST OF SPARE PARTS	49
MATADOR WARRANTY	56

CONTACT INFORMATION

For spare parts order from your nearest
Bunnings Warehouse.

Australia for service and warranty queries, please go to the
Garth support website: www.garthsupport.com
or call 1800 427 841

New Zealand for service and warranty queries, please go to
your local Bunnings warehouse or call 09-9782200,
Fax 09-9782222, Email Marketing@bunnings.co.nz
www.matadorbbqs.com.au



MATADOR

FEATURES & BENEFITS



BARBEQUE DIMENSIONS

	Length	Width	Height
Hood & BBQ (6B)	1008.1mm	723.1 mm	519.4 mm
Cabinet (6B)	2292 mm	723.1 mm	1322.2 mm

NOMINAL HOURLY GAS CONSUMPTION

6 Burner	REAR BURNER	SIDE BURNER	SEAR BURNER
TOTAL INPUT ULPG:75MJ/hr INJECTOR SIZE:1.1mm PRESSURE:2.75kPa	TOTAL INPUT ULPG:9MJ/hr INJECTOR SIZE:0.95mm PRESSURE:2.75kPa	TOTAL INPUT ULPG:22MJ/hr INJECTOR SIZE:1.3mm PRESSURE:2.75kPa	TOTAL INPUT ULPG:20MJ/hr INJECTOR SIZE:1.22mm PRESSURE:2.75kPa
NATURAL GAS:82.5 MJ/hr INJECTOR SIZE:1.87mm PRESSURE:1.0kPa	NATURAL GAS:8 MJ/hr INJECTOR SIZE:1.35mm PRESSURE:1.0kPa	NATURAL GAS:18MJ/hr INJECTOR SIZE:2.0mm PRESSURE:1.0 kPa	NATURAL GAS:20 MJ/hr INJECTOR SIZE:2 mm PRESSURE:1.0 kPa

IMPORTANT INFORMATION AND SAFETY

This barbecue has been tested and certified in accordance with Australia Standards AS 4557:2004 and is approved for sale and distribution in Australia and New Zealand.

- Read the Instruction Manual thoroughly before assembling or using the appliance.
- Use OUTDOORS ONLY.
- Before installing the barbecue, consider the location of the gas supply and routing of the gas line. When choosing a location for your barbecue, keep in mind that it should not be located under or against any burnable surface.
- Before using the BBQ, remove any packaging material supplied within and around the BBQ for protection during transit.
- Any modifications to this barbecue may be dangerous. Parts sealed by the manufacturer or their agent must not be manipulated by the user.
- Never alter or modify the regulator or gas supply assembly.
- WARNING: Accessible parts may be very hot, please keep young children away.
- Do not move the appliance during cooking.
- Turn off the gas supply at the gas cylinder after use.

WARNING LABELS & STICKERS

Each barbecue has a number of permanent labels and point of sale (POS) stickers. While all POS should be removed prior to using, the permanent heavy duty labels should NOT be removed.

DATA PLATE:

Located on the body of your barbecue you will find the silver data label which contains important information relating to the testing and approval of this product, as well as the serial number and manufacturing date.

Always refer to the details on this data plate, if you need to contact the manufacturer for information, technical support or to order spare parts.

Record the serial number, place and date of purchase on the Warranty pages at the end of this document, for quick future reference.

Garth Australia Pty Ltd Level 16, 145 William Street Melbourne, Victoria, 3000 AUSTRALIA T: +61 3 8998 7990 F: +61 3 9591 7267 www.garthaustralia.com					garth outdoor kitchens					
<input type="checkbox"/> MAINDOOR 4 800-170000-001		<input type="checkbox"/> MAINDOOR 8 800-170000-002		<input type="checkbox"/> MAINDOOR REAR BURNER 800-170000-003		<input type="checkbox"/> MAINDOOR WOK BURNER 800-170000-004		<input type="checkbox"/> MAINDOOR SEAR BURNER 800-170000-005		
TOTAL INPUT <input type="checkbox"/> LPG 45 kPa INJECTOR SIZE: 4.1 mm PRESSURE: 2.75 kPa NATURAL GAS 27.5 kPa INJECTOR SIZE: 1.67 mm PRESSURE: 1.6 kPa		TOTAL INPUT <input type="checkbox"/> LPG 75 kPa INJECTOR SIZE: 4.1 mm PRESSURE: 2.75 kPa NATURAL GAS 27.5 kPa INJECTOR SIZE: 1.67 mm PRESSURE: 1.6 kPa		TOTAL INPUT <input type="checkbox"/> LPG 9 kPa INJECTOR SIZE: 6.8 mm PRESSURE: 2.75 kPa NATURAL GAS 9 kPa INJECTOR SIZE: 3.6 mm PRESSURE: 1.6 kPa		TOTAL INPUT <input type="checkbox"/> LPG 35 kPa INJECTOR SIZE: 4.3 mm PRESSURE: 2.75 kPa NATURAL GAS 35 kPa INJECTOR SIZE: 2.2 mm PRESSURE: 1.6 kPa		TOTAL INPUT <input type="checkbox"/> LPG 10 kPa INJECTOR SIZE: 1.25 mm PRESSURE: 2.75 kPa NATURAL GAS 10 kPa INJECTOR SIZE: 7 mm PRESSURE: 1.6 kPa		
BAI-400243										
<input type="checkbox"/> NZ CLEARANCE FROM COMBUSTIBLE MATERIALS R25 6302 SIDES AND BACK: 1800mm VERTICAL ABOVE: 1000mm Unleashed LPG inlet pressure 2.75 kPa to cylinder pressure Natural gas inlet pressure 1.6 kPa to 3.6 kPa										
<input type="checkbox"/> INPUT: 230-240 Vac 50/60 Hz 10A/15A OUTPUT: 12Vdc 1.57A 200W a. Use only with a GFI protected circuit. b. Use only outdoor cords approved for outdoor use marked with W-A and rated for the power of this appliance.										
SERIAL NUMBER:					DATE:					
FOR OUTDOOR USE ONLY										

SAFETY COMPLIANCE LABEL:

While there is a requirement under the Regulations for all gas products to be safe, the Australia / New Zealand regulatory environment establishes the limits of fundamental safety.

The Safety Compliance Label confirms that this barbecue has been certified as compliant and deemed suitable for importing and operation in Australia / New Zealand.



WARNING: The appliance must not be used indoors.

Contact your local Municipality for any building codes regulating outdoor barbecue installations.

When using an ULPG supply system in an enclosure, ventilation must be provided. Gas vapour is highly explosive and can cause serious injury if allowed to accumulate in a confined space and ignited.



MATADOR



SAFETY

How do I use a ULPG Appliance Safely?

The safety record for gas appliances in Australia and New Zealand is excellent, and reflects both the high quality of appliances sold as well as growing consumer awareness about safe practice.

It is important that you READ THE MANUFACTURER'S INSTRUCTIONS thoroughly. If you have any questions or doubts, call the retailer or visit the Garth Support website.

www.garthsupport.com

If there is a leak:

- Turn the cylinder off.
- Ventilate the area to disperse gas.
- Check all connections.
- If the leak persists, keep the cylinder upright and take outside if possible. Keep skin away from any gas or liquid escaping from the cylinder.
- Keep the cylinder at least 20 metres away from any sparks or ignition sources, including electrical equipment, camera flashes, engines and motors.
- Disperse gas by encouraging maximum ventilation and spraying with a fine water spray.

If there is a fire:

- If the fire is at the barbecue, turn the gas off at the cylinder. Smother the flames with a wet cloth, fire blanket or extinguish using a fire extinguisher.
- If the fire is at the cylinder, or you can not get to the valve to turn the gas off, contact the fire brigade immediately.
- Using a garden hose, direct the water to the middle of the cylinder to keep it cool. Try not to extinguish the flame. At least if the gas is burning, it won't be able to build up pressure and explode.

Setting Up The Drip Tray

- Line the primary drip tray with foil.
- Put a fat absorbent material NOT sand or kitty litter in the small secondary drip tray.
- Ensure you regularly clean and replace the foil and fat absorber.
- Fat fires from the result of an excessive build up of grease and fats are NOT covered by Warranty.

A Note on Fire Prevention:

Most fires in outdoor barbecues are caused by a build up of fats and greases. Regularly cleaning of your barbecue is recommended. Refer to the Maintaining Your Barbecue section in this booklet for further information or visit the Garth Support website.

- NEVER operate this barbecue without a regulator.
- NEVER alter or modify the regulator or gas supply assembly.
- DO NOT connect your barbecue to an unregulated gas cylinder.
- DO NOT connect your gas barbecue to a gas cylinder exceeding this capacity
- TURN OFF the gas supply at the gas cylinder after use.
- DO NOT store empty or full spare gas cylinders under or near this or any other appliance
- Keep the gas hose away from hot surfaces and protect from dripping grease. Avoid unnecessary twisting of the hose. Visually inspect the hose prior to each use for cracks, excessive wear or other damage. Replace the hose if necessary.
- NEVER test for gas leaks with a lit match or open flame.
- NEVER light the barbecue with the hood closed or before checking the burner tubes are seated over the gas valve orifices.
- This barbecue must not be used indoors.
- WARNING: Accessible parts may be very hot. Keep young children away.
- This appliance must be kept away from flammable materials during use.
- Ensure that the barbecue is on a level and stable surface.
- DO NOT move this barbecue during use.
- Remove the drip tray before moving.

DO'S

- ✓ Have ULPG cylinder (LP units) filled by an authorised ULPG supplier.
- ✓ Check all gas line connections for leaks with a soapy solution prior to lighting and tighten until bubbles disappear.
- ✓ Preheat the barbecue for 2 - 5 minutes before cooking.
- ✓ After cooking, turn knob to hi setting for 5 minutes to burn off excess grease deposits. Then turn off gas at the knob and at the cylinder.
- ✓ Turn the gas off promptly should you be unable to light the barbecue immediately. Wait one minute before attempting to light again.
- ✓ Have proper tools, tongs, mittens and hot pads ready prior to removing foods.
- ✓ Trim excess fats from meats to minimize flare-ups.
- ✓ Let the barbecue cool before removing any parts for cleaning.
- ✓ Be careful of the control valve setting, hi - lo. A lower setting may generally be preferred.
- ✓ Minimum gas cylinder requirement is 9kg.



DON'TS

- ✗ Don't install the barbecue closer than 1000mm on the sides or 1000mm in the back to any combustible surface or less than 1 meter beneath any overhead combustible construction.
- ✗ Don't attempt any adjustment of the regulator. It has been preset and tested.
- ✗ Don't allow the ULPG cylinder to lie on its side. Keep it in an upright position.
- ✗ Don't turn a control knob on until a lighted match is inserted in the lighting hole ready to light burner (Manual ignition only).
- ✗ Don't use plastics or untempered glass utensils on the barbecue.
- ✗ Don't wear long loose flowing clothing around the barbecue. Long flowing hair is also easily ignited, especially by unexpected flare-ups. Tie hair back or wear a hat or scarf.
- ✗ Don't put food on the barbecue and leave it unattended or unwatched for long periods. Most fats can catch fire even on the lower setting.
- ✗ Don't use caustic materials to clean barbecue parts.
- ✗ Don't exceed temperature of 480°F or 250°C with the hood closed.



Do not replace the grill with an extra hotplate. You will violate the gas approval and your warranty will be voided. The grill provides the ventilation needed for the barbecue to operate safely, it is not designed to be a solid hotplate device.

WARNING!




MATADOR

INSTALLATION & ASSEMBLY

It is important to read these instructions thoroughly. If you have any problems, contact the manufacturer or contact the retailer.

1. The appliance must be installed in accordance with these Instructions and Installation requirements of the local Gas Authority and installation code AS-NZS 5601.
2. Before installing the barbecue, consider the location of the gas supply and routing of the gas line. If connecting to Natural Gas (approved models only), please refer to instructions on page 14. When choosing a location for your barbecue, keep in mind that it should not be located under any burnable surface. All sides, including the back, should not be any closer than 1000 mm for a combustible surface. A minimum clearance height of 1 meter is required from any combustible surfaces overhead.
3. A 3/8" SAE male thread is exposed for connection on the right hand side.



4. ULPG systems with a self contained gas supply should be connected as follows: Connect regulator and flexible hose, using a spanner, between the leg and the barbecue. Take care not to over tighten the joints. Never operate your barbecue without a regulator.

5. After connecting the gas supply, turn on the gas ensuring all gas valves are in the OFF position and check for leaks by brushing a soap and water solution over all joints. The presence of bubbles indicates a leak. Under no circumstances should a naked flame be used to check for leaks. If a gas odour is present and no leaks can be found, do not use the barbecue and refer to place of purchase.
6. Light each burner separately and inspect the flames. They should be a soft blue colour, with an occasional yellow tip. If the burner is noisy and the flames are sharp and bright blue, or conversely, is hazy with considerable yellow or there is a lack of heat from the burner, please clean the burners as detailed under Maintaining your Barbecue. If this does not rectify the problem please refer to the place of purchase.
7. If, after following the instructions, satisfactory performance cannot be obtained, please refer to your place of purchase.
8. **Seasoning the Cooking Surfaces**
 - Before using the BBQ for the first time, the cooking surfaces should be washed with a mild soap and water solution to remove any dust.
 - Dry the cooking surfaces and then apply a light coating of cooking oil.
 - Light your barbecue for the first time and turn all the burners to the LO position.
 - Leave burners alight for 30 minutes for curing.
 - Your barbecue is now seasoned and ready for your first barbecue.
9. **Service**

Other than general cleaning, servicing of this barbecue must be carried out by an authorised person.

NOTE: The regulator thread that connects to the cylinder is anti-clockwise thread.

NOTE: If your appliance fails to operate Successfully, please go to the Garth Support website: www.garthsupport.com or call 1800427841 (Australia), 0800357050 (New Zealand) for warranty assistance

POSITIONING THE BARBECUE

This appliance should only be used in an above ground, open air situation with natural ventilation, without stagnant areas, where gas leakage and products of combustion are rapidly dispersed by wind and natural convection.


Any enclosure in which the appliance is used shall comply with one of the following:

- An enclosure with walls on one side, but at least one permanent opening at ground level and no overhead cover.
- Within a partial enclosure that includes an overhead cover and no more than two walls.

Within a partial enclosure that includes an overhead cover and no more than two walls, the following shall apply:

- At least 25% of the total wall area is completely open;
- and
- At least 30% of the remaining wall area is open and unrestricted.

In the case of balconies, at least 20% of the total of the side, back and front wall areas shall be and remain open and unrestricted.



Minimum Distances from Combustible Material

The barbecue must not be installed under or on any combustible material. Minimum clearance from any combustible materials of ALL sides of the barbecue is 1000mm and 1000mm overhead.

BARBECUES MUST BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS, LOCAL GAS FITTING REGULATIONS, MUNICIPAL BUILDING CODES AND THE GAS INSTALLATION CODE AS/NZS 5601.

The following figures are diagrammatical representations of outdoor areas described. Rectangular areas have been used in these figures - the same principle applies to any other shaped area.




figure (a)




figure (b)




figure (b)




figure (c)




figure (d)

This appliance shall only be used in an above ground open-air situation with natural ventilation, without stagnant areas, where gas leakage and products of combustion are rapidly dispersed by wind and natural convection.

Any enclosure in which the appliance is used shall comply with one of the following:
An enclosure with walls on all sides, but at least one permanent opening at ground level and no overhead cover.
Within a partial enclosure that includes an overhead cover and no more than two walls.



MATADOR

PORTABLE GAS CYLINDERS

What is ULPG?

ULPG is fuel gas compressed until it turns to liquid, then stored in a bottle or cylinder under pressure for easy transport.

The minimum size gas bottle to be used for this BBQ is 9Kg

How is it different from Natural Gas?

ULPG is similar to natural gas. It is colorless, non-poisonous and does not pollute when burnt. Appliances, like heaters or barbecues, that can work on natural gas can often be converted to work on ULPG and vice versa. There is one important difference - ULPG is heavier than air so if it escapes it does not float away. Instead ULPG will collect and form in gas pools at ground level or at the bottom of your appliance.

How do I connect the appliance to the gas cylinder?

There are three types of connection to ULPG cylinder. Some appliances require a hose and regulator. The regulator is a device attached to the hose to reduce the gas pressure.

The Dataplate on these appliances should indicate the correct pressure – e.g. “ULPG pressure, 2.75kPa.”

Other appliances simply require a hose. These deliver gas at high pressure to the appliance. The dataplate on these should read “Cylinder Pressure Only”.

Finally, some appliances are designed for direct connection to a certain type of cylinder (e.g. Primus or Companion). The data plate on these appliances should read “Cylinder Pressure Only”.

How do I use the Gas Cylinder?

Most ULPG cylinders work basically the same. There is a valve handle at the top, which you turn to release the gas. This works the same as a water tap, except that the gas is released at high pressure. Portable appliances often have a short length of hose which connects the gas bottle to the appliance.

A few simple rules here:

1. Store the cylinder safely

When you are not using your ULPG cylinder, store it where it cannot be knocked around and damaged. Store it away from direct heat and make sure that the area is well ventilated in case of slow leaks building up. Also, keep away from any other bottles of compressed gases and if possible, use a cylinder sealing plug to prevent leaks.

2. Always keep the cylinder upright.

3. Refilling

When the cylinder runs out of ULPG, please swap the empty gas bottle for a full one through any gas exchange program.

4. Inspection

If you do not have a cylinder exchange program available in your area and have your gas cylinders filled, have the cylinder inspected EVERY 10 YEARS at an authorised testing station. The date of every inspection is imprinted onto the cylinder itself.

5. Repairs

Do not tamper with any fitting attached to any ULPG gas cylinder. Contact the supplier or an authorised testing station

6. Keep protected from heat

Heat will increase the pressure inside the bottle due to the ULPG expanding. This could cause the safety valve to open and allow gas to escape. If the cylinder feels hot to the touch, keep the cylinder shielded from the appliance.

7. Hose Inspection

Check the gas hose and fittings for deterioration once a year or whenever replacing the gas cylinder. The hose must be replaced if it is cracked, split, cut or damaged.

IF THERE IS A GAS LEAK

1. Turn the gas cylinder off.
2. Ventilate the area to disperse any accumulated gas.
3. Check all connections.
4. If the leak persists, keep the cylinder upright and take to an open area.
5. Keep skin away from any gas or liquid escaping from the cylinder.
6. Keep the cylinder at least 20 meters away from any sparks or ignition sources including electrical equipment, camera flash, engines or motors.
7. Disperse gas by providing maximum ventilation and spraying with a fine water spray.


Always turn off the gas supply at the gas cylinder after use.

GAS LEAK TEST

Before lighting your barbecue it is important to carry out this simple test to check whether the gas cylinder, hose and regulator are working / connected correctly.


NEVER TEST FOR GAS LEAKS USING A LIT MATCH OR OTHER NAKED FLAME

①



TURN OFF THE GAS VALVE


②




TURN ON THE GAS BOTTLE

③





MAKE SOAPY WATER SOLUTION





④



CHECK FOR LEAKS BY BRUSHING A SOAP AND WATER SOLUTION OVER ALL JOINTS. THE PRESENCE OF BUBBLES INDICATES A GAS LEAK.



⑤



RE-TIGHTEN THE CONNECTION IF GAS LEAKAGE OCCURS



MATADOR


USING THE BARBECUE

LIGHTING INSTRUCTIONS

This BBQ uses a new type of ignition system; please see below for lighting procedures

NOTE: Light all main burner before lighting the side burner.


1. READ INSTRUCTION MANUAL
BEFORE LIGHTING
2. LIFT THE HOOD
3. FOR MAIN BURNERS AND SIDE
BURNER: PRESS AND TURN
SLOWLY TO HI FOR AUTO
IGNITION TO LIGHT
FOR REAR BURNER: PRESS AND
TURN SLOWLY TO HI AND PRESS
IGNITION BUTTON TO LIGHT
4. IF BURNER DOES NOT LIGHT,
TURN TO OFF, WAIT 2 MINUTES
AND THEN REPEAT PROCEDURE
5. BEFORE USING REAR BURNER
REMOVE WARMING RACK
6. BEFORE USING THE SIDE BURNER
LIFT THE SIDE BURNER LID



NOTE: It is important to ensure that all control valves, including the gas cylinder, are turned off after use.

FOR MANUAL IGNITION

1. Light a 90mm barbecue match or a lighting gun and hold adjacent to the lighter hole at the right end of the barbecue.



2. Turn the right hand gas control knob to the **HI** position. The burner will light from the match.
3. Once the right burner is lit, the burner next to it can be turned on and will light off the lit burner. Repeat till all burners are alight.

Each burner can be adjusted to provide a low setting by turning the gas control knob to the **LO** position.

PREHEATING

Light the burners as previously directed and turn to HI and allow the barbecue to preheat for 2 - 5 minutes.

PREPARE THE COOKING SURFACE

It is preferable to apply a light coat of cooking oil using a long handed brush to the cooking grills prior to lighting each time, the oil will keep food from sticking to the cooking surface.

USING THE HOOD WHEN COOKING

When using the barbecue with the hood closed, use the two outside burners only and do not exceed 250°C. Exceeding 250°C can damage the barbecue and void your warranty.

FLARE-UP CONTROL

Anytime you cook meat above an open flame you will have flare-ups which are caused when the natural juices from the meat fall on the flame tamers (diffusers) below the cooking plates.

Flare-ups, and the resulting smoke, are what give meat cooked over an open flame that delicious outdoor flavour. So expect and encourage some flare up.

However, excessive flaring can be caused by cooking extra fatty or marinated foods directly on the grill plates, by cooking with too high a temperature or by a build up of fats and residue in the drip tray beneath the burners.

These types of flare-ups should be controlled, or your food will burn.

To prevent excessive flare-ups, trim off excess fat from meat and poultry before placing on the grill, cook fatty or marinated meats on the barbecue plate and clean your drip tray regularly.

To control excessive flare-ups caused by too high a heat, turn the control knob down to a lower setting.

Throw a small amount of baking soda or gently spray a small amount of water (from a meat baster or spray bottle) directly onto the flame tamers to put out excessive flaring.

Do not spray aerosols in the vicinity of this appliance while it is in operation.

Do not use or store flammable materials in or near this appliance.

Do not place articles on or against this appliance.

Do not modify this appliance.

MAINTAINING YOUR BARBECUE

CARING FOR THE BURNERS & INJECTORS

To ensure continued satisfaction from your barbecue it is essential to keep the burners and injectors clean.

Under normal usage, your barbecue should be left burning for five minutes after cooking has ceased. This will burn off any excess fats, juices, etc.


Occasionally, after long cooking sessions, excess fats, juices and marinades can clog the burners. Remove the burners (see instructions below) and after brushing with a barbecue brush, wash in hot water and detergent – ensuring that all ports are free from detergent.

Rinse in water, shake of excess water and dry if possible. Return to the barbecue and light immediately to remove any remaining moisture.


Apply a light coating of cooking oil to the burners if the barbecue is not to be used for an extended period.

REMOVING THE BURNERS


1. Make sure the barbecue has been switched off and has completely cooled down if recently used.
2. Ensure all gas control knobs are set to the off position and the gas cylinder has been turned off.
3. Lift the grill plate and oil channel off the barbecue.




4. Lift the flame diffuser from position as shown below.



5. Remove the bolts at the rear of the BBQ from the burner.



6. Lift and swing out the burner from position as shown below.



7. Simply reverse the previous procedure to reinstall the burners, flame diffuser and grill plate.

CARING FOR THE GRILLS & HOTPLATES

After cooking, turn the control knobs to the HI setting for five minutes to burn off any excess grease deposits.

Then turn off the gas at the control knob and at the cylinder. Let the barbecue cool before removing any parts for cleaning.

The grills and hotplates should be cleaned regularly depending upon usage and types of food cooked (ie sausages, fatty foods) to prevent a build up of fats and greases.

Cast Iron cooking surfaces should require washing. Simply heat the barbecue and use either a barbecue brush or tool to scrape the surface clean.

A light brushing with cooking oil should be applied to the grills and hotplates if the barbecue is not to be used for an extended period.

CLEANING THE BARBECUE

To ensure your barbecue is ready the next time you want to use it, turn all burners OFF and take a long handed brush and carefully brush off the cooking surfaces.

Remember to protect hands from the heat by using an oven mitt to hold the brush.

The barbecue body should also be cleaned regularly using hot water and detergent, depending upon usage to prevent a build up of fats and greases.

Remember to dry thoroughly and cover the barbecue securely with a weather proof cover.

Before use checks:

Remove accumulated grease and other cooking residue
Inspect the gas hose and regulator and periodically replace annually

Check all connections for gas leakage

Check gas cylinder date stamp is current



MATADOR

TROUBLESHOOTING

My BBQ will not light properly. Why?

- Check LPG gas supply.
- Check to insure all gas connections are secure, including the gas hose connection to your Side Burner (most models).
- Check that the end of each burner is positioned properly over each gas valve.

When first lighting my BBQ I have a strong smell of gas.

- Check all connections are tight & then perform a **LEAK TEST** section in this instruction.

CAUTION - BEWARE OF FLASH-BACK:

Spiders and small insects occasionally spin webs or make nests in the bbq burners during transit and warehousing. These webs can lead to a gas flow obstruction which could result in a fire in and around the front of the burner. This type of fire is known as a "FLASH-BACK" and can cause serious damage to your bbq and create an unsafe operating condition for the user.

Although an obstructed Burner is not the only cause of "FLASH-BACK", it is the most common cause.

To reduce the chance of "FLASH-BACK", you must clean the burner before assembling your barbecue. Also perform the burner cleaning procedure on page 7 if your bbq has not been used for an extended period of time.

I found a damaged part while unpacking my new barbecue from the box. How do I get a replacement part?

or
While assembling my new barbecue, I realised a part is missing. Who do I contact to replace parts that were missing from my box?

Garth Australia Pty Ltd stocks replacement parts for your gas barbecue. Follow these steps for fast and accurate part replacement:

- Then, refer to the **LIST OF SPARE PARTS** to identify the missing part(s) and go to our Garth Support website **www.garthsupport.com**, or contact us on our free call number:
Australia - 1800 427 841
New Zealand - 0800 357 050

Note: Recommended Maintenance

Recommended maintenance should be carried out by an authorised person every 12 (twelve) months for the life expectancy of the appliance.

For Technical Assistance

If you experience any technical issues with your barbecue, in the first instance review the instruction manual or contact the Garth Customer Support Department through the Garth Support website at **www.garthsupport.com** for assistance.

For Spare Parts

To order spare parts, you can return to your place of purchase and ask them to order a part for you. Alternatively, you can order directly through the Garth Support website at **www.garthsupport.com**

You will need to provide the following information:

- Model of Barbecue
- Year of Purchase
- Part requiring replacement (refer to the Spare Parts List in your Assembly Manual)
- Name of the warranty service company (if applicable)

- Locate the serial number of your BBQ as found on the silver data Label. This could be located on the bottom of the front fascia of the BBQ, the right hand side of the BBQ frame, on the rear of the BBQ frame or behind the cabinet door, depending on your model. Then, it's a good idea to write the serial number & date of purchase in the **MATADOR WARRANTY** section for quick future reference.

CONNECTING NATURAL GAS

This barbecue model is approved for conversion from Propane to Natural Gas (for Australia only).

The following steps are required to complete the conversion:

1. Contact a registered Gas Fitter / Plumber to obtain a quote for the conversion and to confirm whether this appliance will work efficiently with the current gas supply to your household, in accordance with the Installation Code AS5601.
2. The Gas Fitter / Plumber will need to source the necessary parts for the conversion.
(Note: Replacement jets can be ordered directly from Garth with an official Purchase Order and by quoting of the Gas Fitter / Plumber's Registration Number.)
3. Upon completion of the conversion, the Gas Fitter / Plumber is LEGALLY required to issue a Compliance Certificate.
4. DO NOT attempt to complete the conversion yourself.
5. Failure to comply with these requirements and Installation Code AS 5601 will automatically void the Warranty for this product.
6. Contact Garth Support to purchase a natural gas conversion kit.

Restraining tether for appliances with hoses, for connection to fixed gas supply


Where a mobile appliance is to be connected to a fixed gas supply via a flexible hose connection, a restraining tether of adequate strength shall be fixed to the appliance and be suitable to be fixed to the wall within 50 mm of each connection point. The length of the tether shall not exceed 80% of the length of the hose assembly.

NOTE: The restraining tether is intended to prevent stress being imparted onto the hose assembly when the appliance is moved out of its normal operating position.



MATADOR


REPLACING LIGHT BULB




BBQ LIGHT


INPUT: 230-240 Vac 50Hz pf=0.97
 OUTPUT: 12Vac 1.67A 20VA

STEP 1.




STEP 2.




	Light Bulb Type	Maximum Voltage	Maximum Wattage
	G4	12V	10W


STEP 3.




STEP 4.




STEP 5.




PARTS DIAGRAM-SECTION 1




1. CASTOR X4




2. Cabinet bottom panel




3. Drawer holder



4. Decoration panel for side shelf




5. Drawer X2




6. Front decoration panel




7. Drawer handle X3




8. CABINET BACK PANEL




9. CABINET LEFT PANEL



10. CABINET RIGHT PANEL




11. OIL CHANNEL



12. BBQ FRAME + HOOD



13. Cabinet connection plate X4



14. Front decoration panel magnet bracket X2



15. CONTORL KNOB X8



16. DRANER MAT X2



16: 6mm x 10mm



33: 5mm x 12mm



8: 5mm x40mm



6: 4mm



41: 5mm



2: 6mm



37: 5mm



2



16: 8mm




MATADOR

ASSEMBLY INSTRUCTIONS-SECTION 1

STEP 1

 16: 6mm x 10mm

 16: 6mm




STEP 2

 9: 5mm x 12mm

 4: 5mm x 40mm

 13: 5mm

 13: 5mm




STEP 3

 11: 5mm x 12mm


 11: 5mm

 11: 5mm




STEP 4

 9: 5mm x 12mm

 9: 5mm


 9: 5mm





MATADOR

STEP 5


 4: 5mm x 12mm

 4: 5mm

 4: 5mm






STEP 6


 2: 4mm


 2

 2: 6mm




STEP 7

 4: 4mm




MATADOR

STEP 8




STEP 9


-  4: 5mm x 12mm
-  4: 5mm



PARTS DIAGRAM-SECTION 2




1. CastorX4




2. Cabinet bottom panel




3. Cabinet top panel




4. Rubber bumper




5. Cabinet Left panel



6. left Door




7. Side burner bench mounting bracket




8. Cabinet back panel




9. Gas hose mounting panel



10. Top bench



11. Side burner bowl




12. Storage box



13. Roller storage slot




14. Handle




15. Slide in/out gas cylinder bowl



16. Cabinet front cross bar x2




17. Fat tray panel



18. Transformer cable separation panel



19. Wire clip




20. Transformer



21. Door hinge x2



22. Side granite mounting bracket X2



23. Drawer slide



16: 6mm x 10mm



46: 5mm x 12mm



16: 5mm x 8mm



4: 5mm x 40mm



14: 4mm x 10mm



2: 4mm



4: 5mm



66: 5mm



36: 5mm



16: 6mm




MATADOR


ASSEMBLY

INSTRUCTIONS-SECTION 2

STEP 1


 16: 6mm x 10mm


 16: 6mm





STEP 2

 6: 5mm x 12mm

 8: 5mm


 8: 5mm

 2: 5mm x40mm




STEP 3

-  8: 5mm x 12mm
-  8: 5mm
-  8: 5mm



STEP 4


-  8: 5mm x 12mm
-  8: 5mm
-  8: 5mm






MATADOR

STEP 5


 8: 5mm x 8mm



 8: 5mm



STEP 6

 8: 5mm x 8mm


 8: 5mm



STEP 7


 4: 5mm x 12mm


 4: 5mm




STEP 8

 8: 5mm x 12mm

 4: 5mm


 8: 5mm




MATADOR

STEP 9

 4: 5mm x 12mm

 4: 5mm

 4: 5mm




STEP 10

 4: 5mm x 12mm

 4: 5mm

 4: 5mm




STEP 11




4: 4mm x 12mm



2: 4mm




STEP 12



MATADOR

STEP 13



 8: 4mm x 12mm



STEP 14

 2: 5mm x 12mm


 2: 5mm




PARTS DIAGRAM-SECTION 3





1. CASTOR X4




2.Top bench




3.Cabinet bottom panel




4.Side burner bench mounting bracket




5.Side granite mounting bracket



6.Cabinet back panel




7.Right door



8.Cabinet top panel




9.Cabinet front cross bar




10. heat shield



11.Drawer handle




12.Side bench X2



13.Rubber bumper x2



14.burner fitting plate



15.burner fitting plate



16.burner fitting plate



16: 6mm x 10mm



39: 5mm x 12mm



6: 5mm x 8mm



4: 5mm x 40mm



12: 4mm x 10mm



2: 4mm



16: 6mm



49: 5mm



37: 5mm





MATADOR

ASSEMBLY INSTRUCTIONS-SECTION 2

STEP 1


 16: 6mm x 10mm


 16: 6mm





STEP 2

 6: 5mm x 12mm

 8: 5mm


 8: 5mm


 2: 5mm x 40mm




STEP 3

 8: 5mm x 12mm


 8: 5mm


 8: 5mm





STEP 4

 6: 5mm x 12mm

 6: 5mm


 4: 5mm




MATADOR

STEP 5

 6: 5mm x 8mm


 6: 5mm



STEP 6


 4: 4mm x 12mm

 2: 4mm




STEP 7

 6: 5mm x 12mm


 6: 5mm


 6: 5mm





STEP 8

 3: 5mm x 12mm

 3: 5mm


 3: 5mm




MATADOR

STEP 9

 4: 5mm x 12mm

 4: 5mm




STEP 10


 4: 5mm x 12mm

 4: 5mm

 4: 5mm





STEP 11



STEP 12


8: 4mm x 12mm





STEP 14

 2: 5mm x 12mm

 2: 5mm x 40mm

 4: 5mm

 4: 5mm




STEP 15

 2: 5mm x 12mm

 2: 5mm x 40mm


 4: 5mm

 4: 5mm




STEP 12

 2: 4mm x 10mm



STEP 13





MATADOR


STEP 16



x2




STEP 17




MATADOR


STEP 18



STEP 19

 2: 5mm x 12mm


 2: 5mm




OPTIONAL MATADOR FRIDGE

(NOT INCLUDED IN PRODUCTION)

STEP 1




STEP 2




MATADOR


STEP 3




STEP 4



STEP 5




STEP 6




MATADOR

Rotisserie Instructions


1.  2: 6.5mm  2: M6
 2: M6X12  2: 6.5mm




2.




3.




4.




5.



6.




Drawer Adjustement Instructions



If drawer is not level (such as shown on diagram b and c), you can adjust the drawer refer to the procedure below.

Drawer Adjustement procedure:



1.Slide out the drawer and then unscrew the bolts as shown on diagram d (Please screw out the bolts roughly 3mm in this step) ;

2.Adjust the drawier on left and right side as shown on diagram e until the drawer is level;


3.Tighten the bolts mention in step 1.




MATADOR

Titan Kitchen regulator and wire connection instructions


1.Side burner ignition wire connection:




2.Regulator, BBQ light wire, knob light wire and electricy wive attachment:



3.Regulator attachment instructions



4.Attach the BBQ light wire to transformer and attach the knob light wire to battery box



Rotisserie Instructions

direct cooking method

This is where direct heat is used to cook the roast.

If your barbecue has no rear burners, turn the burners on directly below the meat. Juices will fall on the grate and flame diffuser and vapourise. Turn the burners to the hi or low position depending on the height of the food above the flame.

Be careful of excessive flare up.

If your barbecue has a rear burner, then you should remove the cooking grates and place an aluminium drip tray onto the front burners and under the roast. Place several centimeters of water into the drip tray and add fruit juices or wine along with any other of your desired herbs or spices. Place the balanced rotisserie shaft in the motor and switch the motor on.

Turn on the rear burners. Cook the food with a medium flame, being careful to avoid burning. Cooking with the hood closed will help retain flavour, heat and moisture in the process.

Baste the roast a few times during cooking to keep it moist. Cook until an inserted meat thermometer registers a cooked temperature. Do not leave the meat thermometer in the roast during the cooking process.

indirect cooking method

In this method, there is no heat directly underneath the food. Rather, circulating hot air is used to cook the roast.

Remove the cooking grates from the barbecue and place an aluminum drip tray underneath the food. Pour some water into the drip tray and add your favourite flavourings.

If using smoking chips or chunks, now is the best time to add your smoker box to the heat.

Place the balanced rotisserie shaft in the motor and switch the motor on.

Make sure there is no heat directly under the food. Use only burners to the side of the food. Close the hood and maintain a medium temperature (around 230 degrees Celsius) inside the hood by adjusting the remaining burners. Try not to open the hood too often during the cooking process as this will add to the overall cooking time.

Check the internal temperature of the roast with a meat thermometer before removing the roast from the barbecue. Do not leave the meat thermometer in the barbecue during cooking.




MATADOR.

LIST OF SPARE PARTS

For spare parts refer to your
store of purchase.

For warranty visit:

www.garthsupport.com



PART NUMBER	PART NAME	SUPPLIER CODE	AVAILABLE OR NOT
1	Side Burner Trivet	SB-103	
2	Wok burner	TMB003-1	
3	Wok burner base	TMB003-2	
4	Wok burner venturi	TMB003-4	
5	Side burner bowl	RCTR0-4902-09100-081	
6	Side burner injector Holder	RCTR0-0801-07080-074	
7	Side burner injector	INJ-1.27SBE	
8	Side Burner Under Strut	RCTR0-3001-04080-033	
9	Side burner ignition wire	Q3561	
10	Side bench	RCTB0-1901-21000-080	
11	Side granite mounting bracket	RCTB0-2001-07200-031	
12	left Door	RCTB0-1601-09060-085	
13	Door hinge	RCTB0-3401-00000-080	
14	Dool handle	RCTB0-0101-11000-031	
15	Side burner lid bracket	RCTB0-3201-09150-080	
16	Side burner Lid	RCTB0-0201-09080-085	
17	Storage box lid	RCTB0-2201-09080-085	
18	Top bench	RCTB0-2601-21000-080	
19	Cabinet front cross bar	RCTB0-0601-07060-031	
20	Cabinet top panel	RCTB0-0801-07060-031	
21	Drawer holder	RCTR0-1401-07100-074	
22	Drawer slide	RCTR0-1301-00000-080	
23	Slide in/out gas cylinder bowl	RCTB0-2701-07080-031	
24	Cylinder bowl handle	BH-JD4	
25	Rubber bumper	K2224	
26	Rubber buffer fitting plate	RCTB0-3001-07150-031	
27	Cylinder bowl support	RCTB0-2801-07080-031	
28	Cabinet bottom panel	RCTB0-1201-07080-031	
29	Cabinet bottom strengthen frame	RCTB0-2901-00000-031	
30	Self levelling castors	VM160329	
31	Cabinet back panel	RCTB0-0701-07060-031	
32	gas hose mounting panel	RCTB0-3301-07060-031	
33	Storage box	RCTB0-2101-09070-081	
34	Rotisserie storage slot	RCTB0-2401-09070-081	
35	Oil cup	RCTB0-1801-09050-081	
36	Transformer	RCTR0-3501-00000-000	
37	Transformer cabel separation panel	RCTR0-3801-07060-031	
38	Wire clip	RCTR0-3701-13000-000	
39	Right bench panel	RCTB0-3101-00000-031	
40	Bolt pack	BP-B325-17-1	






MATADOR

LIST OF SPARE PARTS

For spare parts refer to your
store of purchase.

For warranty visit:

www.garthsupport.com



PART NUMBER	PART NAME	SUPPLIER CODE	AVAILABLE OR NOT
1	Top bench	RCTB0-2602-21000-080	
2	Top bench mounting bracket-1	RCTB0-3501-07060-031	
3	Top bench mounting bracket-2	RCTB0-3601-07060-031	
4	Top bench mounting bracket-3	RCTB0-3701-07060-031	
5	Right bench panel	RCTB0-3102-00000-031	
6	fridge heat shield panel	RCTB0-3801-07060-031	
7	Right door	RCTB0-1701-09060-085	
8	Door hinge	RCTB0-3401-00000-080	
9	Door handle	RCTB0-0101-11000-031	
10	Cabinet front cross bar	RCTB0-0602-07060-031	
11	Cabinet top panel	RCTB0-0801-07060-031	
12	Rubber buffer fitting plate	RCTB0-3001-04150-031	
13	Rubber bumper	K2224	
14	Cabinet bottom panel	RCTB0-1202-07080-031	
15	Cabinet bottom strengthen frame	RCTB0-2902-00000-031	
16	Self levelling castors	VM160329	
17	Cabinet back panel	RCTB0-0702-07060-031	
18	Right Side Bench	RCTB0-1902-21000-080	
19	Side granite mounting bracket	RCTB0-2001-07150-031	
20	Bolt pack	BP-B325-17-2	




MATADOR

LIST OF SPARE PARTS

For spare parts refer to your
store of purchase.

For warranty visit:

www.garthsupport.com



PART NUMBER	PART NAME	SUPPLIER CODE	AVAILABLE OR NOT
1	Hood outer top	RCHD6-0701-09060-085	
2	BBQ frame	RCBQ6-2803-04100-033	
3	Grillsmart hotplate	B03057-M	
4	Warming rack	RCBQ6-0101-01000-033	
5	Hood second skin top	RCHD6-0801-09060-085	
6	Glass support strip	RCHD6-1501-11000-080	
7	Hood right end	RCHD0-0601-03000-031	
8	Hood left end	RCHD0-0501-03000-031	
9	Hood hinge serew	RCHD0-0201-01000-077	
10	Hood hinge holder	RCHD0-0301-04000-077	
11	Hood hinge pin	RCHD0-0101-01000-077	
12	Rubber bumper	K2224	
13	Temperature gauge bowl	TG-B05	
14	Temperature gauge bezel	BS131016-B	
15	Temperature gauge	N160307	
16	Glass seal	RCHD0-1601-02000-080	
17	hood gass	GBZ-6	
18	Hood second skin bottom	RCHD6-1001-04060-084	
19	Hood outer bottom	RCHD6-0901-09060-085	
20	Left hood handle base	RCHD0-1201-03000-031	
21	Hood handle	RCHD6-1101-01000-031	
22	Right hood handle base	RCHD0-1301-03000-031	
23	BBQ frame back cover	RCBQ6-3301-07060-104	
24	Fascia heat shield panel	RCBQ6-2401-05050-080	
25	BBQ front decoration part	RCBQ6-2201-00000-031	
26	Fascia	RCBQ6-2302-09080-085	
27	Ignition box	PI-PT01	
28	Light Switch	RCBQ0-8001-10000-080	
29	Oil channel	RCBQ6-1304-10050-080	
30	Rear burner gas valve	GC-081A	
31	Main burner gas valve	GC-077A	
32	Side burner gas valve	N0056A	
33	Sear burner gas valve	GC-085A	
34	Control knob bezel	BS170331	
35	Sear burner Control knob beze	BS170329	
36	Control knob	BKNB-207A	
37	Main burner ignition pin	Q3558	
38	Main Burner	BR160122	
39	Sear burner ignition pin	Q3562	
40	Sear Burner	B03094-M	
41	BBQ support foot	RCBQ0-5301-04100-033	
42	Oil cup	RCBQ0-4701-05050-080	
43	Fat tray	RCBQ6-2002-10060-080	
44	Fat tray handle	RCBQ6-0901-09060-080	
45	badge	BA-B2015V2	
46	Cabinet top panel	RCTR6-1002-07060-031	
47	Front decoration panel magnet	RCTR6-10201-07060-031	
48	Drawer front face	RCTR6-10101-09060-085	
49	Drawer handle	RCTR0-6101-11000-031	
50	Cabinet magnet	MG-10	



MATADOR

PART NUMBER	PART NAME	SUPPLIER CODE	AVAILABLE OR NOT
51	Drawer holder	RCTR0-1401-07100-031	
52	Drawer slide	RCTR0-1301-00000-074	
53	Drawer	RCTR6-1101-07000-031	
54	Drawer handle	RCTR0-6101-11000-031	
55	middle cabinet storage tray	RCTR6-9701-07060-031	
56	Cabinet bottom panel	RCTR6-1902-07080-031	
57	Cabinet bottom strengthen frame	RCTR6-8802-00000-031	
58	Self levelling castors	VM160329	
59	Grillsmart grill	B03058-M	
60	Rear burner cover	RCBQ0-5101-04060-011	
61	Rear burner injector	B279-15B-H-03	
62	Rear burner	TMA0823	
63	Rear burner holder	RCBQ0-5401-04060-011	
64	V shape flame tamer	RCBQ0-0501-10100-080	
65	Sear burner flame tamer	RCBQ0-7601-10100-080	
66	Knob light wire set	RCBQ6-6903-00000-080	
67	knob lights	RCBQ0-6803-00000-080	
68	BBQ Light set	BQLW-2L	
69	Right BBQ Light Support Plate	B238-B-08	
70	Left BBQ Light Support Plate	B238-B-09	
71	BBQ light Bulb	BQ-BU10W	
72	Rear Burner Ignition wire	UL-1650	
73	Rear Burner S/S Flexible Pipe	FP-160-01	
74	Manifold S/S Flexible Pipe	FP-110-02	
75	Cabinet back panel	RCTR6-1602-07060-031	
76	Cabinet left side panel	RCTR0-1702-00000-031	
77	Cabinet right side panel	RCTR0-1802-00000-031	
78	Cabinet connection plate	RCTR6-10001-07060-031	
79	Side Burner S/S Flexible Pipe	FP-060-01	
80	Hose and Regulator	RC008002	
81	Drawer mat	MAT-892V2	
82	Bolt pack	BP-B325-17-3	

MATADOR WARRANTY

Thank you for purchasing one of our quality Matador BBQs.

YOUR MATADOR BBQ IS COVERED AGAINST DEFECTS FOR A PERIOD OF 5 YEARS FOR PARTS AND LABOUR, REPAIR OR REPLACEMENT. THIS WARRANTY EXCLUDES SURFACE RUST AND DAMAGE CAUSED BY ABUSE OR NEGLECT.

CONDITIONS OF THE WARRANTY

- The appliance must be operated and maintained in accordance with the instructions supplied in the operating manual.
- Any repair does not extend the warranty period.
- Any parts other than original Matador parts will void this warranty.

Installation Conditions

- All installations must conform to the applicable Gas, Electrical and Building standards as laid down by the local codes for state or region.
- If the appliance is changed to natural gas (if applicable), it must be converted and installed by a licensed gas fitter.

FOR WARRANTY CLAIMS

Garth Australia Pty Ltd.
52 Boundary Road
Sunshine West
Victoria 3020
AUSTRALIA

Garth Support website: www.garthsupport.com
or call: 1800 427 841
email: service@garth.com.au

The warranty for New Zealand is given by
Bunnings NZ Ltd
PO Box 14436,
Panmure, Auckland, 1741
NEW ZEALAND

Tel: 09-9782200
Fax: 09-9782222
Email: marketing@bunnings.co.nz

Any claim under this warranty must be made within 5 years of the date of purchase of the product.

Proof of purchase must be presented.

For Australian Customers

To make a claim under the warranty please contact Garth support website: www.garthsupport.com or return the product (with proof of purchase) to any Bunnings store. (see: www.bunnings.com.au for store locations)

Garth Australia bears reasonable, direct expenses of claiming under the warranty.

The warranty covers manufacturer defects in materials, workmanship and finish under normal use.

This warranty is provided in addition to other rights and remedies you may have under law: our goods come with guarantees which cannot be excluded under the Australian Consumer Law. You are entitled to replacement or refund for a major failure and to compensation for other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The warranty excludes damage resulting from product misuse or product neglect. The warranty covers domestic use only and does not apply to commercial applications

For New Zealand Customers

To make a claim under the warranty, take the product (with proof of purchase) to any Bunnings store (see www.bunnings.co.nz for store locations).

Bunnings NZ Ltd bears reasonable, direct expenses of claiming under the warranty. You may submit details and proof to our store for consideration.

The warranty covers manufacturer defects in material, workmanship and finish under normal use.

The warranty is provided in addition to other rights and remedies you may have under law: our goods come with guarantees which cannot be excluded under the Consumer Guarantees Act 1993 (NZ). You are entitled to replacement or refund for a major failure and to compensation for other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

The warranty excludes damage resulting from product misuse or product neglect. The warranty covers domestic use only and does not apply to commercial applications.

Goods presented for repair may be replaced by refurbished goods of the same type rather than being repaired. Refurbished parts may be used to repair the goods.



MATADOR

WHAT IS NOT COVERED IN THE WARRANTY

- Removal or re-installation costs. This warranty does not cover costs for transit, nor in home service.
- Liability will only be accepted for loss or damage during transit if at the time the product was being transported by Bunnings or a Bunnings approved contractor.
- Lack of maintenance, abuse, neglect, misuse, accidental or improper installation of this appliance.
- Scratches, dents, corrosion or discoloration caused by heat, abrasive chemical cleaners or chipping of porcelain enamel parts.
- Corrosion or damage caused by exposure to the elements such as insects, weather, hail or grease and fat fires.
- Rusting of cast iron plates, grills and burners.
- Cleaning and wear and tear; service calls of this nature are chargeable.
- Commercial use of the product.
- Unauthorized repairs or modifications during the warranty period.
- Glass breakage due to misuse or overheating
- Consumable items, example - batteries.

RECORD THE FOLLOWING INFORMATION

Attach the copy of the purchase receipt here:

Date of Purchase _____
Purchased From _____
Location _____
Model Name and Number _____
Serial Number _____
Receipt Number _____

Note: The serial number is located either on the outside of the packing carton or outside or inside the appliance.

FOR TECHNICAL ASSISTANCE

For Australia customers if you experience any technical issues with your Matador BBQ, in the first instance review the instruction manual or contact the warranty service agent below.

For New Zealand customers if you experience any technical issues with your Matador BBQ, in the first instance review the instruction manual or contact your local Bunnings warehouse.

FOR SPARE PARTS

Call your local Bunnings warehouse and ask them to order a part for you. You should provide the following information.

Model of BBQ _____
Year of purchase _____
Name of warranty service
company above _____
Part that requires replacement
(refer to the list of spare parts in the
instruction manual) _____



Visit www.matadorbbqs.com.au

For technical and warranty support call

1800 427 841 (Aus)

0800 357 050 (NZ)

Your purchase receipt will be required for warranty claims.

For spare parts contact your local Bunnings Warehouse