



Bondall PTY LTD  
ACN: 008 734 096  
ARS: 27 008 734 096

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4066

bondall@bondall.com  
www.bondall.com

## SLATE SEALER

REVISED: OCTOBER 2004

### DESCRIPTION

Tileguard Slate Sealer is a premium quality single pack, clear dressing for slate, natural stone and various quarry tiles.

Tileguard Slate Sealer leaves a glossy finish but this will vary depending on porosity, texture and application technique.

**TEST AREA.** Always test on a small inconspicuous area, to ensure that the product is achieving the desired result, prior to application over the entire area.

### FEATURES AND BENEFITS

- Enhances the natural colour of stone
- Easy to apply
- Suitable for interior and exterior use
- Fast drying
- Prevents soiling
- Waterproofs the surface
- Hard wearing clear finish

### SURFACE PREPARATION

- Surface preparation is important. All surfaces should be completely dry and free from grease, grime, dust and other contaminants prior to the application of Slate Sealer. Clean by using Tileguard Tile & Grout Cleaner. Rinse thoroughly with water after cleaning.

### APPLICATION

- Stir well before use, DO NOT SHAKE. Use a 25mm broad timber or metal paddle and stir with a lifting motion to incorporate the entire product.
- Apply one coat of Slate Sealer as an initial sealer coat and allow drying for four to six hours. Apply a final coat of Slate Sealer to the entire surface.
- Apply Slate Sealer with a good quality paintbrush, applicator pad or spray.
- Slate Sealer will make some surfaces slippery.
- No sanding is necessary prior to re-coating. Simply apply another coat of Slate Sealer when you want to restore lustre.
- Do not apply if the temperature is below 10°C or if rain is expected within 24 hours.
- Ensure adequate ventilation during use.

### COVERAGE

Approximately 10 square metres per litre on high-density surfaces and 4-5 square metres on highly porous surfaces.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD  
ACN: 008 734 096  
ARS: 27 008 734 096

113 Belmont Ave  
Belmont WA 6104  
PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4066  
bondall@bondall.com  
www.bondall.com

## THINNING

Not recommended

## GLOSS LEVEL

Will leave a gloss finish but this will vary upon porosity, texture and application techniques.

## DRYING TIME

Slate Sealer will be touch-dry in 2 hours. Drying times are a guide only. Longer drying times may be required in cooler or humid conditions.

Allow drying for as long as possible before full use, light foot traffic is permissible after 4-6 hours depending on the weather conditions at the time. Allow at least 48 hours before allowing heavy foot traffic. Optimum coating properties after 7 days.

## CLEAN UP

Clean all equipment promptly with warm water and a little detergent followed by a fresh water rinse.

Do not pour contents or washing down drains or sinks. Dispose of as per your council regulations.

## COLOUR

Dries clear.

## SIZES

Available in 1 litre and 4 litre containers.

## PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation. Use a suitable respirator if spray application is employed. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass of water to drink and do not induce vomiting.

Refer to MSDS for more details.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD  
ACN: 008 734 096  
ARS: 27 008 734 096

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4066

[bondall@bondall.com](mailto:bondall@bondall.com)  
[www.bondall.com](http://www.bondall.com)


## DISCLAIMER

The performance of this product is dependant upon its correct preparation, application onto sound surfaces and attention to the instructions on the label. The wide variety of surface conditions make it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specification and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Advisory Service on 1800 810 123 or (08) 9277 6844. See Web Site: [www.bondall.com](http://www.bondall.com)



Wholly Australian Owned & Manufactured

the solution  bondall

