Wiha PicoFinish electric.

The VDE-GS tested precision screwdriver.



The smooth-running turn-cap enables fast

Imprint with the screw symbol and sizes eases recognition.

The new ergonomic Wiha PicoFinish electric precision screwdriver has protective insulation on the bronzed blade which is certified in accordance with VDE-GS and individually tested for breakdown in a water bath at 10,000 V. Because of this, this new family expands the application possibilities of VDE-GS tested fastening tools with tools for smaller screw sizes. These are necessary especially when settings should be made on live electrical or electronic components. Sensitive turning is particularly easy due to its octagonal profile at the beginning of the quick-turning

A further advantage: This tool eliminates the risk of accidentally touching live parts with a blank blade and causing a short circuit.



Wiha PicoFinish electric.

- Ergonomic handle design with soft zone for comfortable work
- Through hardened, bronzed blade of chrome-vanadiummolybdenum steel for a long lifespan
- Protective insulation spraycoated directly onto the blade
- Safety when working with live equipment up to 1,000 V AC and 1,500 V DC
- Each screwdriver is individually tested in a water bath at 10.000 volts according to IEC 60900:2012
- Ideal for all fine and delicate work in electrical engineering and electronics







Wiha PicoFinish electric.



NEW



PicoFinish electric slotted screwdriver.

Handle with rotating cap and rapid-turning zone.

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened,

black-finish. Insulation moulded directly onto blade.

Handle: Wiha PicoFinish handle for sensitive and fast screw fixing. Standards: DIN ISO 2380. Manufactured acc. to IEC 60900:2012.

Application: For all work on or around electrical components up to 1,000 V AC.

Order-No.	1	=	\ominus ;	•	==	—	
38874	1.5	40	0.25	2.0	154	9	10
38875	2.0	60	0.4	2.0	160	18	10
38876	2.5	60	0.4	2.5	160	18	10
38877	3.0	60	0.5	3.0	160	18	10
38878	3.5	60	0.6	3.5	160	18	10





NEW 2271P

©E 60900:2012

PicoFinish electric Philips screwdriver. Handle with rotating cap and rapid-turning zone.

Individually tested protective insulation 1,000 V AC, VDE and GS tested.

DIN ISO 8764

Diaue.	DINIOC	0104.				
Order-No.	1	≕ ■	•t	==	- ÷	
38879	PH00	60	2.0	154	9	10
38880	PH0	60	3.0	160	18	10
38881	PH1	60	4.0	160	18	10





DYE 60900:2012 1000 V IEC 60900:2012

2270P K6 PicoFinish electric slotted/Phillips screwdriver set, 6-pcs. Individually tested protective insulation

1,000 V AC, VDE and GS tested.

Order-No.	Series				
38996	2270P K6				1
1	2270P	1.5x40	2.0x60	2.5x60	3.0x60
⊕	2271P	PH00x60	PH0x60		