

Technical Data Sheet

Pond Sealer - Clear

Waterproofing

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description

Pond Sealer Clear is a seamless clear sealer, designed for waterproofing new or renovated fish ponds and water features. Suitable for surfaces and structures that will not experience movement, **Pond Sealer Clear** will remain watertight under permanently wet conditions. Where there are pre-existing holes, cracks or expected movement, use one of the Pond Sealer Colour membranes.

Features and Benefits

- | | |
|--|---|
| <ul style="list-style-type: none"> • Non-toxic and safe for fish and plants • Safe and easy to apply • Excellent adhesion to substrates | <ul style="list-style-type: none"> • Quick drying • Easy to repair • UV Stable |
|--|---|

Area of Use

- | | |
|--|---|
| <ul style="list-style-type: none"> • Fish ponds | <ul style="list-style-type: none"> • Ornamental water features |
|--|---|

Technical Data

Number of Coats:	Min 3	Curing time:	7 days
Spreading Rate Per Coat:	6-10m ² /L	Colour:	Clear
Wet Film Per Coat:	750 micro	Thinner:	Water
Recoat (@25°C):	4 hours	Shelf Life:	12 months

Application Guide

Surface Preparation

- The surface should have a light even texture. Masonry should be flush pointed and all defects in existing surfaces made good. Ensure all high points and protrusions are ground off.
- Surfaces must be clean and dry, sound and free from contaminants.
- Blow-holes, areas of honeycombing, etc., to be filled and the surface brought back to an even profile with a suitable repair render. Trowel to a smooth even finish and allow to cure.
- Do not apply **Pond Sealer Clear** to wet or damp substrates – moisture content should be less than 15%. Check with a moisture meter if necessary. If dampness is present, prime surfaces with 2 coats of Dampstop.

Application Procedure and Equipment

- Mix equal parts of **Pond Sealer Clear** and water. Apply a thin, but even wet coat and allow to dry for approximately 15 minutes.
- Apply 2nd coat of unthinned **Pond Sealer Clear** over surface by brush or roller.
- Apply 3rd coat of unthinned **Pond Sealer Clear** at right angles (90°) to the 1st coat. Allow 7 days drying to ensure full cure before filling with water.

Technical Data Sheet

Pond Sealer - Clear

Waterproofing

7 Day Technical Support 1800 655 711

Precautions

- Where fish or plants are being used, thoroughly rinse the dry surface and drain prior to refilling.
- Do not apply **Pond Sealer Clear** if the temperature is below 10°C, if relative humidity is above 85% or if rain is imminent.

Cleaning

- Wash all equipment with water before product dries.

Health and Safety

Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear gloves and eye protection during application.

First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	1L,	Flash Point:	N/A
Weights:	1Kg	UN Number:	N/A
Dangerous Goods Class:	N/A		

Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.