Safety Data Sheet Hydrated Lime

Section 1: Material and Supplier Information

Product Name: Hydrated Lime

Applicable In: Australia

Other Names: Hydrated Lime

Recommended Use: Hydrated Lime can be used as neutralizing agent in water and sewage treatment, a binder in

mortars and renders, and soil stabilization.

Company Details: Independent Cement & Lime Pty Ltd

750 Lorimer Street

Port Melbourne, VIC 3207 ABN 49 005 829 550

Emergency contact details: Contact Person: Technical Manager

Telephone: Office hours 03 9676 0000 or Poison information center 13 11 26

Phone: VIC 03 9676 0000 **Fax:** VIC 03 9646 4954

This Safety Data Sheet (SDS) is issued by Independent Cement Pty Ltd in accordance with the Code and guidelines from the Australian Safety and Compensation Council (ASCC). The information in it must not be altered, deleted or added to. Independent Cement Pty Ltd will not accept any responsibility for any changes made to its SDS by any other person or organization. Independent Cement Pty Ltd will issue a new SDS when there is a change in product specifications and/ or ASCC standards, guidelines or regulations.

Section 2: Hazards Identification

Statement of This product is classified as HAZARDOUS according to Safe Work Australia criteria. Not

Classified as a dangerous good by the criteria of the ADG code, IMDG or IATA.

GHS Classifications

Skin Corrosion/ Irritation Criteria 2
Serious Eye Damage/Eye Irritation: Criteria 1
Specific Target Organ Systematic Toxicity (Repeated Exposure): Category 2

SIGNAL WORD DANGER

Pictograms



Bulk Cement Orders 1300 137 611

200 Power St Glendenning NSW 2761

New South Wales

T 02 9625 8999

F 02 9625 0470



Hazard Statements

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H318 Causes serious eye damage

H373 May cause damage to lungs and respiratory tract through prolonged or repeated exposure.

Prevention Statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection

Response Statements

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338+P321 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present.

Continue rinsing. The use of Diphoterine® has been shown to significantly reduce the risk of permanent injury. It is essential that the Diphoterine is used as quickly as possible (ie. within 10 seconds of contact

with lime) in order to obtain the maximum benefit from its absorbent and neutralising properties.

P333 + P313 If skin irritation or rash occurs get medical advice/attention.

Disposable Statements

P501 Dispose of contents/container in accordance with relevant regulations.

UN No None Allocated Hazchem Code None Pkg Group None Allocated

Allocated

DG Class None Allocated Subsidiary Risk(s) None EPG None Allocated

Allocated

Section 3: Composition / Information on Ingredients

Ingredient	Formula	Proportion	CAS Number
Calcium hydroxide	Ca(OH) ₂	85-95%	1305-62-0
Magnesium hydroxide	Mg(OH) ₂	0.5-1.5%	1309-42-8



Crystalline silica (Quartz)	SiO ₂	0.4-0.7%	14808-60-7
Aluminum Oxide	Al ₂ O ₃	0-2%	1344-28-1

Section 4: First Aid Measures

Eye: If Hydrated Lime is splashed in to the eyes flush thoroughly with flowing water until advised to

stop by a doctor If available, immediately flush eyes with Diphoterine solution

Inhalation: Remove from dusty area to fresh air. If symptoms persist, seek medical attention.

Skin: Remove heavily contaminated clothing immediately. Wash off skin thoroughly with water. A

shower may be required. Seek medical attention for persistent irritation or burning of the skin. If

available, immediately flush eyes with Diphoterine solution

Ingestion: Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute stomach

contents. If symptoms persist, seek medical attention.

Advice to Doctor: Treat symptomatically.

First Aid Facilities Eye wash station.

Additional Aggravated Medical Conditions

Information

Inhalation Over exposure resulting from prolonged and repeated inhalation of dust containing crystalline

silica can cause bronchitis, silicosis (scarring of the lung). It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin, Joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scaring of the lung) and lung cancer in persons exposed to

crystalline silica.

Skin Prolonged and repeated skin contact with Hydrated Lime powder, hydrated lime in wet concrete,

mortars and slurries may result in irritant dermatitis or alkaline burns.

Eye Irritating to the eye. If Hydrated Lime is splashed in to the eye, alkaline burns can cause

permanent damage.

Section 5: Fire Fighting

Flammability: Not flammable. Does not support combustion of other materials.

Fire and Explosion: No fire or explosion hazard exists.

Extinguishing: Non-flammable; use suitable extinguishing agent for surrounding fire

Hazchem Code: None Allocated



Procedures

Section 6: Accidental Release Measures

Spillage: If spill (bulk), contact emergency services if appropriate. Wear dust proof goggles, PVC/rubber

gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place

in sealable containers for disposal or reuse. Avoid generating dust.

Emergency Follow safety requirements for personal protection under Section 8

Exposure Controls/Personal Protection.

Section 7: Handling and Storage

Handling: Before use carefully read the product label. Use of safe work practices are recommended to

avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing

hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

Storage: Store in a cool, dry, well ventilated area, removed from

excessive moisture and heat.

Property/Environmental Refer to Section 13.

Section 8: Exposure Controls / Personal Protection

Ventilation Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation hazard

exists, mechanical extraction ventilation is recommended. Maintain dust levels below the

recommended exposure standard.

Exposure Standards Aluminum Oxide (1344-28-1)

ES-TWA: 10 mg/m³ (Respirable Dust)

Calcium hydroxide (1305-62-0)

ES-TWA: 5 mg/m3 (Respirable Dust)

Iron (III) oxide (1309-37-1)

Crystalline Silica (Quartz) (14808-60-7)

ES-TWA: 0.1 mg/m³ (Respirable Dust)

Wear dust proof goggles/safety glasses and rubber or PVC gloves. Where an inhalation risk

exists, wear a clear P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear a long sleeve shirt and full-length trouser. At high dust levels, wear a Class P3

respirator or a Powered Air Purifying Respirator (PAPR) with class P3 filter.











PPE

Section 9: Physical and Chemical Properties

AppearanceWhiteSolubility (water)100 g/L.OdorSlight odorSpecific Gravity2.1 - 2.3

pH (in water) Approximately 12 % Volatiles Not Available **Vapor Pressure Flammability** Non-Flammable Not Available Not Available **Flash Point** Not Relevant **Vapor Density Boiling Point** Not Available **Upper Explosion Limit** Not Relevant

Melting Point> 580°CLower Explosion LimitNot RelevantEvaporation RateNot AvailableAutoignition
TemperatureNot Available

Bulk Density $300 - 700 \text{ kg/m}^3$ Particle Size $99\% < 75 \text{ } \mu\text{m}$

Section 10: Stability and Reactivity

Chemical Stability: Chemically Stable

Conditions to Avoid: Keep free of moisture

Incompatible Materials Incompatible with acid (e.g. hypochlorite), maleic anhydride, nitroethane, nitromethane,

nitroparaffins, nitropropane and phosphorus.

Decomposition Products: May evolve calcium oxides when heated to decomposition

Hazardous Reactions: None

Section 11: Toxicological Information

Acute Toxicity No known toxicity data for this product.

Eyes Irritant upon contact with powder/dust. Over exposure may result in pain,

redness, corneal burns and ulceration with possible permanent damage.

Inhalation Slightly corrosive. Irritating to the respiratory system, causing coughing and

sneezing. Over exposure may result in severe mucous membrane irritation and bronchitis. Crystalline silica can cause silicosis (lung disease) with chronic over exposure, however due to low levels present and product application, adverse

health effects are not anticipated.

Skin Irritating to the skin. Prolonged and repeated contact with powder or wetted

form may result in skin rash, dermatitis and sensitisation.

Ingestion Slightly corrosive. Ingestion may result in burns to the mouth and throat, with

vomiting and abdominal pain. Due to product form, ingestion is not considered

a likely exposure route.

Mutagenicity Insufficient data available for this product to classify as a mutagen.

Carcinogenicity Hydrated Lime is not classified as a carcinogen by NOHSC.



Section 12: Ecological Information

Toxicity The aquatic toxicity of calcium hydroxide is due to its alkalinity.

Persistence and Neutralised to calcium carbonate by absorption of atmospheric carbon dioxide and is not

Degradability degraded by oxidation.

Mobility in Soil A low mobility would be expected in a landfill situation.

Section 13: Disposal Considerations

Waste Disposal Neutralise with dilute acid (e.g. 3 mol/L hydrochloric acid) or similar. For small amounts,

absorb with sand or similar and dispose of to an approved landfill site Contact the

manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation. Keep out of sewer stormwater

drains.

Section 14: Transport Information

Not classified as a dangerous good by the criteria of the ADG code.

Transport is by rail or road in bulk or bag form.

Drivers of trucks transporting bagged products should ensure that the bags are properly restrained.

Shipping Name None Allocated

UN NoNone AllocatedHazchem CodeNone AllocatedPkg GroupNone AllocatedDG ClassNone AllocatedSubsidiary Risk(s)None AllocatedEPGNone Allocated

Section 15: Regulatory Information

Poison Schedule AICS A poison schedule number has not been allocated to this product using the criteria in the

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP). All chemicals listed on the

Australian Inventory of Chemical Standards (AICS).

Section 16: Other Information

Additional Information PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The Recommendation for protective

equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the



availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

mg/m³ - Milligrams per cubic metre

ppm - Parts Per Million

ES-TWA - Exposure Standard - Time Weighted Average

CNS - Central Nervous System

NOS - Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number – used to uniquely identify chemical compounds.

IARC - International Agency for Research on Cancer.

Report StatusThis document has been compiled by Independent Cement and Lime Pty Ltd the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.

While the information in this Safety Data Sheet has been prepared in good faith, Building Product Supplies does not warrant that the information is accurate, complete or up to date.

Contact Point

For further information on this product contact:

Telephone: Office hours 03 9676 0000

Facsimile: 03 9646 4954

Web site: http://www.independentcement.com.au/

Advice Note

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

03 9676 0000

Or

www.independentcement.com.au/

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- determine whether the information or product is suitable for their purpose;
- assess and control any risks associated with the information or product; and
- obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Independent Cement and Lime Pty Ltd:

• excludes all representations, warranties and guarantees in relation to any information in this Safety Data Sheet; and



• will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Safety Data Sheet.



Safety Data Sheet Hydrated Lime