

# Technical Data Sheet

## Grout Sealer

Sealers

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description			
<p><b>Grout Sealer</b> is a revolutionary waterborne hard acrylic polymer finish. <b>Grout Sealer</b> provides a clear, transparent, non-silicone water repellent coating that will enhance and protect the appearance your grout. The hard film is resistive to water damage, disfigurement by airborne pollutants and its water repellent properties are supplemented by a highly effective biocide to inhibit the growth of fungi, algae and lichens. <b>Grout Sealer</b> is both trafficable and highly resistant to UV light.</p>			
Features and Benefits			
<ul style="list-style-type: none"> <li>• Water repellent</li> <li>• Safe and easy to use</li> <li>• Stain resistant</li> <li>• UV stable</li> </ul>		<ul style="list-style-type: none"> <li>• Biocide protected</li> <li>• Clear satin to gloss finish</li> <li>• Suitable for foot traffic</li> </ul>	
Area of Use			
<ul style="list-style-type: none"> <li>• Bathrooms</li> <li>• Living areas</li> </ul>		<ul style="list-style-type: none"> <li>• Laundries</li> </ul>	
Technical Data			
Number of Coats:	2	Recoat (@25 °C):	2 hours
Spreading Rate Per Coat:	500mL will cover an average kitchen and dining room floor	Curing time:	7 days
Wet Film Per Coat:	200 microns	Colour:	Clear
		Thinner:	N/A
		Shelf Life:	12 months
Application Guide			
<p>Surface Preparation</p> <ul style="list-style-type: none"> <li>• Clean surfaces of all contaminants such as efflorescence, mould, lichen, etc.</li> <li>• Remove all grease, dust or dirt.</li> <li>• Rinse surface with water and scrubbing brush, rinse and allow to dry thoroughly.</li> </ul> <p>Application Procedure and Equipment</p> <ul style="list-style-type: none"> <li>• May be applied by brush, or roller applicator (available at hardware outlets). Wipe excess product off the surface before product dries.</li> </ul>			
Precautions			
<ul style="list-style-type: none"> <li>• Do not apply if air or surface temperature is below 10°C, if relative humidity is above 85%.</li> <li>• Not recommended for use on glazed/glassy surfaces such as some ceramic tiles. Assess <b>Grout Sealer</b> on a small area initially to determine suitability.</li> </ul>			

# Technical Data Sheet

## Grout Sealer

Sealers

7 Day Technical Support 1800 655 711

### Cleaning

- Wash equipment with water before product dries.

### Health and Safety

#### Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear gloves and eye protection during application.

#### First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

### Transport and Storage

Sizes:	500mL	Flash Point:	N/A
Weights:	0.5Kg	UN Number:	N/A
Dangerous Goods Class:	N/A		

### Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.