



Deck

SpecRite™



Manufactured For Results.

MERBAU FJ CONCEALED FIXED DECKING

SELECT GRADE HARDWOOD-KILN DRIED-AS2796.2 2006



Available at

BUNNINGS
warehouse

Compatible
with



Ekodeck
Quickfix

- Create the ultimate deck by joining pre-grooved merbau deck pieces
- Safe, quick and easy to install - works like tongue and groove floorboards
- Pre-oiled to preserve the timber's natural colour
- Timber certified from legally verified forest sources
- Approved for use in bushfire-prone areas, compliant to BAL29
- Durability class 1 for a long life
- Naturally resistant to fungi and insects like termites and dry wood borers
- Recommended for use with Ekodeck Quickfix Decking Fastening system
- Fasteners sold separately - please consult a Bunnings team member



Australian Standard
Compliant AS/NZS 2796



Kiln Dried
Timber



Class A Bond Glue
(Weather Resistant)



Full Size
Timber



Select
Grade



MERBAU FJ CONCEALED FIXED DECKING

SELECT GRADE HARDWOOD-KILN DRIED-AS2796.2 2006

- Max joist spacing - 450mm centres
- Min ground clearance - 400mm
- Min distance from side or end to fixed structures - 7mm
- Min distance from side edge for fixings - 12mm
- Min distance from end for fixings - 12mm

Applications

Decking, fencing, screening and gates

Timber Quality

Select grade in compliance with AS2796.2-2006 and kiln dried for a long-lasting, high-quality appearance.

Fixings

SpecRite Concealed Fix Merbau Decking is compatible with Ekodeck Plus Quickfix decking fastening system. Please consult a team member at your nearest Bunnings store for assistance.

This product is designed for 'concealed fix' method of installation only. 'Top fix' method of installation should not be used on this product.

Cutting

Tungsten carbide tipped cutting tools and high quality drill bits are recommended for best results. Apply decking oil to cut ends to maximise the life of your deck. Ensure appropriate eye, ear and breathing protection is used when cutting timber.

Ventilation

A minimum ground clearance of 400mm is recommended to allow for adequate ventilation. Additional side and top ventilation is required if the deck is installed with less than 400mm clearance.

Storage

Decking should be stored flat, off the ground and protected from the weather prior to installation.

Finishing

This Merbau decking has been pre-oiled with Feast Watson Traditional Timber Oil. To prolong the life of your product and maintain its premium look, apply 2 finishing coats of an oil based Feast Watson decking product.

Step 1 - Clean surface with Feast Watson Woodclean

Step 2 - Apply 2 finishing coats of an oil based Feast Watson decking product

Important - To finish with a water-based decking product, prepare Merbau by first washing with Intergrain PowerPrep followed by cleaning surface with Intergrain Reviva, check surface is ready for coating by performing a water bead test and sprinkling water on the timber. If the water is absorbed into the timber it is ready for coating, then finish with Intergrain UltraDeck.

Warning: Merbau has tannin, a naturally occurring substance which will leach the first few times it is exposed to moisture. A thorough and regular hose down during the first few days will assist with flushing excess tannin away.

Warning: Do not burn off-cuts



9 318757 053882

Available at
BUNNINGS
warehouse