

# PORION

## Exterior Flexible Filler

Single Pack

## Flexible Exterior Filler

The one that never lets go!



### Repairs • Patches • Fills


Always keep a tub of **PORION** in the workshop - it has so many uses for exterior\* jobs that need a flexible filler. Use **PORION** on decks, window frames, etc to repair rotten timber and masonry. **PORION** is unaffected by temperature and won't crack with vibration. Paint to match surrounds when dry.

### Application Tips for Porion Success:

- Always stir vigorously before use.
- To make **PORION** more workable you can add a few drops of water - but only a few drops.
- For a satin-smooth finish, smooth the final application of **PORION** with a wet knife or brush.
- When using as a filler remember **PORION** sets very hard. To avoid excessive rubbing down, do not use too much or overfill the hole. For smoothing off when set, rub down with dry emery paper.
- With deep holes, apply **PORION** in several thin layers rather than one thick one. Drying time: - 2 hours.
- Frost does not affect **PORION** when set but **PORION** should be stored in a frost-free place and should not be used when the temperature is below 5°C.

\*For interior\* jobs, use Timbermate Water-based Woodfiller (see separate flyer).

### For Timber & Masonry




Patching

Cut away decay wood (or use Earl's WOOD HARDENER) until only sound timber is left. **PORION** is easily moulded into the shape of the original timber and makes a perfect repair if smoothed and painted or stained.



Masonry Fillings

**PORION** is ideal for sealing around pipes because it won't crack with temperature changes or vibration. For central heating pipes no longer than 6 metres, wind plastic foil e.g. polythene sheet, around pipe to allow movement through the seal when heating up and cooling down.



Rotted Timber

Use **PORION** just like putty. **PORION** is more resistant to rain than putty and will never shrink, crack or fall out once applied. To remove **PORION** from broken glass, soften with a blow lamp. To repair rotten wood, use Earl's WOOD HARDENER.



Timber Imperfections

Use **PORION** for filling nail holes and repairing knot holes, etc on decks. Add the colourant to the **PORION** to match. Fill holes, not more than 5mm at a time. Fill and allow to dry.

**Note: When dry, PORION will not absorb stain.**

Colour	500gram	1kg	5kg	15kg
Grey	PG05 8710405261471	PG1 8710405260221	PG5 8710405260238	PG15 8710405260245
White	PW05 9317354160900	PW1 9317354161006	PWH5 8710405262461	PWH15 9315284151500

Distributed by Timbermate Products Pty Ltd

Phone (03) 9873 4811 or call  
Toll Free 1800 354 811 (Except Mobiles)