

Technical Data Sheet

AquaBlock

Sealing

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description	
<p>AquaBlock Waterproof is a high cover surface sealer with exceptional water resistant properties. AquaBlock will cover, seal and leave a paintable water resistant coating to all surfaces prior to top coating with water based acrylic paints.</p>	
Features and Benefits	
<ul style="list-style-type: none"> • Excellent adhesion to porous and non porous surfaces. • Seals off stains. • Excellent coverage. 	<ul style="list-style-type: none"> • Provides a 'level playing field' for topcoats. • May be sanded. • Low odour.
Areas of Use	
<ul style="list-style-type: none"> • Bathrooms • Laundries • Eaves 	<ul style="list-style-type: none"> • Kitchens • Hallways • Interior and exterior
Technical Data	
<p>Number of Coats: 1-2</p> <p>Spreading Rate Per Coat:</p> <p>1st Coat 12-14m²/L</p> <p>2nd Coat 12-14m²/L</p> <p>Wet Film Per Coat: N/A</p>	<p>Recoat (@25°C): 1-2 hour</p> <p>Colour: White</p> <p>Curing time: 12 hours</p> <p>Shelf Life: 12 months</p>
Application Guide	
<p>Surface Preparation</p> <ul style="list-style-type: none"> • Ensure all surfaces are clean, dry and free of contaminants. • Any loose, friable and or water damaged surfaces should be removed and repaired. • To achieve maximum adhesion and performance all surfaces must be dry prior to application. <p>Application Procedure and Equipment</p> <ul style="list-style-type: none"> • Due to the wide variety of surfaces a test patch should be applied prior to full application. • AquaBlock is best applied with a good quality medium nap roller or brush. • Apply AquaBlock following specified coverage rates leaving a smooth and consistent finish. • To ensure maximum water resistance a second coat should be applied. 	
Precautions	
<ul style="list-style-type: none"> • Do not apply if the temperature is below 10°C, if relative humidity is above 85%. • Do not apply to wet substrates – moisture content should be less than 15%. Check with a moisture meter if necessary. 	
Cleaning and Maintenance	
<ul style="list-style-type: none"> • Application equipment can be cleaned with water before product dries. 	

Technical Data Sheet

AquaBlock

Sealing

7 Day Technical Support 1800 655 711

Health and Safety

Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- If product is splashed on skin it should be washed off with water before it can dry.
 - Wear gloves and eye protection during application

First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.
 Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin®.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	1L, 2L, 4L, 10L	Flash Point:	N/A
Weights:	1.4kg, 2.8kg, 5.6kg, 14kg	UN Number:	N/A
Dangerous Goods Class:	N/A	Poisons Schedule:	N/A

Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.