

Caroma®

Revision: 1.0

Date: June 2017

Supersedes all previous issues

Sahara II

3.26.1

Vitreous China 4.5/3 litre Dual Flush
Wall Faced Close-Coupled Toilet Suite



Caroma®

Sahara II

Vitreous China 4.5/3 litre Dual Flush Wall Faced Close-Coupled Toilet Suite



A softened geometric designed wall faced toilet suite conceals plumbing fittings for a clean and modern look. The pan connection system includes the patented Caroma Uni-Orbital® Connector for increased installation flexibility. The Caroma Uni-Orbital® Connector extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 195mm with a recommended setout of 140mm.

- Pan:** Sahara II 4.5 litre full flush washdown pan with box rim.
- Traps:** Universal trap for S or P-trap installations.
- Cisterns:** Sahara II cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard bottom inlet with optional back entry conversion kit.
Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. For back entry installation, accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.
- Fixing:** The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.
- Seats:** The Sahara soft close seat is provided as standard with the Sahara suite. The seat features a easy quick release mechanism that allows for cleaning. A quality solid section compression moulded toilet seat, fitted with buffers and metal hinges.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

