

© CrommelinWaterproofing



How to seal fish ponds

CROMMELIN POND SEALER is a water based permanent solution to seal fishponds and ornamental pools.

How to seal fish ponds

Ideal for all ornamental and commercial ponds, POND SEALER is available in a range of colours as well as clear. It is easily applied and will transform your plain pond in to a decorative garden feature.



YOU WILL NEED

1 litre of POND SEALER will cover approximately 0.75m² of pond.
1 litre of POND SEALER CLEAR will cover approximately 3-5m².



EQUIPMENT

POND SEALER is easily applied with a paint brush or roller.



NUMBER OF COATS

A minimum of 2 coats are required and should be applied at 90° to each other. A third coat may be required to reach the specified thickness.



DRYING TIME

Allow 2 hours between coats.
Allow 7 days to fully cure before filling your pond.



CLEAN UP

POND SEALER is easily cleaned up with water before it dries.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

Crommelin

SOLUTIONS FOR CONSTRUCTION



Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is proven defective, our liability is limited to the replacement of the product.