

## Line Marking Paint



Dy-Mark's Line Marking Paint is a fast drying acrylic paint, specially formulated to provide long lasting lines. Line Marking Paint is designed for use with the Dy-Mark Line Master and ideal for marking on car parks, factories, warehouses, sporting fields and courts.

### DIRECTIONS FOR USE

#### Preparation

Shake can for at least 20 seconds after the mixing ball begins to rattle.

#### Application

Insert can into the Line Marking Machine's Spot Marking Handle. To achieve the narrowest line width, the spot marking handle must be inserted into the lowest position. Line width can be increased by raising handle in slot. Line width ranges between approx. 60mm and 100mm. Test line width by marking on cardboard until desired width is achieved. Masking wheels are designed to sharpen lines by catching any overspray at the edges only.

### TECHNICAL DATA

<b>Size:</b>	500g Aerosol
<b>Finish:</b>	Matt
<b>Colour:</b>	8 Standard Colours
<b>Consistency:</b>	Liquid
<b>Coverage:</b>	80 – 100 metres of line per aerosol can (depending on line width)
<b>Suitable Surfaces:</b>	Concrete, bitumen, grass, soil, timber
<b>Drying Time:</b>	10 minutes at 25°C
<b>Ideal Application Temperature:</b>	Between 5°C and 40°C

### STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions. Protect aerosol cans against physical damage.

### DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

### SAFETY INFORMATION

#### HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

Please note that the slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, correct application and environmental conditions.

Dy-Mark recommends a risk assessment prior to use to determine if the product is suitable to the:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants e.g. water, solvents or chemicals

For more information regarding the product's slip resistance, please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.

### FIRST AID

#### KEEP OUT OF REACH OF CHILDREN

**If swallowed:** Do not induce vomiting.

**Eye contact:** In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

**Note:** the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.