



CARPET & CORK ADHESIVE

DUNLOP CARPET & CORK ADHESIVE is a water based, high strength adhesive that is suitable for use over a range of surfaces such as concrete, marine ply and fibre-cement sheet.



SUITABLE SURFACES

Concrete, marine plywood, fibre-cement sheet.

SURFACE PREPARATION

Surfaces must be dry, smooth, clean and free of any contaminants that may limit adhesion to the subfloor. The surface must be protected from moisture. Highly porous concrete or timber subfloors should be primed with DUNLOP PRIMER AND ADDITIVE before applying adhesive. Imperfections in the subfloor can be fixed using either DUNLOP FLOOR LEVELLERS or DUNLOP FLOOR REPAIRERS. The adhesive should not be applied in extremely hot or cold conditions (i.e. below 10°C or above 30°C).

APPLICATION

- 1 For smooth backed carpets or cork tiles use a 2.4 x 2.4 x 2.4mm "V" Notched trowel and for textured backed carpets use a 3.2 x 1.6 x 3.2mm "V" notched trowel.
- 2 Spread adhesive onto the subfloor, forming an even coat with the recommended trowel size.
- 3 Install carpet immediately into the wet adhesive. Cut, fit and reposition carpet within 60 minutes. For cork and carpet with stiff backing, allow the adhesive to become tacky for 10-15 minutes before laying the cork/carpet.
- 4 Roll the carpet/cork in both directions with suitable drum roller as per manufacturer's recommendation to ensure 100% adhesive transfer.
- 5 Do not allow traffic for 24 hours and heavy traffic for 48 hours. Do not expose to water from cleaning or other source for 48 hours.

Note: Drying times will be slower when temperature is below 10°C and faster if above 30°C.

COVERAGE

1 litre of DUNLOP CARPET & CORK ADHESIVE will cover approximately 2.5m² with a 3.2mm "V" notch trowel or 3.5m² with a 2.4mm "V" notch trowel. Coverage will vary depending on the condition of the subfloor and application technique.

CLEAN UP

Clean tools and equipment immediately after use, with soapy water. Dried adhesive can be removed with mineral turps.

SHELF LIFE

A shelf life of 12 months is expected when stored in an unopened container at 23°C.

PRECAUTIONS

Always ensure there is adequate ventilation when using the adhesive. Material Safety Data Sheet (MSDS) available on the Dunlop website.

SAFETY

Avoid eye and skin contact. If eye contact occurs, flush with water for at least 15 minutes and seek medical attention. Wash skin thoroughly with soap and water. If swallowed, do not induce vomiting, call doctor immediately.

TOLL FREE HOTLINE

1800 222 841 (Aust) 0800 224 070 (NZ)
www.dunlopdjy.com

Made under license.
Ardex Australia Pty Ltd
ABN 82 000 550 005
20 Powers Road
SEVEN HILLS NSW 2147
Australia
Ph: +61 2 9851 9199