



# Petrol High Pressure Cleaner Quick Start Guide

## RPW3200Y

**WARNING:** This procedure sheet is not a substitute for reading the operator's manual. To reduce the risk of injury, the user must read and understand the operator's manual before using the product.

### PUMP QUICK START

- 1 Connect garden hose and high pressure hose to pump.
- 2 Connect high pressure hose to trigger handle.
- 3 Connect trigger handle to spray wand.
- 4 Connect 0 DEG, or 25 DEG, or 40 DEG spray nozzle to spray wand.
- 5 Turn water on.
- 6 Hold trigger for 30 seconds.  
*NOTE: Squeeze trigger prior to start. Minimum garden hose diameter is 18mm (3/4 in.).*

### ENGINE QUICK START

- 7 Switch engine to OFF.
- 8 Close the fuel valve.
- 9 Check the engine oil. When the dipstick oil cap is placed inside the filler, do not re-thread. The oil should be visible between the minimum and maximum marks.
- 10 Check the fuel. Always use fresh, unleaded (91 or higher) fuel.  
*NOTE: Fuel without fuel stabiliser added to it begins to turn stale from 30 days onwards.*
- 11 Switch engine to ON and open fuel valve.

- 12 Pull choke to **START**.  
*NOTE: If engine is hot, push to RUN.*
- 13 Start engine. Do not pull the starter grip more than 4 times.  
*REPEAT STEP 6*
- 14 Let the engine run for 30 seconds, then gradually push choke to **RUN**.

### SOAP USE

- NOTE: Soap dispenses with soap nozzles only!*
- 1 Pour soap into soap tank.
  - 2 Connect soap nozzle to spray wand.
  - 3 Pull trigger to dispense.

### SHUT DOWN

- 1 Switch engine to OFF.
- 2 Close fuel valve.
- 3 Flush unit by squeezing trigger. Turn off water.
- 4 Remove high pressure hose and garden hose.

