

# ORION FREESTANDING INSTALLATION INSTRUCTIONS

## QLD - HEAD OFFICE

Decina Bathroomware Pty Ltd  
99 Cobalt Street  
CAROLE PARK QLD 4300

T: (07) 3271 1944  
F: (07) 3879 4244

## NSW/ACT

Decina Bathroomware Pty Ltd  
8/17 Stanton Road  
SEVEN HILLS NSW 2147

T: (02) 9838 4944  
F: (02) 9838 9055

## VIC

Decina Bathroomware Pty Ltd  
36-40 Villas Road  
Dandenong South VIC 3175

T: (03) 9768 3768  
F: (03) 9768 3769

## WA/NT

Decina Bathroomware Pty Ltd  
3/44 Hutton Street  
Osborne Park WA 6017

T: (08) 9242 4766  
F: (08) 9242 4733

## SA

Decina Bathroomware Pty Ltd  
109B Morphett Road  
Camden Park SA 5038

T: (08) 8376 6233  
F: (08) 8376 6211

## TAS

P. D. Trading  
4/46 Mornington Road  
Hobart TAS 7018

T: (03) 6245 9008  
F: (03) 6245 9002

## NTH QLD

N.B. Agencies  
56 Leigh Street  
West End Townsville QLD 4810

T: (07) 4771 3400  
F: (07) 4771 4955

Website: [www.decina.com.au](http://www.decina.com.au)




 100%  
australian  
made & owned

**DECINA**  
BATHROOMWARE  
*relaxing your senses*

## SKIRT REMOVAL



1. Begin at the skirt gap



2. Pull edge towards you to separate.



3. Gradually work your way anti-clockwise, peeling off the skirt.


## BATH/SPA BATH INSTALLATION



1. Fit waste and prepare the waste plumbing. If using an offset connector, Decina recommend a through connector.




2. Place bath in its final position for height adjustment. **Please note that the bath weighs 100kgs and the spa weighs 125kgs,** so adequate provisions for safe lifting must be made.




3. For the neatest appearance, height from the floor to the underside of the rim should be between 535mm and 538mm. This height may be more, but the result will be a larger gap between the skirt and the floor.



4. Adjust the four support feet to achieve the correct height.




5. Adjust the two holding feet to match the correct height and align in a convenient location for drilling.



6. Fix to the floor with appropriate fasteners.


## SKIRT INSTALLATION



1. Choose the position of the skirt join and place the clipped magnet on the bottom rail, below the fixed magnets on the right hand side. Place the second clipped magnet on the opposite side of the bath to the first.



2. Bring the recessed end of the skirt toward the bath so the top lip fits tightly under the bath rim but above the bath frame.




3. The edge should be located close to but not over the second magnet.



4. Work around the bath in a clockwise direction, pushing the skirt to the bath. Ensure that the top lip remains at the correct height.



5. Leave the end slightly open, checking to ensure the clipped magnet will line up to the steel square on the skirt.




6. Push the joint to the bath and continue working in a clockwise direction, ensuring the lip height remains correct.



7. Push the joint to the bath and continue working in a clockwise direction, ensuring the lip height remains correct.



8. Continue to the end of the skirt.



9. Push the end against the bath and inspect the skirt to see if it is sitting correctly the whole way around.