

SADOLIN Hardwood Oil



Unique product formulated to penetrate & protect wooden garden furniture.

Enhances the natural beauty of the wood
Easy to apply
Excellent absorption characteristics

- Product Description:**
- * Sadolin Hardwood Oil is a premium high quality hardwood oil developed to offer added benefits to those normally associated with traditional wood protection.
 - * Sadolin Hardwood Oil absorbs deeply into the surface of most timber species and provides protection against the weather.
 - * Sadolin Hardwood Oil is water repellent and is especially suitable for exterior hardwood surfaces where a natural appearance is required.
- Use:**
- * Sadolin Hardwood Oil is recommended for wooden garden furniture.
- Colour Range:**
1. Natural Teak
 2. Colourless
- Preparation:**
- * Sadolin Hardwood Oil is recommended for use on bare timber, as well as timber surfaces which were previously coated with other oil treatments or timber coatings that do not provide a surface film build e.g. preservative pre-treatments.
 - * Ensure that the timber is clean, dry and free from grease. Timber species that contain high levels of natural oils or extractives (e.g. Teak, Iroko, Merbau, Kwila, Blackbutt etc) should be thoroughly degreased / seasoned prior to treating with Sadolin Hardwood Oil.
 - * For best results, leave your furniture outside in the weather for 8 to 12 weeks. If it doesn't rain during this time, or if the setting is in a protected position, hose it down thoroughly twice each week. This process will extract the tannins / oil and dust out of the wood effectively.
 - * Prepare the surface by abrading with sandpaper and if necessary use a wood cleaner to remove any discolouration.
 - * Preservative pre-treatments must also be fully dried before the application of Sadolin Hardwood Oil.
- Application:**
- * Stir well before and during application and apply by cloth (preferably) or brush. Do not apply at temperatures below 5°C. Do not thin.
 - * Apply one coat of Sadolin Hardwood Oil and allow it to dry for 5 to 30 minutes depending on the temperature and humidity. Remove any residue of Sadolin Hardwood Oil, which has not been absorbed, by gently wiping with a cloth. This will help to prevent "glossy" blemishes on the surface.
 - * For maximum durability, apply at least 2 coats of Sadolin Hardwood Oil to all surfaces.
 - * As & when lustre diminishes, clean down and apply a further coat.
 - * NB: The colourless version does not contain UV inhibitors and is therefore less durable than the Natural Teak.
- Coverage:**
- * Approximately 15-18 m²/litre on smooth wood.
- Packaging:**
- * 750ml & 2¹/₂ litres
- Drying Time:**
- * Touch dry: 4-6 hours.
 - * Repainting: Subsequent coats can be applied after 12-24 hours
- Cleaning:**
- * Clean brushes immediately after use with Mineral Turps then soapy water
- Important Information:**
- Protect from frost.
 - Shelf life: (Unopened) at least 5 years from production date.