

Technical Data Sheet



Tint

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description

DiamondCoat Tint is a tinting system designed to be used in conjunction with DiamondCoat Tintable Sealer by providing a colour alternative to rejuvenating aged concrete and masonry. When used in conjunction with DiamondCoat Tintable Sealer is an ideal alternative to paving paints.

Features and Benefits

- | | |
|--|---|
| <ul style="list-style-type: none"> • 1L tint to 8L DiamondCoat Tintable Sealer • Available in 4 colours • Resists oils, grease and general dirt pick up | <ul style="list-style-type: none"> • 1 coat system provides a wash of colour • 2 coat system is needed to achieve opacity • Colour penetrates up 2mm |
|--|---|

Areas of Use

- | | |
|--|--|
| <ul style="list-style-type: none"> • All previously uncoated areas of concrete requiring a stain-resistant durable coloured finish • Domestic walkways and driveways • Warehouse floors | <ul style="list-style-type: none"> • Garage and house floors • Pedestrian areas • Pattern concrete • Stencilled concrete |
|--|--|

Technical Data

<p>Number of Coats: 2 (for solid colour)</p> <p>Spreading Rate Per Coat:</p> <p>1st Coat (thinned 10%) 4 – 12 m²/L</p> <p>2nd Coat 4 – 12 ²/L</p> <p>Wet Film Per Coat: 85 - 265 microns</p> <p>Recoat (@25°C): Min. 4 hours</p>	<p>Curing time: 7 days</p> <p>Colour: Charcoal, Mid Grey, Terracotta, Warm Sand</p> <p>Thinner: Not Required</p> <p>Shelf Life: 12 months</p>
--	---

Application Guide

Surface Preparation

- Refer to DiamondCoat Tintable Sealer Technical Data Sheets

Application Procedure and Equipment

- The correct quantity of DiamondCoat Tint needs to be added to the correct size container.
- This should be stirred thoroughly for 10 minutes ensuring no air is entrained.
- Sealing of sloping surfaces may increase the potential for pedestrians to slip. DiamondCoat Anti Slip can be added to provide an improved slip resistant profile. Please ensure to follow the 'Application Procedure and Equipment' method, stated in DiamondCoat Anti Slip technical data sheet.
- Do not apply if temperate is over 35°C or under 5°C. Where hot windy conditions occur, apply in the morning.
- If necessary thin using DiamondCoat Solvent

Technical Data Sheet



Tint

7 Day Technical Support 1800 655 711

Precautions

- Do not apply if humidity is above 85% or if rain is imminent.
- DiamondCoat Tint may increase the slipperiness depending on the surface and the quantities of sealer used.

Cleaning

- Equipment can be cleaned with DiamondCoat Solvent.

Health and Safety

Safety Precautions

- Avoid breathing vapor. Wear organic vapor respirator meeting the requirements of AS1715 and AS1716.
- Provide good ventilation – open windows and doors and use circulating fans.
- Wear eye protection.
- Wear PVC or neoprene gloves. Avoid contact with skin.
- If product is splashed on skin it should be washed off with water before it can dry.
- Keep out of the reach of children.

First Aid

- Swallowed: If poisoning occurs contact a doctor or Poisons Information Centre. Do not induce vomiting. Risk of aspiration into lungs. Give water to drink.
- Eye: Gently flush with running water, holding eyelids open for 15 minutes. Seek medical attention.
- Skin: Remove contaminated clothing and gently flush affected areas with soap and water. Seek medical attention if irritation develops. Launder clothing before re-use.
- Inhalation: Remove patient from exposure, into fresh air. Apply artificial respiration if patient has stopped breathing. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin®.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	1L,	Flash Point:	43°C
Weights:	1.5Kg	UN Number:	1263
Dangerous Goods Class:	3.2	Poisons Schedule:	5
Hazchem Code:	3 (Y)		

Technical Data Sheet



Tint

7 Day Technical Support 1800 655 711

Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.