

Product Spotlight Sheet

Reflecta-Shield Plus™

greenguide


features and benefits reference



Phone: 1300 308 165 Fax: 1300 308 164

Web: gibuildingsciences.com.au

Reflecta-Shield Plus[™] the original



Performance Comparison of Reflecta-Shield Plus™ to Competing Insulation Materials Flat Metal Roof 0-5° & Flat Plasterboard Ceiling				
Insulation		Summer (Downwards)	Winter (Upwards)	Thermal Break
1*	GI Building Sciences™ Reflecta-Shield Plus™	RT 3.1	RT 1.2	0.10
2*	60mm Glasswool Roofing Blanket	RT 3.5	RT 2.1	0.20
3*	Kingspan Insulbreak 65	RT 3.2	RT 1.4	0.20

- 1. Thermal calculations for GI products by James Fricker as per AS/NZS 4859.1&2 Airspace 40mm & 300mm
 2. Glasswool R Values source the Insulation Council of Australia & New Zealand Insulation Handbook VZ, Jan 2015 Airspace 300mm
 3. Kingspan RValues source Kingspan Section J Compliance Solutions Brochure Issue 2, October 2013 Airspace Range 100 1200mm

- **Reflecta-Shield Plus™** and other thermos-cellular insulation materials have now been used by the building industry for well over 20 years.
- Initially designed as an alternative to fibrous insulation materials Reflecta-Shield Plus™ has continually proven to outperform conventional insulation materials and demonstrate greater longevity under harsh Australian climate conditions.

Suitable for almost every building type commercial or domestic, Reflecta-Shield Plus™ offers great performance benefits for almost every building application.

Features – Fact vs Fiction

- 15 Year Warranty
- ☐ Suitable for use in Residential & Commercial Walls & Roofs
- ☐ Class 2 Vapour Barrier
- ☐ 30m x 1500mm Roll
- ☐ AS 1530.2 & AS/NZS 1530.3 Compliant
- Structure enables it and Other Cellular Materials to be easily installed

Key Benefits

- ☐ A Good medium for managing condensation
- □ 1500mm Wide reduces Wastage compared to the 1350mm Wide Foam Product
- □ Fully Recyclable
- □ Able to be Cut to Length for Major Projects
- ☐ Cost of Raw Materials More Stable than Foam ensuring Long Term Cost Competitiveness
- □ The Entry Level all-rounder suited to Commercial, Domestic or Shed Construction Projects

Products are to be stored standing upright and on pallets not more than two high. Product warranty is voided for any product stored horizontally resulting in squeeze or crush. Returns of product displaying effects of deformation due to incorrect storage practices will not be accepted.









