

DATASHEET

JOHNSTONE'S PROFESSIONAL Timber Stripper



Timber Stripper

Fast acting, low odour timber finish and paint remover for interior / exterior.

FEATURES AND BENEFITS

| | |
|---------------------|---|
| IDEAL SURFACE | Most exterior and interior timber surfaces. Note: Not suitable for epoxies and 2-Pack oil based coatings. Do not use on plastic surfaces, vinyl, masonite or rubber |
| USES | Removing most water and oil based timber coatings including acrylics, polyurethanes and varnishes |
| WATER BASED FORMULA | Yes |
| EASE OF APPLICATION | The application properties of Johnstone's make it easy to apply to all timber substrates |
| AUSTRALIAN MADE | Yes |

PRODUCT SPECIFICATIONS

| | |
|----------------------|---|
| CLEAN UP | Water |
| VOC LEVEL | 600g per litre |
| DRY TIMES: TOUCH DRY | Do not let product dry on timber surface |
| DRY TIMES: RECOAT | Do not let product dry on timber surface |
| RECOMMENDED COATS | 1 |
| COVERAGE | Approximately 0.5 square meters per litre when applied 2mm thick on a horizontal surface. |
| PACK SIZES | 1L, 4L |
| COLOUR RANGE | Clear |

DATASHEET

SURFACE PREPARATION

| | |
|--|---|
| NEW HARDWOOD | Ensure coated timber surface is dry, clean and free from dirt and debris prior to application |
| SOFTWOODS: TREATED PINE & WESTERN RED CEDAR | Ensure coated timber surface is dry, clean and free from dirt and debris prior to application |
| PREVIOUSLY PAINTED OR VARNISHED TIMBER | Ensure coated timber surface is dry, clean and free from dirt and debris prior to application |
| PREVIOUSLY STAINED OR OILED TIMBER | Ensure coated timber surface is dry, clean and free from dirt and debris prior to application |

APPLICATION

| | |
|----------------------------|---|
| EQUIPMENT | Brush |
| APPLICATION METHODS | Apply a thick coat by synthetic bristle brush. Do not exceed coverage rates. Take care on vertical or overhanging surfaces as Johnstone's Professional Timber Stripper may drip. Allow 15 – 20 minutes to penetrate and soften or wrinkle the coating. Stripping times will vary depending on the type of finish, thickness of the coating to be removed and age of the coating. Test with a paint scraper to ensure that the coating is easily removed. Remove old coating using a paint scraper or if appropriate, a high pressure water cleaner for large exterior projects. On timber surfaces, work in the direction of the timber grain. On curved, rough surfaces or mouldings, use a synthetic hard bristle brush or scourer. IMPORTANT: The stripper remains active while in a wet state. Do not allow Johnstone's Professional Timber Stripper to dry on the surface. For best results, cover with a plastic drop sheet to stop stripper from drying out and work in small area's at a time. Thick or stubborn coatings may require more than one application to completely remove. Sand as necessary to remove any residue before refinishing the surface. Clean stripped surfaces thoroughly with water and allow top dry. |

PRECAUTIONS

| | |
|-----------------------------|--|
| STORAGE INFORMATION | Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5°C temperature. Keep containers sealed when not in use |
| SAFETY AND FIRST AID | <p>KEEP OUT OF REACH OF CHILDREN Avoid skin and eye contact. Provide adequate ventilation. If using inside, keep windows and doors open during application and drying time</p> <p>IF SWALLOWED: Give plenty of water to drink. Seek medical advice EYE CONTACT: Rinse with plenty of running water. Seek medical advice if irritation occurs</p> <p>24 HOUR MEDICAL EMERGENCY RESPONSE SERVICE CALL: AUSTRALIA: 1800 883 254 NEW ZEALAND: 0800 000 096</p> |
| ENVIRONMENTAL INFO | Johnstone's Timber Stripper is free from Methylene Chloride and NMP which are found in most traditional paint and varnish strippers. This makes Johnstone's Timber Stripper safer for interior usage and gentler on the environment when compared to these traditional strippers. Do not pour left over content down the drain. Unwanted material should be brushed out on newspaper allowed to dry then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first |
| VENTILATION | When using in an interior environment allow suitable ventilation |

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Customer Service Australia on 131 686 or info@johnstoneswoodcare.com.au.

PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Customer Service Australia: 131 686 Further information: www.johnstoneswoodcare.com.au Email: info@johnstoneswoodcare.com.au