



OIL PRODUCTS

Diggers Raw Linseed Oil

DESCRIPTION

Diggers Raw Linseed Oil is 100% NATURAL oil obtained by pressing seeds of the flax plant.

TYPICAL USES

- Timber sealer and protector
- Outdoor timber fences/gazebos
- Outdoor furniture oil
- Untreated cricket bats
- Not suitable for sealed/finished timber surfaces

FEATURES

- 100% Raw Linseed Oil
- Longest drying time
- Creates a finish that is generally impervious to water, heat, scratches and most stains
- Light stain on pale woods

APPLICATION

- 1. Clean and dry surface. Mix **Diggers Raw Linseed Oil** 50:50 with **Diggers Mineral Turpentine** for increased timber protection.
- Apply two coats with a brush, roller or spray gun. Diggers Raw Linseed Oil is the longest drying linseed oil and should be applied in very thin coats and rubbed well into the wood. It is important to allow drying time between coats. Clean excess oil with a clean lint free cloth to avoid the surface drying sticky.

How does Linseed Oil work? When linseed oil is applied to a porous surface it fills the pores and as it is exposed to the air it gels to form a protective film. The film is generally impervious to water, heat, scratches and most stains.

NOTE: Soak rags in water as spontaneous ignition may occur on drying. Dispose of rags by controlled incineration or at an approved landfill.

SAFETY

Wear suitable protective clothing, gloves and eye/face protection when using this product.

Code	Pack Size	Unit Barcode	Carton Barcode	Ctn/Plt
16404-61DIG	6 x 1 litre	9311052002616	19311052002613	112
16404-4DIG	4 x 4 litre	9311052000148	19312852002063	48
16404-20	1 x 20 litre	9312852836623	N/A	32

QUEENSLAND Tel +61 7 3308 5200 Fax +61 7 3308 5201 NEW SOUTH WALES Tel +61 2 8709 9600 Fax +61 2 9791 5066 **VICTORIA** Tel +61 3 9408 4144 Fax +61 3 9408 4155

SOUTH AUSTRALIA Tel +61 8 8222 1333 Fax +61 8 8260 7883 WESTERN AUSTRALIA Tel +61 8 9352 3000 Fax +61 8 9352 3033

© Copyright Recochem Inc. All rights reserved. All content remains the property of Recochem Inc. All other trademarks mentioned are trademarks or registered trademarks of their respective owners. All text, images, graphics and PDF files are subject to the copyrights and intellectual property rights of Recochem Inc. Separate to the purpose of review and private use, this information cannot be used without written permission from Recochem. Information contained herein is for general information only and should not be used as an infallible to a product's specification and or performance.

Typical Characteristics

Appearancegolder	n-brown			
visco	ous fluid			
Specific Gravity	0.92			
Flash Point	150°C			
Auto Ignition Point	350°C			
🗊 SDS available				

