



# Ready-to-Go RENDER



A Ready-to Go Render which has been premixed to an optimal consistency. Suitable for indoor and outdoor projects over a wide variety of surfaces including brickwork, AAC blocks, FC sheet and concrete, the easy trowel, easy float formulation of Dunlop renders makes it perfect for the DIYers and Trade alike.

## APPLICATION RANGE

Suitable for rendering walls, both indoor and outdoor, at an application thickness from 1-5 mm.

It can be applied over the following surfaces:

- Brickwork
- Blue board
- Concrete blockwork
- Concrete walls
- AAC (autoclaved aerated concrete) panels and blocks

If a higher build is required on an uneven surface, use DUNLOP MULTIPURPOSE ACRYLIC RENDER as a base coat and use DUNLOP Ready-to-Go RENDER as a finishing coat.

## SURFACE PREPARATION

Clean off dust, oil, grease and all loose contaminating materials or coatings. Green concrete should be allowed to cure for 28 days prior to rendering.

If dry and porous, dampen the surface to be rendered by brushing or sponging the surface or applying a light mist spray of water to prevent rapid drying of the render.

Jointing of all FC sheet and blueboard should be carried out as per manufacturers instructions.

## MIXING

No mixing required.

## APPLICATION

- 1 Apply the render with a steel trowel, evenly spreading the mix over the surface.
- 2 After 10-30 minutes, depending on ambient and surface conditions, work can begin on the surface finish. The surface finish can be dense and smooth by using a wooden or plastic float or coarse and sandy by using a sponge to give the required effect.

## FINISHING

After 10-30 minutes, depending on ambient and surface conditions, work can begin on the surface finish. The surface finish can be dense and smooth by using a wooden or plastic float or coarse and sandy by using a sponge to give the required effect. The roll-on mix and a textured roller can be used to achieve a textured surface finish.

## DRYING TIME

The render surface is touch dry in 2-4 hours @ 23°C. A second coat may be applied after 24 hours and the surface will reach full cure after 7 days. Before application of a decorative finish (i.e. paint) allow the render to cure for a minimum of 1 day for each 2mm thickness of the render. It is recommended that Ready-to-Go RENDER is overcoated with a quality acrylic paint to protect the finished surface from dust and wind borne contaminants that can adversely effect the appearance and longevity of the surface. Cold, damp or humid conditions may lengthen the drying time.

## COVERAGE

Coverage will vary depending on the condition of the surface and site conditions. As a guide, 16kg of DUNLOP Ready-to-Go RENDER will cover approximately 6m<sup>2</sup> at 1mm thickness or 2m<sup>2</sup> at 3mm thickness.

## CLEAN UP

Clean all tools in water immediately after use.

## SHELF LIFE

12 months when stored in a dry place, in original unopened packaging.

## PRECAUTIONS

DUNLOP Ready-to-Go RENDER is not suitable for use over floors and is not suitable for application over painted surfaces. Do not apply in temperatures below 5°C or above 35°C or application in extreme conditions such as high wind or direct sunlight. Protect the render from rain after application for 48 hours.

## SAFETY DATA

The presence of cement in the product gives an alkaline mortar which may cause some irritation if prolonged contact with skin takes place. Keep out of the reach of children. Use gloves to prevent skin irritation. Avoid inhaling dust by using a dust mask. Wash immediately with plenty of water if material enters the eyes. Additional information is in the Material Safety Data Sheet (MSDS) available at [www.dunlopdij.com](http://www.dunlopdij.com)



# Ready-to-Go RENDER

## DUNLOP GUARANTEE

Product is guaranteed for 10 years when installed to manufacturers instructions. Manufactured under a quality system certified as complying with ISO 9001 by an accredited certification body.

## USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.

## TECHNICAL INFORMATION

### Product Characteristics

Colour White

### Characteristics of Mix

Ready-mixed

### Application Properties

Touch Dry 2-4 hours

Recoat Time 24 hours

Full Cure 7 days

## TOLL FREE

1800 222 841 (AU)

0800 224 070 (NZ)

[www.dunlopdij.com](http://www.dunlopdij.com)

ARDEX Australia Pty Ltd ABN 82 000 550 005  
7/20 Powers Rd, Seven Hills NSW 2147

ARDEX Australia Pty Ltd

NSW Ph (02) 9851 9199 Fax (02) 9838 7970

VIC Ph (03) 8339 3100 Fax (03) 9308 9332

QLD Ph (07) 3817 6000 Fax (07) 3881 3188

SA Ph (08) 8406 2500 Fax (08) 8345 3207

WA Ph (08) 9256 8600 Fax (08) 9455 1227

ARDEX New Zealand Ltd

Ph (03) 373 6900

Fax (03) 3849 779