


INTRODUCTION

Your **EVIE Sensor** communicates to the **WX8** to automatically disable your watering schedules after 5mm of rain, reducing your water usage in the process.

The sensor uses two electrodes (A) connected to a Radio Frequency (RF) Transmitter.

When water begins to fill the sensor, the circuit between the two electrodes completes, and the RF Transmitter can wirelessly communicate to the **WX8** to stop watering. After the water in the sensor evaporates, the circuit is once again disconnected, and the RF Transmitter tells the **WX8** it can continue with your watering schedules. The sensor holds a maximum of 25mm of rainfall.


Your **EVIE Sensor** regulates how quickly watering will resume after rain. This comes from the amount of rainfall collected, and how quickly it evaporates in heat or wind.



- i** When water fills above the internal electrodes (A), the **EVIE Sensor** will detect the moisture and any automatic watering starts will be disabled in **Holman Home**
- i** As the water evaporates and the water level drops below the centre weir (B), the sensor will report back to your **WX8** as dry, and any automatic watering starts will be reinstated in **Holman Home**


PAIRING TO THE WX8 IRRIGATION CONTROLLER

- i** Your **EVIE Sensor** should already be paired with your **WX8 Irrigation Controller**
1. Check the **DEVICE INFORMATION (C)** page in **Holman Home** to ensure your **EVIE Sensor** is paired to the **WX8** correctly and the battery is in good condition
 2. If your **EVIE Sensor** does not appear to be paired to your **WX8**, please see our pairing instructions overleaf



INSTALLATION

- i** To communicate to the **WX8 Irrigation Controller**, the **EVIE Sensor** needs to be installed no more than 20 metres from the controller with a clear line of sight




- i** The **EVIE Sensor** needs to be mounted horizontally on a gutter and attached with the wing nut screw (D) provided
- i** Choose a gutter location where the **EVIE Sensor** will not be knocked by surrounding trees or by potentially strong wind
- i** Ensure the **EVIE Sensor** is within 50m range of your **WX8**
- i** Use the elbow screw (E) to level the **EVIE Sensor** on your gutter

CHECKING YOUR EVIE SENSOR

To check if your **EVIE Sensor** is working, please follow these steps:

1. Fill the sensor with water
2. Stand at ground level, holding the sensor under your gutter near the intended installation point
3. You will need to wait up to a minute for **Holman Home** to detect moisture through the **EVIE Sensor**
4. **Holman Home** should currently report (F) that the **EVIE Sensor** is detecting and that automatic watering starts have been disabled
5. Once **Holman Home** has confirmed it is working correctly, empty the water and install the sensor in the desired location



TROUBLESHOOTING

If for some reason the **EVIE Sensor** has been disconnected from your **WX8**, **Holman Home** will show this in the **DEVICE INFORMATION** screen (F).

The following instructions highlight how to re-pair your **EVIE Sensor** to the **WX8**:

1. Bring your **EVIE Sensor** to your **WX8** irrigation controller so that you can operate both devices simultaneously
2. On the **EVIE Sensor**, remove the rubber plug (G) on the underside and check there are two CR2032 batteries (H) installed
3. On your **WX8**, turn the dial to **OFF**
4. Press and hold **START** for 5 seconds until the LEDs of **ZONE 1** and **2** both flash, alternating between red and blue (for 20 seconds only)
 - i** The next step must be completed in the first 20 seconds while the LEDs are still flashing
 - i** If you run out of time it is possible to attempt the process again
5. On the **EVIE Sensor**, press and hold the internal button (I) until the **WX8** LEDs of **ZONE 3** and **4** are alight
 - i** If the pairing succeeds, these LEDs will be blue
 - i** If the pairing fails, these LEDs will be red
6. After pairing is successful, on the **WX8**, turn the dial to **RUN** to exit the pairing mode
7. Wait at least one minute for the **Holman Home** to show **EVIE Sensor** is connected to the **WX8** in the **DEVICE INFORMATION** screen (J)
8. Replace the rubber plug back into **EVIE Sensor** (G)
9. Follow the instructions for **CHECKING YOUR EVIE SENSOR** as listed overleaf
10. Re-install your **EVIE Sensor** as per the **INSTALLATION** instructions overleaf
 - i** For additional pairing help, please visit <https://www.holmanindustries.com.au/> to access additional support pages or contact our Customer Service team

