



Manufacturers of BIO-SAFE Technology

Application Data Sheet:

SUPER SEAL

GROUT & TILE SEALER

APPLICATION:



- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
 - Make sure the surface to be sealed is clean and free from grout residue.
 - Allow newly laid tiles and grout to dry, at least 30 minutes – 1 hour. (Because the sealer is breathable the surface will dry out normally)
 - Shake can well and hold approx. 15 - 20 cm away from surface, apply in a sweeping motion.
 - More porous surfaces may require more than one application. Allow 30 minutes between coats.
 - **SUPER SEAL** will dry quickly and fully cure in 24 hours.
 - Buff off any excess residue with a soft white cotton cloth within an hour of spraying.
-

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*