


ametalin THERMALBREAK 7™

EXTRA HEAVY DUTY

DOUBLE SIDED REFLECTIVE FOAM INSULATION RESIDENTIAL & COMMERCIAL



MEETS NCC REQUIREMENTS FOR A THERMAL BREAK OF R0.2 IN STEEL FRAMED CONSTRUCTION

Product Code: **TB7-30** | I/N: 0811234

ametalin THERMALBREAK 7™ is an Extra Heavy Duty three-in-one reflective insulation, thermal break and medium vapour barrier for use in all roof, wall types. It meets the NCC requirements for in-situ material R-value of R0.20 for a thermal break in steel framed construction, and is also suitable for use in timber framed construction.


Designed to manage heat gain and heat loss, ametalin THERMALBREAK 7™ offers superior thermal performance to conventional insulation, and reduces thermal bridging and conductivity between building elements.

- ▶ The most cost effective R0.20 thermal break product in the Ametalin product range.
- ▶ 150 mm flap provided for increased coverage and reduced wastage.
- ▶ Contributes a reflective R-value when installed adjacent to an air cavity.
- ▶ Highly effective in dampening noise.
- ▶ Fibre-free and non-allergenic.
- ▶ Water resistant, fire resistant.
- ▶ Rigorously tested by independent recognised accredited laboratories in compliance with AS/NZS 4859.1:2002/Amtd 1:2006 to ensure all product claims are met.

Construction

ametalin THERMALBREAK 7™ is made with aluminium foil laminates with reflectivity of 97% and emissivity of 0.03 to one side and 95% reflectivity and emissivity of 0.05 to the other, in compliance with AS/NZS 4200.1.6.3. At its core is 7.8 mm of chemically cross-linked, closed-cell XPE foam.

Ametalin utilises Advanced Laminating Technology; the polymer adhesive remains tacky for an indefinite period and provides superior resistance to heat, fire and delamination.



Declared Total System R-values for Typical Systems*

ametalin THERMALBREAK 7™ has a material R-value of 0.21 to meet thermal break requirements. When it is incorporated into typical construction systems, the following thermal performance can be achieved:


			WINTER	SUMMER
Metal Roof unventilated	22° Pitched metal roof, 190 mm raked ceiling	CALC. REF: 12239	R _T 1.4	R _T 3.7
Metal Roof ventilated	22° Pitched metal roof with flat ceiling	CALC. REF: 299r404	R _T 1.3	R _T 2.8
Metal Roof unventilated	22° Pitched metal roof with flat ceiling	CALC. REF: 299r405	R _T 1.5	R _T 2.5
Tile Roof unventilated	22° Pitched tile roof with flat ceiling	CALC. REF: 12084	R _T 1.5	R _T 2.5
Commercial Office Roof	Suspended ceiling at 1000 mm	CALC. REF: 299r402	R _T 1.4	R _T 4.6
Warehouse Shed Roof	5° metal roof 100 mm ceiling	CALC. REF: 299r401	R _T 1.5	R _T 3.2
Warehouse Shed Roof	5° metal roof with no ceiling	CALC. REF: 299r403	R _T 1.0	R _T 2.0
Steel Stud Framed Wall	Metal cladding direct to 90 mm stud, no lining	CALC. REF: 299w501	R _T 1.3	R _T 1.1
Concret Tilt Slab Wall	150 mm stud, plasterboard lining	CALC. REF: 13017	R _T 2.1	R _T 1.9

* The contribution of this product to the total system R-value depends on installation and environmental conditions. The R-values will be reduced in the event of the accumulation of dust on upward facing surfaces and in those cavities that are ventilated.

DECLARED TOTAL SYSTEM R-VALUES*

METAL ROOF

22° pitched flat ceiling ventilated




CALCULATION REF: 299r404

WINTER	R _T 1.3
SUMMER	R _T 2.8

TILE ROOF

22° pitched flat ceiling unventilated



CALCULATION REF: 12084

WINTER	R _T 1.5
SUMMER	R _T 2.5

COMMERCIAL OFFICE

5° pitched, 1000 mm ceiling




CALCULATION REF: 299r402

WINTER	R _T 1.4
SUMMER	R _T 4.6

WAREHOUSE SHED

5° pitched, no ceiling




CALCULATION REF: 299r403

WINTER	R _T 1.0
SUMMER	R _T 2.0

WALLS:


Stud Framed



CALCULATION REF: 299w511

WINTER	R _T 1.9
SUMMER	R _T 1.7


Brick Veneer



CALCULATION REF: 299w502

WINTER	R _T 2.2
SUMMER	R _T 1.9


Double Brick



CALCULATION REF: 299w503

WINTER	R _T 2.3
SUMMER	R _T 2.1

ametalin THERMALBREAK 7™



TB7-30

Classification

ametalin THERMALBREAK 7™ classifications in accordance with AS/NZS 4200.1:2017 and AS/NZS 4859.1:2006

PRODUCT	ametalin THERMALBREAK 7™	AS/NZS 4200.1:2017
FLAMMABILITY INDEX	AS 1530.2-1993	Low Low ≤ 5
MATERIAL THERMAL RESISTANCE	ASTMC518	0.21 m ² ·K/W (R0.21)
DUTY	AS/NZS 4200.1:2017	Extra Heavy Classification
EMITTANCE	AS/NZS 4201.5:1994	Bright side: 0.03 Anti-glare side: 0.05 Value
REFLECTIVITY	AS/NZS 4200.1.6.3	Bright side: 97% Anti-glare side: 95% Value
RESISTANCE TO WATER PENETRATION	AS/NZS 4201.4:1994	High Pass
VAPOUR BARRIER	ASTM E96	Medium, PROCEDURE B, WET CUP TEST Classification
MACHINE DIRECTION TENSILE STRENGTH	AS 1301.448s-91	14.6 kN/m Min 13.0 kN/m
LATERAL DIRECTION TENSILE STRENGTH	AS 1301.448s-91	13.6 kN/m Min 10.5 kN/m
MACHINE DIRECTION EDGE TEAR	TAPPI T 470 om-89	384 N Min 90 N
LATERAL DIRECTION EDGE TEAR	TAPPI T 470 om-89	293 N Min 90 N
RESISTANCE TO DRY DELAMINATION	AS/NZS 4201.1:1994	Pass Pass
RESISTANCE TO SURFACE CORROSION	AS/NZS 4859.1:2002	Pass Pass
SHRINKAGE (REPEATED WETTING & DRYING)	AS/NZS 4201.3:1994	0.0% < 0.5%

PRODUCT CODE: TB7-30	THICKNESS: 7.8 mm
ROLL SIZE: 1350 mm x 22.25 m +150 mm flap (30 m ²)	UNCOMPRESSED R-VALUE: R0.21
NOMINAL WEIGHT: 13 kg	COMPRESSED R-VALUE: R0.20

WATER VAPOUR TRANSMISSION RATE: 1.3 g/m ² ·24hr (23°C, 50% RH)	AMETALIN CLASSIFICATION: MEDIUM VAPOUR BARRIER
---	--

Vapour Barrier Properties

ametalin THERMALBREAK 7™ has a Water Vapour Transmission (WVT) rate of 1.3 grams per square metre per 24 hours tested at 23°C, 50% Relative Humidity (RH).

NCC Compliant

ametalin THERMALBREAK 7™ complies with AS/NZS 4859.1:2002/Amdt 1:2006 and AS/NZS 4200.1:2017, and therefore meets all the requirements of the *National Construction Code* for insulation and pliable building membranes.

BUSHFIRE ATTACK LEVELS

ametalin THERMALBREAK 7™ complies with AS 3959-2009 *Construction of buildings in bushfire-prone areas* for use in roof systems BAL – LOW to BAL – 40 and wall systems BAL – LOW to BAL – FZ.

Total System R-values

R-values apply to typical conditions for mainland Australian capital cities and have been calculated in accordance with AS/NZS 4859.1:2002/Amdt 1:2006. For detailed design of building systems, seek advice based on actual site conditions from a qualified licensed engineer.

Reflectivity

ametalin THERMALBREAK 7™ is made with aluminium foil laminates with reflectivity of 97% and emissivity of 0.03 to one

side and 95% reflectivity and emissivity of 0.05 to the other in compliance with AS/NZS 4200.1.6.3.

Storage

This product should be stored upright and under cover in a clean, dry place in the pack provided.

Dimensions

ametalin THERMALBREAK 7™ is sold in size: 1350 mm x 22.25 m + 150 mm flap (30 m²)

Specification Notes

When specifying, state the following:

Product Name: AMETALIN THERMALBREAK 7™

The insulation to be installed shall be Ametalin ThermalBreak 7™ double sided reflective, fibre-free thermo-reflective insulation, comprised of cross-linked, closed-cell core XPE foam with anti-glare foil facing on one side and plain foil facing on the other side, and 150 mm overlap piece included. Material R-value in-situ R0.20. Product is manufactured by Ametalin and shall be installed in accordance with AS/NZS 4200.2: 1994 *Pliable Building Membranes and Underlays, Part 2: Installation Requirements*.

Emittance Bright Side: 0.03, Anti-glare Side: 0.05

Material R-value: R0.21 uncompressed / R0.20 in-situ

Water Vapour Transmission (WVT): 1.3 g/m²·24hr

Vapour Resistance: 89.34 MN·s/g

Vapour Barrier Classification: Medium

Water Barrier Classification: High

Duty: Extra Heavy in accordance with AS/NZS 4200.1:2017

© 2018 Ametalin All Rights Reserved. Ametalin is a division of Amalgamated Metal Industries Pty. Ltd. Product information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but due to factors outside our knowledge and control which may affect the use of products, no warranty is given or implied with respect to this information or the product itself regarding the suitability of the product for any particular purpose. The usage of this and other building membranes will affect moisture migration in the building element. The purchaser should independently determine the suitability of the product for the intended purpose. For large projects with complex air-conditioning and condensation issues, designers may wish to contact our technical department. Batch number is printed on product. Product colour may vary from batch to batch. Amalgamated Metal Industries Pty. Ltd. reserves the right to amend product specifications without prior notice. Information provided is considered to be true and correct at the time of publication. DTE-43313-2

AUSTRALIAN DESIGNED, AUSTRALIAN OWNED.

AMETALIN

9 -11 Playford Crescent Salisbury North SA 5108

T: +61 8 8285 6955 F: +61 8 8285 5911 E: info@ametalin.com W: ametalin.com

Manufacturers of building membranes | insulation products | flexible packaging

Health and Safety Information

Ametalin has assessed ametalin THERMALBREAK 7™ according to the criteria outlined in the *National Occupational Health and Safety Commission (NOHSC):1008 (1998)* and *NOHSC: 1005 (1999)*. As a result of the assessment, this product is classified as non-hazardous according to the NOHSC criteria. To reduce risk of UV damage when installing this product, wear protective clothing, safety glasses and sunscreen, and work in the shade wherever practical.

Installation

ELECTRICAL SAFETY PRECAUTIONS - BEFORE YOU START:

Ametalin stresses the importance of safe installation practices for foil-based insulation as critical to installer and consumer safety. Aluminium Foil Insulation Association Inc. (AFIA) has prepared Work Method Statements and Hazard Management forms to assist contractors and installers in safe installation of reflective insulation products. These documents are available under 2009 AFIA WMS & Hazard Management, at www.afia.com.au/news/health-and-safety/.

ametalin THERMALBREAK 7™ should be installed in accordance with *AS/NZS 4200.2: 1994 Pliable Building Membranes and Underlays, Part 2: Installation Requirements*.

GENERAL

ametalin THERMALBREAK 7™ is not designed to withstand prolonged direct exposure to the elements. Accordingly, the outer construction envelope should be installed without delay. Aluminium foil should not come into contact with wet concrete or mortar, as the aluminium is susceptible to alkali corrosion. If installed within 500 metres of the sea, or in a non-residential building where foil surfaces may be exposed to a corrosive atmosphere (including agricultural sheds), foil surfaces should face an enclosed, un-vented air space. To ensure optimum thermal insulation performance, as well as satisfactory durability, an air space adjacent to each side of the product is recommended.

ROOFS

In roofs, ametalin THERMALBREAK 7™ is to be installed as a continuous membrane, blue anti-glare side facing out and laid over rafters. Joins must be overlapped by no less than 150 mm to facilitate drainage. A 150 mm flap is provided for convenience. When ametalin THERMALBREAK 7™ is used under tiles it must be installed under battens with appropriate drape in order to comply with *AS 4200.1:2017*.

FRAMED WALLS & GABLES

In framed walls and gables, ametalin THERMALBREAK 7™ should be installed horizontally as a continuous membrane by fixing to all framing members with the blue anti-glare side facing out and overlapped by no less than 150 mm to facilitate drainage. A 150 mm flap is provided for convenience.

ametalin THERMALBREAK 7™ should extend from the top plate to the bottom plate on concrete slabs or bearers in timber construction. Fixings are to be no more than 450 mm apart and should be galvanised clouts, or staples, for fastening to timber construction and tek screws for fastening to steel constructions. In high wind areas, it is recommended to install using flat punched

multi-point fasteners or cap screws. Horizontal, vertical and end overlaps must be 150 mm if not taped or 50 mm taped with Ametalin 75mm Reinforced Insulation/Ducting Tape, with all top layers overlapping the outside of lower layers to prevent water ingress. Stagger any vertical overlaps. Any damage made to ametalin THERMALBREAK 7™ during installation including holes and tears must be repaired.

Where ametalin THERMALBREAK 7™ is intended to act as a vapour barrier, tape and seal all overlapped joints, penetrations and discontinuities with Ametalin 75mm Reinforced Insulation/Ducting Tape to prevent air movement. When ametalin THERMALBREAK 7™ is installed as a sarking membrane, all penetrations shall be sealed or turned up to facilitate drainage around penetration. Ensure window and door openings are cut neatly and carefully and are properly fitted at flashing points. ametalin THERMALBREAK 7™ shall be cut back from any hot flue to avoid being a fire hazard. This can be achieved by a clear space of at least 50 mm, or as recommended by the manufacturer of the flue and approved by the local authority.

DOUBLE BRICK & MASONRY CAVITY WALLS

After the outer leaf of the double brick or masonry cavity wall is laid, place Ametalin Cavity Spacers™ onto the brick ties via the vertical slit provided, with the white adhesive side facing inwards. Install one cavity spacer per square metre to ensure the required air space. Remove adhesive tape backing. Install ametalin THERMALBREAK 7™ horizontally, cut slits through the pliable building membrane at all brick tie positions, and place ametalin THERMALBREAK 7™ into position over the brick ties. Push the membrane and the cavity spacer into position against the outer leaf of bricks, continue to lay the inner leaf of brick or masonry.

FLOORS

Adequate drainage provisions must be given for all floor applications. Contact our technical department for more information about use in floors.

© 2018 Ametalin All Rights Reserved. Ametalin is a division of Amalgamated Metal Industries Pty. Ltd. Product information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but due to factors outside our knowledge and control which may affect the use of products, no warranty is given or implied with respect to this information or the product itself regarding the suitability of the product for any particular purpose. The usage of this and other building membranes will affect moisture migration in the building element. The purchaser should independently determine the suitability of the product for the intended purpose. For large projects with complex air-conditioning and condensation issues, designers may wish to contact our technical department. Batch number is printed on product. Product colour may vary from batch to batch. Amalgamated Metal Industries Pty. Ltd. reserves the right to amend product specifications without prior notice. Information provided is considered to be true and correct at the time of publication. DTE-43313-2

AUSTRALIAN DESIGNED, AUSTRALIAN OWNED.

AMETALIN

9-11 Playford Crescent Salisbury North SA 5108

T: +61 8 8285 6955 F: +61 8 8285 5911 E: info@ametalin.com W: ametalin.com

Manufacturers of building membranes | insulation products | flexible packaging