

1. Identification of the material and supplier

<u>Names</u>	
Product name	: Sikaflex®-227
<u>Supplier</u>	
Supplier/Manufacturer	: Sika Australia Pty. Ltd. 55 Elizabeth Street (Locked Bag 482 BDC) Wetherill Park, NSW 2164 Australia
Telephone no.	: +61 2 9725 11 45
Fax no.	: +61 2 9725 33 30
Emergency telephone number	: +61 1800 033 111
<u>Uses</u>	
Use of the substance/mixture	: Chemical product for construction and industry

2. Hazards identification

Classification	: Xi; R36/38 R43 R52/53
Risk phrases	 R36/38- Irritating to eyes and skin. R43- May cause sensitisation by skin contact. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	: S24- Avoid contact with skin. S37- Wear suitable gloves.
Statement of hazardous/dangerous nature	: HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.

3. Composition/information on ingredients

Mixture	: Yes.		
Calcium carbonate		471-34-1	10 - <30
Polyvinylchloride		9002-86-2	1 - <10
Titanium dioxide		13463-67-7	1 - <10
xylene		1330-20-7	1 - <10
Hydrocarbons		8002-09-3	1 - <10
tosyl isocyanate		4083-64-1	0.1 - <1
dibutyltin dichloride		683-18-1	0 - <0.1

Other ingredients, determined not to be hazardous according to Safe Work Australia criteria, and not dangerous according to the ADG Code, make up the product concentration to 100%.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First-aid measures

First-aid measures

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Sikaflex®-227

4. First-aid measures		
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Skin contact	: Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.	
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	
Notes to physician	: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	

5. Fire-fighting measures

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	No specific fire or explosion hazard.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazardous combustion products	 Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
Large spill	:	Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Version :	1.01	Page: 2/6
-----------	------	-----------

6. Accidental release measures

Small spill

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handlin	g
---------	---

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient name	Exposure limits
calcium carbonate	EH40/2005 WELs (United Kingdom (UK), 8/2007). TWA: 10 mg/m ³ 8 hour(s). Form: inhalable dust
	TWA: 4 mg/m ³ 8 hour(s). Form: respirable dust
Ethylene, chloro-, polymer	ACGIH TLV (United States, 2/2010). TWA: 1 mg/m ³ 8 hour(s). Form: Respirable fraction
titanium dioxide	Safe Work Australia (Australia, 8/2005).
	TWA: 10 mg/m ³ 8 hour(s).
xylene	Safe Work Australia (Australia, 8/2005).
y	STEL: 655 mg/m ³ 15 minute(s).
	STEL: 150 ppm 15 minute(s).
	TWA: 350 mg/m³ 8 hour(s).
	TWA: 80 ppm 8 hour(s).
dibutyltin dichloride	Safe Work Australia (Australia, 8/2005). Absorbed
	through skin. Notes: as Sn
	STEL: 0.2 mg/m³, (as Sn) 15 minute(s). TWA: 0.1 mg/m³, (as Sn) 8 hour(s).
Recommended monitoring	
procedures	atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory
	protective equipment.
Exposure controls	
Engineering measures	: No special ventilation requirements. Good general ventilation should be sufficient to
Engineering measures	control worker exposure to airborne contaminants. If this product contains ingredients
	with exposure limits, use process enclosures, local exhaust ventilation or other
	engineering controls to keep worker exposure below any recommended or statutory
	limits.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	eating, smoking and using the lavatory and at the end of the working period.
	Appropriate techniques should be used to remove potentially contaminated clothing.
	Contaminated work clothing should not be allowed out of the workplace. Wash
	contaminated clothing before reusing. Ensure that eyewash stations and safety
	showers are close to the workstation location.
Eyes	: Safety eyewear complying with an approved standard should be used when a risk
	assessment indicates this is necessary to avoid exposure to liquid splashes, mists or
	dusts.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should
	be worn at all times when handling chemical products if a risk assessment indicates
	this is necessary.
Version :	1.01 Page: 3/6

Exposure controls/personal protection 8.

Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Physical and chemical properties 9.

Physical state	: Solid.
Colour	: Various.
Odour	: Characteristic.
Density	: 1.26 g/cm ³ [20°C (68°F)]
Flash point	: Closed cup: 64.6°C (148.3°F)

10 . Stability and reactivity

Stability	: The product is stable.
Conditions to avoid	: No specific data.
Materials to avoid	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Potential acute health effects	2				
Inhalation	:	No known significant effects or critical hazards.			
Ingestion	1	Irritating to mouth, throat and stomach.			
Skin contact	:	Irritating to skin. May cause sensitisation by skin contact.			
Eye contact	:	Irritating to eyes.			
Acute toxicity					
Product/ingredient name calcium carbonate titanium dioxide xylene		Result LD50 Oral LD50 Oral LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral LC50 Inhalation	Species Rat Rat Rat Rabbit Rat Rat	Dose 6450 mg/kg >5000 mg/kg 6.82 mg/l >1700 mg/kg 4300 mg/kg 5000 ppm	Exposure - - 4 hours - - 4 hours
Pine oil 4-isocyanatosulphonyltoluen dibutyltin dichloride	е	Gas. LD50 Oral LD50 Oral LD50 Oral LC50 Inhalation Vapour	Rat Rat Rat Rat	3200 mg/kg 2234 mg/kg 50 mg/kg >364 mg/m3	- - - 4 hours
Conclusion/Summary	:	Not available.			
Potential chronic health effect	:ts				
Chronic toxicity					
Conclusion/Summary	:	Not available.			
Carcinogenicity					
Conclusion/Summary	1	Not available.			
<u>Mutagenicity</u>					
Conclusion/Summary	1	Not available.			
<u>Teratogenicity</u>					
Conclusion/Summary	1	Not available.			
Reproductive toxicity					
Version : 1.0 ^o	1				Page:

11. Toxicological information

Conclusion/Summary	: Not available.
Chronic effects	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>toms</u>
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation redness
Eyes	: Adverse symptoms may include the following: irritation watering redness
Target organs	: Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

12. Ecological information		
Environmental effects	:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Aquatic ecotoxicity		
Conclusion/Summary	:	Not available.
Other ecological information		
Biodegradability		
Conclusion/Summary	:	Not available.
Other adverse effects	:	No known significant effects or critical hazards.
13. Disposal cons	sic	derations

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Empty
containers or liners may retain some product residues. This material and its container
must be disposed of in a safe way. Significant quantities of waste product residues
should not be disposed of via the foul sewer but processed in a suitable effluent
treatment plant. Dispose of surplus and non-recyclable products via a licensed waste
disposal contractor. Disposal of this product, solutions and any by-products should at
all times comply with the requirements of environmental protection and waste
disposal legislation and any regional local authority requirements. Avoid dispersal of
spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

<u>ADG</u>

Not regulated.		
ADG Class	:	-
Label No.	:	

<u>adr</u>

Not regulated.

<u>IMDG</u>

Not regulated.

Marine pollutant : No.

<u>IATA</u>

Version :	1.01	Page: 5/6

14. Transport information

Not regulated.

15. Regulatory information

Standard for the Uniform Sch	neduling of Drugs and Poisons		
7			
Control of Scheduled Carcinogenic Substances			
Ingredient name No listed substance		<u>Schedule</u>	
Australia inventory (AICS)	: All components are listed or exempted.		
EU Classification	: Xi; R36/38 R43 R52/53		

16. Other information

Person who prepared the MSDS	:	Validated by DeSilva on 18.01.2012.
Date of previous issue	:	23.07.2010.

✓ Indicates information that has changed from previously issued version.

Disclaimer

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.