

Etch Primer



Dy-Mark's Etch Primer has been designed to provide excellent adhesion to metals that are difficult to bond to. Etch Primer provides outstanding corrosion protection and is a suitable base for a range of top coats. A fast dry product, Etch Primer is suitable for use on gates, fences, railings, pipes and gutters.

DIRECTIONS FOR USE

Preparation

New Steel – Sand and degrease the surface. Apply Etch Primer directly to the steel. For best results, top coat with Dy-Mark's Hi-Performance Enamel. **Rusted Steel** – Do not use Etch Primer on rusted steel. For best results, use Dy-Mark's Metal Primers. **Timber** – Clean, dry and sand the surface. Apply Etch Primer directly onto timber. Top coat with Dy-Mark's Hi-Performance Enamel. **Aluminium / Stainless Steel / Galvanised Iron / Zinalume® / Copper / Alloys** – Sand and degrease the surface before applying Etch Primer. For best results, top coat with Dy-Mark's Hi-Performance Enamel.

Application

Shake the can for at least 20 seconds after the mixing ball begins to rattle. Hold can in the inverted position, approximately 20 – 25cm from surface. Adjust nozzle to achieve the desired spray pattern. Apply one or two even coats.

TECHNICAL DATA

Size:	325g Aerosol
Finish:	Matt
Colour:	Grey
Consistency:	Liquid
Coverage:	Approximately 2 sqm per can (depending on the surface)
Suitable Surfaces:	Aluminium, galvanised iron, new steel, Zinalume®, alloys, timber
Drying Time:	Touch dry in 10 minutes; Recoat after 2 hours
Temperature:	Between 10°C and 40°C
Clean Up:	Dy-Mark Acetone

STORAGE

Store below 50°C. Do not store in direct sunlight or in vehicles under hot conditions. Protect aerosol cans against physical damage.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If **swallowed**: Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.