

**JOHNSTONE'S PROFESSIONAL FURNITURE OIL** has been specially formulated to protect, rejuvenate and maintain the natural look of exterior timber furniture.

**AQUA PROTECT TECHNOLOGY:** Creates a highly durable barrier that repels water and resists mould, dirt and stains.

**UV PROTECTION:** Blocks out harmful UV rays for longer lasting results.

**WATER BASED:** Low odour, easy clean up.

**FINISH:** Low lustre.

- IDEAL FOR:** Exterior timber furniture, tables and chairs.
- SUITABLE SURFACES:** Exterior new and weathered soft and hard wood timber furniture.
- FINISH:** Semi-transparent low lustre in 3 timber tones.
- COVERAGE:** Approx. 12m<sup>2</sup> per litre (dependent on porosity of the timber substrate).

## SURFACE PREPARATION

### **NEW HARDWOOD TIMBER FURNITURE:**

Allow the timber to naturally weather for 6 weeks. Alternatively, apply Johnstone's Professional Hardwood Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Sanding of hardwood timber substrate prior to application of product is recommended, this will provide a key for the Johnstone's Professional Furniture Oil to adhere to.

### **SOFTWOOD TIMBER FURNITURE:**

Ensure timber surface is clean and free from dirt and debris prior to application.

### **PREVIOUSLY PAINTED OR VARNISHED TIMBER FURNITURE:**

Strip back to bare timber using Johnstone's Professional Timber Stripper, and/or sanding. For exterior surfaces clean with Johnstone's Professional Deck & Timber Cleaner following label instructions.

### **PREVIOUSLY STAINED AND OILED TIMBER FURNITURE:**

For exterior surfaces, clean with Johnstone's Professional Deck & Timber Cleaner following label instructions. Rinse with water and allow to completely dry prior to application of Johnstone's Professional Furniture Oil. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application of Johnstone's Professional Furniture Oil.

### **WEATHERED AND GREY TIMBER FURNITURE:**

For best results, sand timber back to fresh substrate. Clean with Johnstone's Professional Deck & Timber Cleaner following label instructions. Ensure surface is dirt and dust free prior to the application of Johnstone's Professional Furniture Oil.

## APPLICATION

1. Stir thoroughly with a broad flat paddle before and during use.
2. Apply liberally to timber furniture including exposed edges and end grain preferably by brush or applicator pad. Initially applied, the Johnstone's Professional Furniture Oil will look slightly opaque however, will dry to a semi-transparent finish allowing the timber grain to remain visible.
3. Apply two coats allowing 1 hour between the first and second coat. For increased durability, longevity and coverage of the 12 month Aqua Protect guarantee\* a third coat should be applied.

**MAINTENANCE:** Re-apply as the timber changes colour or when water repellency diminishes due to weathering. Follow surface preparation instructions.

**DRYING AND RECOAT TIME:** All timings quoted at 25°C and 50% humidity. Cooler or humid conditions may require longer.

**IMPORTANT:** Do not apply this product in temperatures below 10°C or above 35°C or when heavy rain or dew is expected during the drying period. In hot temperatures, do not apply in direct sunlight. Attempt to coat when project is shaded.

**CLEAN UP:** Clean brushes and equipment with water.

**COVERAGE:** Approx. 12m<sup>2</sup> per litre.



**TOUCH DRY:** **RECOAT:**

30 minutes

Allow a minimum of 1 hour between coats

## SAFETY & FIRST AID

**KEEP OUT OF REACH OF CHILDREN.** Avoid skin and eye contact.

**IF SWALLOWED:** Give plenty of water to drink. Seek medical advice.

**EYE CONTACT:** Rinse with plenty of running water. Seek medical advice if irritation occurs.

**24 HOUR MEDICAL  
EMERGENCY  
RESPONSE SERVICE  
CALL:**

**AUS:** 1800 883 254  
**NZ:** 0800 000 096