



May 2017

## Earthwool® Multi-Use Rolls

### Description

Earthwool Multi-Use rolls are made using recycled glass and with ECOSE® Technology, a revolutionary binder based on rapidly renewable materials instead of petro-based chemicals. ECOSE Technology reduces binder embodied energy and contains no added phenol, formaldehyde, acrylics or artificial colours.

### Application

Earthwool Multi-Use rolls provide a cost-effective thermal and acoustical barrier for energy-efficient construction. The consistent quality, low dust, and clean-cutting resilient glasswool makes installation fast.

Earthwool Multi-Use rolls can be used for walls and topping up existing insulation in the ceiling.

### Performance

#### Thermal Conductivity

ASTM C 518 and AS/NZS 4859.1: 2002.

#### Thermal Resistance

ASTM C 653 and AS/NZS 4859.1: 2002.

### Technical Data

#### Water Vapour Absorption (ASTM C 1104)

- Less than 5% by weight.

#### Corrosion Resistance (ASTM C 665)

- No greater than sterile cotton.

#### Microbial Growth (ASTM C 1338)

- Does not support microbial growth.

#### Fire Hazard Properties (AS/NZS 1530.3)

- Ignitability: 0, Spread of flame: 0, Heat Evolved: 0, Smoke Developed: 0-1.

#### Combustibility (AS 1530.1)

- Non-combustible.



**EARTHWOOL**  
the feel good glasswool insulation

with **ECOSE**  
TECHNOLOGY

## Earthwool® Multi-Use roll

### Specification Compliance

AS/NZS 4859.1: 2002 Materials used in the Thermal Insulation of Buildings and comply with the Australian Building Code requirements: B2 - Durability, E3 - External Moisture, F2 - Hazardous Building Materials, and H1 - Energy Efficiency.

### Bio-solubility

The formulation used for Earthwool insulation has been independently assessed to meet the requirements of the stringent Note Q standard (and is therefore consistent with the highest Australian and New Zealand industry standards), and also assessed by Knauf Insulation against the criteria of the Australian Safety and Compensation Council ASCC Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008 3rd Edition]. As a result of this assessment, Earthwool insulation is not classified as hazardous according to the NOHSC criteria.

### Environmental

Earthwool Multi-Use rolls represent no known threat to the environment and have zero Ozone Depletion Potential and zero Global Warming Potential.

### Features and Benefits

#### Proven Performance

- Preferred by professional installers concerned with quality, appearance and productivity.
- Excellent acoustical properties reduce sound transmission in the home when properly installed in walls, ceiling and floor systems.

#### Durability

- Earthwool insulation is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### Superior Handling

- Highly resilient insulation recovers quickly to full thickness for a snug fit and superior finished aesthetics.
- Consistent quality materials feel good, cut easily and install fast.
- Low dust for easier handling and increased productivity.

Knauf Insulation's Earthwool insulation products with ECOSE® Technology benefit from a formaldehyde-free binder based on rapidly renewable materials instead of petro-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Earthwool insulation products made with ECOSE Technology contain no dye or artificial colours – the colour is completely natural.

### Specification Guide

The insulation shall be Earthwool Multi-Use rolls R\*, \*mm thick, BRANZ appraised to meet the provisions of the BCA. The product will be non-combustible, CFC/HCFC free, zero ODP and GWP, glasswool insulation with high post-consumer recycled glass content and with ECOSE® Technology. It will be manufactured under Quality Assurance Standards ISO 9001:2008 and ISO 14001:2004 by Knauf Insulation and shall be installed in accordance with the instructions issued by them.

\*architect to insert details of products used.

## Earthwool® Multi-Use roll

### Convenient Packaging, Easier Handling

- Earthwool insulation packages feature easy to follow installation instructions.
- MasterBag insulation units (containing multiple packs) ensure reduced handling costs with improved compression – more square metres per bag, more square metres per truck load, fewer trips to the job site and less warehouse space for storage.

### Superior Service and Support

- Knauf Insulation is focused on providing first class customer service, producing high quality product and 'in full on time' deliveries.
- Knauf Insulation recognises the need to establish, develop and support a professional network of distributors and re-sellers in order to service a growing insulation market.
- Knauf Insulation is committed to providing a comprehensive range of relevant sales and marketing literature and web-based technical information to support specifiers and customers.

Material Code	Thickness (mm)	Width (mm)	R-Value (m <sup>2</sup> K/W)	Length (mm)	Rolls per Pack	Area per Pack (m <sup>2</sup> )
253095	90	430	2.0	19000	1	8.17
253093	90	580	2.0	19000	1	11.02



Material Code	Thickness (mm)	Width (mm)	R-Value (m <sup>2</sup> K/W)	Length (mm)	Rolls per Pack	Area per Pack (m <sup>2</sup> )
432158	90	430	2.5	12500	1	5.37
432159	90	580	2.5	12500	1	7.25



### Knauf Insulation Pty Ltd

1/44 Borthwick Avenue,  
Murrarie, QLD 4172

### Customer Service (Sales)

Tel: +61 7 3393 7300

Fax: +61 7 3902 0613

Email: [orders.au@knaufinsulation.com](mailto:orders.au@knaufinsulation.com)

### Technical Advisory Centre

Email: [tech.au@knaufinsulation.com](mailto:tech.au@knaufinsulation.com)

For more information please visit  
[www.knaufinsulation.com.au](http://www.knaufinsulation.com.au)