

Sika[®] Filler-107

Ready to use surface filler for use in wet areas

Product Description Sika[®] Filler-107 is a water based, ready to use general purpose surface filler for use in wet areas.

Uses ■ Sika[®] Filler-107 is suitable for interior surface filling work on plaster, woven fabrics, old wallpapers, etc. in wet environments such as kitchens and bathrooms etc.

Characteristics / Advantages

- Ready to use, no mixing required
- Easy application
- High initial tack or grab on plaster and concrete
- Quick drying
- Not sensitive to moisture

Product Data

Form

Appearance / Colours Grey / blue, grey paste

Packaging 500 ml plastic tube
5 l and 10 l plastic pail

Storage

Storage Conditions / Shelf-Life 12 months from date of production if stored properly in undamaged and unopened original sealed packaging, in dry conditions. Protect from frost.

Technical Data

Chemical Base Filled styrene-acrylate dispersion

Density ~ 1.050 kg/l

Solid Content ~ 62%

Grading D_{max} : 0.15 mm

Layer Thickness 4 mm max.

Construction



System Information

Application Details

Consumption This depends on the substrate roughness and thickness of the layer applied. As a guide, ~ 1 l of Sika® Filler-107 can fill ~ 1 m² per mm thick.

Substrate Quality Clean, free from dust, dry and oil.

Application Conditions / Limitations

Substrate Temperature +5°C min. / +35°C max.

Ambient Temperature +5°C min. / +35°C max.

Application Instructions

Mixing Sika® Filler-107 is supplied ready to use - no mixing is required.

Application Method / Tools Sika® Filler-107 can be applied with a spatula in layer thicknesses from 0 - 4 mm. When filling deep holes or cracks above 4 mm the filler should be applied in several layers and must be allowed to almost dry before each subsequent layer is applied.

Cleaning of Tools Clean all tools and application equipment with water immediately after use. Hardened / cured material can only be mechanically removed.

Waiting Time / Overcoating
 Drying Time: 2 to 4 hours (thicker applications might require a longer time)
 Paintability: Approx. 12 hours

Value Base All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Health and Safety Information For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Important Notification The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. . In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.



Sika Australia Pty
 Limited
 www.sika.com.au

ABN: 12 001 342 329
 Tel: 1300 22 33 48

