

According to NOHSC:2011(2003)

Page: 1 of 1

Revised: 20- July-07 MSDS No: 110

CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA

1. Identification of the substance/preparation and company

Product:

Sika Primer 209N

Recommended use:

Primer for sealants.

Manufacturer/supplier information:

Manufacturer/supplier: Sika Australia Pty Ltd Street/postbox: 55 Elizabeth Street

Town/city and Post Code: WETHERILL PARK NSW 2164

Country: AUSTRALIA
Phone: (02) 9725 1145
Fax: (02) 9725 3330
General information Operations Manager

Emergency information phone: 1800 033 111

2. Composition/information on ingredients

Chemical characterization:

Solvent based polyisocyanate.

Hazardous ingredients:

	CAS No	Concentration
Aliphatic polyisocyanate	28182-81-2	1 -10%
Ethyl acetate	141 - 78 - 6	30- 60%
n- Butyl acetate	123-86-4	1 – 10%
Butanone	78-93-3	10 -30%
Isophorone di-isocyanate,homopolymer	53880-05-0	1 – 10%

3. Hazard identification

Hazard Category:

F Highly flammable

Xi Irritant

Risk Phrase(s):

R11 Highly flammable. R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R66 Repeated exposure may cause skin dryness and cracking.

R67 Vapours may cause drowsiness and dizziness.

Safety Phrase(s):

S24 Avoid contact with skin.

S33 Take precautionary measures against static discharge.

S36/37 Wear suitable protective clothing and gloves.

S51 Use only in well ventilated areas

4. First-aid measures

Inhalation:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical attention in case of respiratory irritation or if feeling unwell in cases of prolonged exposure.



According to NOHSC:2011(2003)

Page: 2 of 1

Revised: 20- July-07 MSDS No: 110

Skin contact:

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Solvents should not be used to clean skin because they may increase the penetration of the material. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact:

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion:

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766). Rinse mouth with water. If swallowed, do NOT induce vomiting. Never give anything by the mouth to an unconscious patient. Seek medical advice.

Notes to physician:

Treat symptomatically.

5. Fire-fighting measures

Specific hazards:

Combustion will produce smoke, carbon dioxide and carbon monoxide and nitrogen oxides.

Special protective precautions and equipment:

On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable extinguishing media:

Use alcohol resistant foam, dry chemical or carbon dioxide.

Do not use full water jet.

6. Accidental release measures

Spills:

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Eliminate all sources of ignition. Wipe up with absorbents such as earth, sand and inert material. Prevent material entering drains and waterways. Collect and seal in properly labelled containers or drums for disposal.

7. Handling and storage

Handling:

Use in well ventilated areas. Avoid contact with water or moist air. Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices.

Storage

Store in a cool, dry, well-ventilated place and out of heat and direct sunlight. Store away from sources of ignition. Keep away from food, beverages and animal feedstock.. Keep containers closed when not in use - check regularly for leaks.



According to NOHSC:2011(2003)

Page: 3 of 2

Revised: 20- July-07 MSDS No: 110

8. Exposure controls/personal protection

National occupational exposure limits:

No value assigned for this specific material by the NOHSC Australia.

However for:

	TWA (ppm)	TWA (mg/m3)	STEL (ppm)	STEL (mg/m3)
Ethyl benzene	100	434	125	543
n- Butyl acetate	150	713	200	950
Ethyl acetate	200	720	400	1440
Butanone	150	445	300	890

Biological Limit Values:

As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures:

Ensure ventilation is adequate to maintain air concentrations below Exposure Standards.

Personal protection equipment:

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Due to variations in glove construction and local conditions, the user should make an assessment of the appropriate gloves to use. Wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. Physical and chemical properties

Appearance:

Physical state: Liquid Colour: Black

Odour: Characteristic

Data relevant to safety:

Density (20 °C): 1.0 g/m3 Flash Point (°C): -4

Solubility partly soluble Viscosity (20 °C): 7 m Pas.

Viscosity (20 °C): 7 m Pas VOC 58.53%

(Typical values only - consult specification sheet)

10. Stability and reactivity

Chemical stability:

This material is thermally stable when stored and used as directed.

Conditions to avoid:

Formation of explosive gas/air mixtures.



According to NOHSC:2011(2003)

Page: 4 of 3

Revised: 20- July-07 MSDS No: 110

Hazardous decomposition products:

Oxides of carbon, smoke, fumes

Hazardous reactions:

No information available.

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects:

Sensitisation

Sensitisation /allergic reaction possible.

Allergic reactions can be observed in sensitive persons even on very low concentrations.

Inhalation: Vapours have a narcotic effect. Reaction time and sense of co-ordination may be effected.

Skin contact: Frequent skin contact may cause skin dryness and cracking and irritation.

Eye contact: Liquid and vapour can cause irritation.

Ingestion:

Small amounts may cause considerable health disorders.

Long Term Effects:

No information available for product.

Acute toxicity / Chronic toxicity:

No LD50 data available for the product.

12. Ecological information

Avoid contaminating waterways.

Ecotoxicity:

No information available.

Persistence and degradability:

No information available.

Mobility:

No information available.

13. Disposal considerations

Refer to State/Territory Land Waste Management Authority.



According to NOHSC:2011(2003)

Page: 5 of 5

Revised: 20- July-07 MSDS No: 110

14. Transport information

ADG/ADR/RID

UN. No. 1866
Dangerous Goods Class 3
Packing Group II
Proper Shipping Name: Resin solution

IMDG

UN. No. 1866

Dangerous Goods Class 3

Packing Group II

Proper Shipping Name: Resin solution

IATA

UN. No. 1866
Dangerous Goods Class 3
Packing Group II
Proper Shipping Name: Resin solution

15. Regulatory information

Poisons Schedule (Aust): S5.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other information

Reason(s) For Issue: Revised

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Date Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.