

## Frosted Glass Spray



**Dy-Mark Frosted Glass** spray creates a smooth frosted effect on plain glass that looks like real etched glass but still permits light to transmit through the painted surface. It is suitable for use on any interior clear glass surface. **Frosted Glass** is ideal for decorating glass ornaments around the home, or can be used on glass windows and doors to create instant privacy. Use stencils for added style.

### DIRECTIONS FOR USE

#### Suitable Surfaces

Ideal for creating etched look on glass doors, windows, skylights, shower doors, and more. Also ideal for decorating vases, bottles, glass ornaments and more.

#### Ideal Application Temperature

Between 10°C and 40°C. Avoid use in windy conditions.

#### Preparation

Surface should be clean, dry and free from contaminants such as oil, grease, dirt and salt. Always apply to side of glass which is protection from exposure to the elements or wear and tear.

#### Application

Before spraying, cover surrounding areas to protect from overspray. **Shake can** for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake can occasionally during use. Hold can upright approximately 20-25cm from the surface. Spray with a smooth sweeping motion. To prevent paint from sagging, apply several light mist coats rather than one heavy coat. **Adjust nozzle** to achieve desired spray pattern. Use horizontal setting to spray up and down and the vertical setting to spray across.

#### Coverage

Approximately 1.8 m<sup>2</sup> per can (depending on the surface and amount of overspray).

#### Drying Time

Touch Dry in 15-20 minutes (25°C). Recoat after 20 minutes. Leave 1 hour before handling. Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

#### After Spraying

**Prevent blocking** by holding the can upside down and spraying until clear gas escapes. Also **wipe spray tip** of nozzle clean.

# TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd PO Box 1556 • Toowong 4066 • Phone: 1300 396 275 • Fax:  
1300 360 440  
[www.dymark.com.au](http://www.dymark.com.au)



## TECHNICAL DATA

**Size:** 325g Aerosol  
**Finish:** Matt  
**Colour:** Opaque  
**Consistency:** Liquid  
**Clean Up:** Dy-Mark General Purpose Thinner or Dy-Mark Xylene

## STORAGE

Store below 50° C. Do not store in direct sunlight or in vehicles under hot conditions.

## DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents of can are under pressure. Do not puncture or incinerate even when empty. When empty, dispose of this container through an approved recycling scheme or seek advice from your local council regarding accepted disposal methods.

## SAFETY INFORMATION

### HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Can be harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

## FIRST AID

### KEEP OUT OF REACH OF CHILDREN

**If swallowed:** Do not induce vomiting.

**Eye contact:** In case of contact with eyes, rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia: 13 11 26; New Zealand: 0800 764 766**).

**Note:** the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.