

Technical Data Sheet

Water Rinsable Degreaser

Solutions

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description			
A general purpose degreaser and cleaner designed to remove grease, grime and dirt from a variety of surfaces such as metal, wood and concrete.			
Features and Benefits			
<ul style="list-style-type: none"> Fast-acting 		<ul style="list-style-type: none"> Rinsable with water 	
Area of Use			
<ul style="list-style-type: none"> Degrease metal prior to priming Degrease concrete surfaces prior to sealing 		<ul style="list-style-type: none"> Degreasing of car engines Paint brush restorer 	
Technical Data			
Number of Coats:	N/A	Curing time:	N/A
Spreading Rate Per Coat:	10-12m ² /L	Colour:	Clear
Wet Film Per Coat:	N/A	Thinner:	N/A
Recoat (@25°C):	N/A	Shelf Life:	12 months
Application Guide			
<p>Application Procedure and Equipment</p> <ul style="list-style-type: none"> Mechanically remove any large deposits of grease and dirt. Apply by brush or cloth a liberal quantity of Water Rinsable Degreaser to the area to be treated. It is recommended to work in manageable areas of approximately 10-20m² at a time, particularly when working outdoors. Scrub the area to loosen the contaminants. After approximately 10 minutes, use fresh water under pressure, to remove the degreaser. Inspect the cleaned treated area and repeat the procedure to any areas where contamination remains. Allow the substrate to dry thoroughly prior to sealing or painting. 			
Precautions			
<ul style="list-style-type: none"> Water Rinsable Degreaser will soften painted surfaces and some plastics. It is recommended to test the product on the substrate prior to doing the whole project. 			
Cleaning			
<ul style="list-style-type: none"> All equipment can be rinsed clean with water. 			

Technical Data Sheet

Water Rinsable Degreaser

Solutions

7 Day Technical Support 1800 655 711

Health and Safety

Safety Precautions

- Avoid breathing vapour. Wear organic vapour respirator meeting the requirements of AS1715 and AS1716.
- Provide good ventilation – open windows and doors and use circulating fans.
- Wear eye protection.

Wear PVC or neoprene gloves. Avoid contact with skin.

- If product is splashed on skin it should be washed off with water before it can dry.
- Keep out of the reach of children.

First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

Skin: Remove contaminated clothing and gently flush affected areas with soap and water. Seek medical attention if irritation develops. Launder clothing before re-use.

Inhalation: Remove patient from exposure, into fresh air. Apply artificial respiration if patient has stopped breathing. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	1L, 4L	Flash Point:	43°C
Weights:	1Kg, 4Kg	UN Number:	N/A
Dangerous Goods Class:	3	Poisons Schedule:	6
Hazchem Code:	3(Y)		

Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.