

Cloverdale WA 6985

BONDALL MONOCEL STAIN & VARNISH

REVISED: NOVEMBER 2005

DESCRIPTION

Bondall Monocel Stain & Varnish is a combined timber stain and clear polyurethane finish. It offers the convenience of a single product finish instead of a separate stain and clear system. It is suitable for use on most interior woodwork, built-in furniture, and panelling. For extra protection on furniture and woodwork overcoat with Bondall Monocel Gloss, Satin or Ultra Gloss.

Note: Bondall Monocel Stain & Varnish is not recommended for MDF board & floors.

SURFACE PREPARATION

Ensure that the timber is dry and free from dirt, grease or wax. Fill nail holes or cracks with a suitable timber putty in a matching timber colour following manufacturer's instructions.

Bare Timber:

- Sand surface smooth with 280 grit sandpaper and thoroughly remove all dust.
- Hint: A coat of Sanding Sealer applied before staining will assist in achieving a uniform colour, especially where end grain is encountered, eg louvre doors, turned legs and broad surfaces.

Previously Painted Surfaces:

• Not recommended unless paint is thoroughly stripped to bare timber before coating.

Previously Clear Coated Surfaces:

- Surfaces previously coated with Bondall Monocel Clear Timber Varnish or Monocel Gold should be sanded and thoroughly cleaned before recoating.
- For unknown finishes it is recommended that the surface be thoroughly stripped to bare substrate, sanded and cleaned before application.

APPLICATION

- Where more than one can of a Bondall Monocel Stain & Varnish is required to complete a job, combine all the contents of all cans into a clean metal or glass container and stir well before using.
- Apply an even coat with a premium quality brush, stain pad or spray equipment. Before application, test the colour on a timber off-cut or section of the job which does not show. If the colour is too strong, thin up to 10% with mineral turps.
- To deepen the colour, apply additional coats of Bondall Monocel Stain & Varnish. Where the desired colour is achieved in one coat, apply one or two coats of Bondall Monocel Clear Timber Varnish over the colour to increase the gloss level.

Bare Timber:

• Apply the first coat thinned 5-10% with mineral turps. Allow to dry, sand lightly and dust off. Apply the second coat and any subsequent coats undiluted.

Surfaces previously coated with Monocel Stain & Varnish or Monocel Clear Timber Varnish or Monocel Gold:

• Lightly sand and apply one or two coats of Bondall Satin Stain & Varnish as required, lightly sanding between coats.

To increase the durability without deepening the colour, the second and subsequent coats should be Bondall Monocel Clear Timber Varnish or Monocel Gold gloss or satin.

For hardwearing conditions additional applications of Bondall Monocel Clear Varnish range may be required.









COVERAGE

Approximately 12 square metres per litre, depending on the texture and porosity of the surface.

GLOSS LEVEL

Satin finish

DRYING TIME

Under normal drying conditions (25°C, 50% humidity) Bondall Monocel Stain & Varnish is touch dry in 4-6 hours. Allow longer for cooler or humid conditions and do not apply if temperature is below 10°C. Allow 24 hours before recoating.

CLEAN UP

- Clean rim and tightly close lid.
- Clean all equipment promptly with mineral turpentine.
- Rinse thoroughly with fresh water and a little detergent.
- Please dispose of any waste materials responsibly.
- Do not pur excess product or washings down drains or sinks.
- Keep unwanted product in sealed containers and use appropriate waste disposal services.

COLOUR

Baltic Pine, Cedar and Jarrah

SIZES

Available in 500ml and 1 litre









PRECAUTION/FIRST AID

- Wear protective clothing (eg coveralls, impervious cloves, goggles).
- Avoid contact with eyes or skin.
- Avoid inhalation and ensure good ventilation during use.
- If spraying, use suitable respirator.
- Seal container when not in use.
- Keep out of reach of children.
- If accidental poisoning occurs, seek urgent medical advice or contact the Poison Information Centre on 13 11 26.
- Material Safety Data Sheet available on request.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is depend antupon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of the contraction of thesurface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the useof this product. Should the product befound defective our liability shall be limited to the replacement of the product only. We reserve the account of the product of theright to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844





