

How to apply **Dulux Rust Effect** Dulux Dulux RUST RUST OLUTION

Worth doing, worth Dulux:



Turn over for details



Products You Will Need

Dulux Rust Effect base paint and Dulux Rust Effect Solution

- Quality masking tape
- A paint stirrer and drop sheet
- A wide paint brush
- Wide-top shallow container for the Rust Effect Solution

Preparation

- Carefully read and follow the instructions on the product label before you begin.
- Surface must be clean, dry and free from dust, oils and grease.
- Mask off the area with painter's tape where you don't want any paint.
- Stir the paint well with a paint stirrer using an up and down scooping action. Make sure you scrape the bottom of the can to ensure particles are evenly distributed.
- Practice your application technique on a large, spare piece of board.

Application

- Brush around the edges of the wall.
- Apply the first two coats of **Dulux Rust Effect** with a wide brush using random brush strokes. Allow 12 hours between coats.
- After 12 hours, apply 2 coats of **Dulux Rust Effect Solution** over the dry **Rust Effect** with a wide brush in random brush strokes. Apply a light mist of water to aid the rusting process. Allow 8 hours between coats.
- Rust residue may be rubbed off when touched.

Suggested Areas To Paint

• Perfect for indoor or outdoor feature walls.

Handy Tips

- Do not roll or spray.
- On exterior surfaces the rust effect will continue to develop over time.
- To avoid rub-off and run-off seal with one coat of Berger[®] Jet Dry[®] Stone & Paving Sealer in Natural finish mixed with water at a 1:1 ratio. Note that a clear coat will change the appearance of the rust effect.

Please note: For further pre-preparation and application advice, see the How To Videos available at www.dulux.com.au



www.dulux.com.au



3UNPOS-185

[®]Berger and Jet Dry are registered trade marks of Berger Paints. [®]Dulux and Worth Doing, worth Dulux are registered trade marks. Dulux Australia, 1956 Dandenong Road, Clayton, Victoria, 3168, Australia