



Briggs & Stratton 18V, 4.0Ah Battery 883252-A

Briggs and Stratton Australia Pty., Ltd.

Chemwatch: 15-80973

Version No: 3.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 29/11/2018

Print Date: 27/02/2019

L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Briggs & Stratton 18V, 4.0Ah Battery 883252-A
Synonyms	Not Available
Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Lithium-ion battery. NOTE: Chemical materials are stored in sealed case. The toxic properties of the electrode materials are hazardous only if the materials are released by damaging the cell or if exposed to fire. The sealed battery is not hazardous in normal use. The chemical hazards are related to the leaked battery contents. Lithium batteries are not subject to the transport code if they meet the requirements of special provision 188.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Briggs and Stratton Australia Pty., Ltd.
Address	3 Imperata Close Kempas Creek NSW 2178 Australia
Telephone	+61 1800 356 632
Fax	Not Available
Website	http://www.briggsandstratton.com/
Email	enquiries@briggsandstratton.com.au

Emergency telephone number

Association / Organisation	Chemwatch	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	Not Available	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 2 9186 1132

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification ^[1]	Acute Toxicity (Dermal) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Carcinogenicity Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - repeated exposure Category 2, Chronic Aquatic Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
SIGNAL WORD	DANGER

Hazard statement(s)

H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.

Continued...

H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P273	Avoid release to the environment.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		sealed metal container contains
Not Available	5-20	electrolyte salt and solvents.
21324-40-3	0.05-5	<u>lithium fluorophosphate</u>
96-49-1	5-20	<u>ethylene carbonate</u>
108-32-7		<u>propylene carbonate</u>
105-58-8		<u>diethyl carbonate</u>
105-37-3		<u>ethyl propionate</u>
24937-79-9	<1	<u>vinylidene fluoride homopolymer</u>
7440-50-8	3-15	<u>copper</u>
7429-90-5	2-10	<u>aluminium</u>
12190-79-3	20-50	<u>lithium cobaltate</u>
7782-42-5	10-30	<u>graphite</u>
Not Available	balance	steel, nickel and inert components.

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

Eye Contact	<ul style="list-style-type: none"> ▶ Generally not applicable. If this product comes in contact with the eyes: <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	Remove patient to fresh air and seek medical attention.

Ingestion	<ul style="list-style-type: none"> ▶ Not considered a normal route of entry. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.
------------------	---

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES**Extinguishing media**

- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known. Extreme mechanical or electrical stresses might cause heating and bursting of the battery. Water might react with electrolyte and may form highly toxic gaseous hydrogen fluoride.
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ May emit acrid smoke. May emit corrosive and poisonous fumes. <p>Decomposes on heating and produces toxic fumes of: carbon monoxide (CO) carbon dioxide (CO₂) hydrogen fluoride metal oxides</p> <p> Lithium ion batteries contain an inflammable electrolyte liquid which might be released at high temperatures (>150 deg C). This electrolyte might ignite if the batteries are mechanically damaged or misused. Burning batteries might ignite batteries which are stored nearby.</p>
HAZCHEM	4W

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid contact with skin and eyes. Place in suitable containers for disposal.
Major Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Wear protective clothing, safety glasses, dust mask, gloves. ▶ Secure load if safe to do so. Bundle/collect recoverable product. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Water may be used to prevent dusting. ▶ Collect remaining material in containers with covers for disposal. ▶ Flush spill area with water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling**

Safe handling	Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid physical damage to containers. Do not wet the battery with water, seawater or acid; or expose to strong oxidizer. Keep the battery away from heat and fire. Do not open the battery. Do not
----------------------	--

	crush, disassemble, drop or solder. Do not give a mechanical shock or deform.
Other information	<ul style="list-style-type: none"> ▶ Keep dry. ▶ Store under cover. ▶ Protect containers against physical damage. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. Keep out of reach of children. Store out of direct sunlight <ul style="list-style-type: none"> ▶ Store away from incompatible materials. Storage at room temperature, approx 20C.

Conditions for safe storage, including any incompatibilities

Suitable container	Store in original containers.
Storage incompatibility	▶ Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	copper	Copper, dusts & mists (as Cu)	1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	copper	Copper (fume)	0.2 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium, pyro powders (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (metal dust)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	aluminium	Aluminium (welding fumes) (as Al)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	graphite	Graphite (all forms except fibres) (respirable dust) (natural & synthetic)	3 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
lithium fluorophosphate	Lithium hexafluorophosphate	7.5 mg/m3	83 mg/m3	500 mg/m3
ethylene carbonate	Glycol carbonate; (Ethylene carbonate)	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene carbonate	Propylene carbonate, 1,2-	3.3 mg/m3	37 mg/m3	220 mg/m3
diethyl carbonate	Diethyl carbonate	12 ppm	140 ppm	810 ppm
ethyl propionate	Ethyl propionate	6.3 ppm	69 ppm	410 ppm
copper	Copper	3 mg/m3	33 mg/m3	200 mg/m3
graphite	Graphite; (Mineral carbon)	6 mg/m3	16 mg/m3	95 mg/m3

Ingredient	Original IDLH	Revised IDLH
lithium fluorophosphate	Not Available	Not Available
ethylene carbonate	Not Available	Not Available
propylene carbonate	Not Available	Not Available
diethyl carbonate	Not Available	Not Available
ethyl propionate	Not Available	Not Available
vinylidene fluoride homopolymer	Not Available	Not Available
copper	100 mg/m3	Not Available
aluminium	Not Available	Not Available
lithium cobaltate	Not Available	Not Available
graphite	1,250 mg/m3	Not Available

MATERIAL DATA**Exposure controls**

Appropriate engineering controls	General exhaust is adequate under normal operating conditions.
Personal protection	
Eye and face protection	None under normal operating conditions. OTHERWISE: <ul style="list-style-type: none"> ▶ Safety glasses.

Skin protection	See Hand protection below
Hands/feet protection	None under normal operating conditions. OTHERWISE: ▶ Rubber Gloves
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Solid shape article with no odour.		
Physical state	Manufactured	Relative density (Water = 1)	Not Applicable
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Not normally a hazard due to physical form of product. Vapors or fumes cause respiratory tract irritation.
Ingestion	Not normally a hazard due to physical form of product. Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	Not normally a hazard due to physical form of product. The electrolyte may cause skin corrosion.
Eye	Not normally a hazard due to physical form of product. The electrolyte may cause eye damage.

Chronic	Not normally a hazard due to physical form of product. [The chemicals in this product are contained in a sealed case and exposure does not occur during normal handling and use.	
Briggs & Stratton 18V, 4.0Ah Battery 883252-A	TOXICITY	IRRITATION
	Not Available	Not Available
lithium fluorophosphate	TOXICITY	IRRITATION
	Oral (rat) LD50: 50-300 mg/kg ^[1]	Not Available
ethylene carbonate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 20 mg - mild Skin (rabbit): 660 mg - moderate
propylene carbonate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2] Oral (rat) LD50: >5000 mg/kg ^[2]	Eye (rabbit): 60 mg - moderate Skin (human): 100 mg/3d-I moderate Skin (rabbit): 500 mg moderate
diethyl carbonate	TOXICITY	IRRITATION
	Not Available	Not Available
ethyl propionate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: >5000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate
vinylidene fluoride homopolymer	TOXICITY	IRRITATION
	Not Available	Not Available
copper	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Inhalation (rat) LC50: 0.733 mg/l4 h ^[1] Oral (rat) LD50: 300-500 mg/kg ^[1]	Not Available
aluminium	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available
lithium cobaltate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral (rat) LD50: >5000 mg/kg ^[1]	Not Available
graphite	TOXICITY	IRRITATION
	Inhalation (rat) LC50: >2 mg/l4 h ^[1] Oral (rat) LD50: >2000 mg/kg ^[2]	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

ETHYLENE CARBONATE	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>for ethylene carbonate</p> <p>Mammalian toxicity: Reliable acute toxicity tests are available on ethylene carbonate. Ethylene carbonate is practically nontoxic following acute oral exposure in a test that meets OECD and EPA test guidelines; the LD50 is >5000 mg/kg. The dermal LD50 is >2000 mg/kg, in a test that meets OECD and EPA test guidelines.</p> <p>Ethylene carbonate is rapidly metabolized to ethylene glycol. Following gavage administration to rats, ethylene carbonate is rapidly converted into ethylene glycol; the half-life for disappearance of ethylene carbonate from blood was 0.25 hours. As a result, the mammalian toxicity of ethylene carbonate is nearly identical to that of ethylene glycol for endpoints where both have been tested</p> <p>Ethylene carbonate was mixed in the diet of 26 male and 26 female CrI: CD(SD) rats for 18 months at concentrations of 25,000 ppm for males and females and 50,000 ppm for females; males were also fed 50,000 ppm for 42 weeks, and 40,000 ppm for 16 weeks. Survivors were observed to 24 months. Compound intake (mg/kg/day) was not reported, but is estimated to be approximately 250 and 500 mg/kg/day. No toxic effects were found in females, but increased mortality was seen in males at both dose levels. No high-dose males survived week 60 and only 10 low-dose males survived to week 78. Males had severe nephrotoxicity, characteristic of ethylene glycol toxicity.</p> <p>The following <i>in vitro</i> genotoxicity tests were conducted on ethylene carbonate, without indications of genotoxicity: an Ames mutagenicity assay, an unscheduled DNA synthesis assay using rat hepatocytes, and a cell transformation assay using BALB/3T3 cells. No <i>in vivo</i> genotoxicity studies on</p>
---------------------------	---

ethylene carbonate were found; however, ethylene glycol has been tested and was negative in a rat dominant lethal assay.

Gavage administration of ethylene carbonate to pregnant rats days 6-15 of gestation resulted in systemic toxicity at doses of 3000 mg/kg/day, including post-dose salivation. The NOAEL for maternal toxicity was 1500 mg/kg/day. Similar to ethylene glycol, there were increased soft tissue (hydrocephalus, umbilical herniation, gastroschisis, cleft palate, misshapen and compressed stomach) and skeletal malformations at 3000 mg/kg/day, but not at 1500 mg/kg/day.

For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed through the gastrointestinal tract. Limited information suggests that it is also absorbed through the respiratory tract; dermal absorption is apparently slow. Following absorption, ethylene glycol is distributed throughout the body according to total body water. In most mammalian species, including humans, ethylene glycol is initially metabolised by alcohol.

dehydrogenase to form glycolaldehyde, which is rapidly converted to glycolic acid and glyoxal by aldehyde oxidase and aldehyde dehydrogenase. These metabolites are oxidised to glyoxylate; glyoxylate may be further metabolised to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate CO₂, which is one of the major elimination products of ethylene glycol. In addition to exhaled CO₂, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination of ethylene glycol from the plasma in both humans and laboratory animals is rapid after oral exposure; elimination half-lives are in the range of 1-4 hours in most species tested.

Respiratory Effects. Respiratory system involvement occurs 12-24 hours after ingestion of sufficient amounts of ethylene glycol and is considered to be part of a second stage in ethylene glycol poisoning. The symptoms include hyperventilation, shallow rapid breathing, and generalized pulmonary edema with calcium oxalate crystals occasionally present in the lung parenchyma. Respiratory system involvement appears to be dose-dependent and occurs concomitantly with cardiovascular changes. Pulmonary infiltrates and other changes compatible with adult respiratory distress syndrome (ARDS) may characterise the second stage of ethylene glycol poisoning. Pulmonary oedema can be secondary to cardiac failure, ARDS, or aspiration of gastric contents. Symptoms related to acidosis such as hyperpnea and tachypnea are frequently observed; however, major respiratory morbidities such as pulmonary edema and bronchopneumonia are relatively rare and usually only observed with extreme poisoning (e.g., in only 5 of 36 severely poisoned cases).

Cardiovascular Effects. Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of oral ethylene glycol poisoning, which is 12-24 hours after acute exposure. The symptoms of cardiac involvement include tachycardia, ventricular gallop and cardiac enlargement. Ingestion of ethylene glycol may also cause hypertension or hypotension, which may progress to cardiogenic shock.

Mycocarditis has been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol. As in the case of respiratory effects, cardiovascular involvement occurs with ingestion of relatively high doses of ethylene glycol.

Nevertheless, circulatory disturbances are a rare occurrence, having been reported in only 8 of 36 severely poisoned cases. Therefore, it appears that acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.

Gastrointestinal Effects. Nausea, vomiting with or without blood, pyrosis, and abdominal cramping and pain are common early effects of acute ethylene glycol ingestion. Acute effects of ethylene glycol ingestion in one patient included intermittent diarrhea and abdominal pain, which were attributed to mild colonic ischaemia; severe abdominal pain secondary to colonic stricture and perforation developed 3 months after ingestion, and histology of the resected colon showed birefringent crystals highly suggestive of oxalate deposition.

Musculoskeletal Effects. Reported musculoskeletal effects in cases of acute ethylene glycol poisoning have included diffuse muscle tenderness and myalgias associated with elevated serum creatinine phosphokinase levels, and myoclonic jerks and tetanic contractions associated with hypocalcaemia.

Hepatic Effects. Central hydropic or fatty degeneration, parenchymal necrosis, and calcium oxalate crystals in the liver have been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol.

Renal Effects. Adverse renal effects after ethylene glycol ingestion in humans can be observed during the third stage of ethylene glycol toxicity 24-72 hours after acute exposure. The hallmark of renal toxicity is the presence of birefringent calcium oxalate monohydrate crystals deposited in renal tubules and their presence in urine after ingestion of relatively high amounts of ethylene glycol. Other signs of nephrotoxicity can include tubular cell degeneration and necrosis and tubular interstitial inflammation. If untreated, the degree of renal damage caused by high doses of ethylene glycol progresses and leads to haematuria, proteinuria, decreased renal function, oliguria, anuria, and ultimately renal failure. These changes in the kidney are linked to acute tubular necrosis but normal or near normal renal function can return with adequate supportive therapy.

Metabolic Effects. One of the major adverse effects following acute oral exposure of humans to ethylene glycol involves metabolic changes. These changes occur as early as 12 hours after ethylene glycol exposure. Ethylene glycol intoxication is accompanied by metabolic acidosis which is manifested by decreased pH and bicarbonate content of serum and other bodily fluids caused by accumulation of excess glycolic acid. Other characteristic metabolic effects of ethylene glycol poisoning are increased serum anion gap, increased osmolal gap, and hypocalcaemia. Serum anion gap is calculated from concentrations of sodium, chloride, and bicarbonate, is normally 12-16 mM, and is typically elevated after ethylene glycol ingestion due to increases in unmeasured metabolite anions (mainly glycolate).

Neurological Effects: Adverse neurological reactions are among the first symptoms to appear in humans after ethylene glycol ingestion. These early neurotoxic effects are also the only symptoms attributed to unmetabolised ethylene glycol. Together with metabolic changes, they occur during the period of 30 minutes to 12 hours after exposure and are considered to be part of the first stage in ethylene glycol intoxication. In cases of acute intoxication, in which a large amount of ethylene glycol is ingested over a very short time period, there is a progression of neurological manifestations which, if not treated, may lead to generalized seizures and coma. Ataxia, slurred speech, confusion, and somnolence are common during the initial phase of ethylene glycol intoxication as are irritation, restlessness, and disorientation. Cerebral edema and crystalline deposits of calcium oxalate in the walls of small blood vessels in the brain were found at autopsy in people who died after acute ethylene glycol ingestion.

Effects on cranial nerves appear late (generally 5-20 days post-ingestion), are relatively rare, and according to some investigators constitute a fourth, late cerebral phase in ethylene glycol intoxication. Clinical manifestations of the cranial neuropathy commonly involve lower motor neurons of the facial and bulbar nerves and are reversible over many months.

Reproductive Effects: Reproductive function after intermediate-duration oral exposure to ethylene glycol has been tested in three multi-generation studies (one in rats and two in mice) and several shorter studies (15-20 days in rats and mice). In these studies, effects on fertility, foetal viability, and male reproductive organs were observed in mice, while the only effect in rats was an increase in gestational duration.

Developmental Effects: The developmental toxicity of ethylene glycol has been assessed in several acute-duration studies using mice, rats, and rabbits. Available studies indicate that malformations, especially skeletal malformations occur in both mice and rats exposed during gestation; mice are apparently more sensitive to the developmental effects of ethylene glycol. Other evidence of embryotoxicity in laboratory animals exposed to ethylene glycol exposure includes reduction in foetal body weight.

Cancer: No studies were located regarding cancer effects in humans or animals after dermal exposure to ethylene glycol.

Genotoxic Effects: Studies in humans have not addressed the genotoxic effects of ethylene glycol. However, available *in vivo* and *in vitro* laboratory studies provide consistently negative genotoxicity results for ethylene glycol.

PROPYLENE CARBONATE

for propylene carbonate:

Numerous adequate and reliable acute toxicity tests are available on propylene carbonate. Oral and dermal tests meet OECD and EPA test guidelines. Propylene carbonate is practically nontoxic following acute exposures; the oral LD₅₀ is >.5000 mg/kg and the dermal LD₅₀ is >3000 mg/kg. No further testing is recommended.

Subchronic studies (13-14 weeks) of propylene carbonate by inhalation (aerosol) and oral (gavage) routes were conducted in rats according to current guidelines. The oral study indicated low systemic toxicity from propylene carbonate (NOAEL = 5000 mg/kg/day). In the inhalation study, no systemic toxicity was seen at concentrations up to 1000 mg/m³; however, there was periocular irritation and swelling in a few males at 500 and 1000 mg/m³. A dermal carcinogenicity study in mice did not indicate tumorigenic potential or systemic toxicity from 2 years of exposure to propylene carbonate. No further testing is recommended.

There is a negative Ames *in vitro* mutagenicity assay of propylene carbonate. A single intraperitoneal injection of 1666 mg/kg propylene carbonate did not induce an increase in micronuclei when examined after 30, 48 and 72 hours. The mutagenicity battery is satisfactorily filled; no further mutagenicity testing is recommended.

Gavage administration of propylene carbonate to pregnant rats days 6-15 of gestation resulted in systemic toxicity at doses of 3000 and 5000 mg/kg/day, including mortality (not seen in 13 week study of non-pregnant rats). The NOAEL for maternal toxicity was 1000 mg/kg/day. This indicates that pregnant rats are more susceptible to propylene carbonate than are non-pregnant rats. There were no significant differences in live litter size, average fetal weight, percentage of males, or malformed fetuses.

No studies of the effect of propylene carbonate on reproduction are available. However, no adverse effects on testis, ovaries, or accessory sex organs were noted in rats following oral or inhalation of propylene carbonate for 13 weeks. Therefore, reproductive effects from propylene carbonate are unlikely

DIETHYL CARBONATE	<p>Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis). Equivocal tumorigen by RTECS criteria</p>
COPPER	<p>for copper and its compounds (typically copper chloride):</p> <p>Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs.</p> <p>No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation.</p> <p>Repeat dose toxicity: In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 1.3 mg/kg bw/day for male and female rats, respectively. No deaths were observed in male rats. One treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach which result from oral (gavage) administration of copper monochloride.</p> <p>Genotoxicity: An in vitro genotoxicity study with copper monochloride showed negative results in a bacterial reverse mutation test with Salmonella typhimurium strains (TA 98, TA 100, TA 1535, and TA 1537) with and without S9 mix at concentrations of up to 1,000 ug/plate. An in vitro test for chromosome aberration in Chinese hamster lung (CHL) cells showed that copper monochloride induced structural and numerical aberrations at the concentration of 50, 70 and 100 ug/mL without S9 mix. In the presence of the metabolic activation system, significant increases of structural aberrations were observed at 50 and 70 ug/mL and significant increases of numerical aberrations were observed at 70 ug/mL. In an in vivo mammalian erythrocyte micronucleus assay, all animals dosed (15 - 60 mg/kg bw) with copper monochloride exhibited similar PCE/(PCE+NCE) ratios and MNPCE frequencies compared to those of the negative control animals. Therefore copper monochloride is not an in vivo mutagen.</p> <p>Carcinogenicity: there was insufficient information to evaluate the carcinogenic activity of copper monochloride.</p> <p>Reproductive and developmental toxicity: In the combined repeated dose toxicity study with the reproduction/developmental toxicity screening test (OECD TG 422), copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39-51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day).</p> <p>WARNING: Inhalation of high concentrations of copper fume may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever.</p>

LITHIUM FLUOROPHOSPHATE & ETHYLENE CARBONATE & DIETHYL CARBONATE & ETHYL PROPIONATE & GRAPHITE	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p>
---	---

LITHIUM FLUOROPHOSPHATE & VINYLIDENE FLUORIDE HOMOPOLYMER & ALUMINIUM & LITHIUM COBALTATE & GRAPHITE	<p>No significant acute toxicological data identified in literature search.</p>
---	---

PROPYLENE CARBONATE & ETHYL PROPIONATE	<p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling of the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p>
---	--

Acute Toxicity	✔	Carcinogenicity	✔
Skin Irritation/Corrosion	✔	Reproductivity	✘
Serious Eye Damage/Irritation	✔	STOT - Single Exposure	✔
Respiratory or Skin sensitisation	✘	STOT - Repeated Exposure	✔
Mutagenicity	✘	Aspiration Hazard	✘

Legend: ✘ – Data either not available or does not fill the criteria for classification
 ✔ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Briggs & Stratton 18V, 4.0Ah Battery 883252-A	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

lithium fluorophosphate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	42mg/L	2
	EC50	48	Crustacea	98mg/L	2
	EC50	96	Algae or other aquatic plants	43mg/L	2
	NOEC	528	Fish	0.2mg/L	2

ethylene carbonate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>100mg/L	2

Briggs & Stratton 18V, 4.0Ah Battery 883252-A

	EC50	48	Crustacea	>100mg/L	2
	EC50	96	Algae or other aquatic plants	17.388mg/L	3
	NOEC	72	Algae or other aquatic plants	100mg/L	2
propylene carbonate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2
	EC50	48	Crustacea	>1-mg/L	2
	EC50	96	Algae or other aquatic plants	12.203mg/L	3
	EC0	24	Crustacea	=500mg/L	1
	NOEC	96	Fish	1-mg/L	2
diethyl carbonate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	46.738mg/L	3
	EC50	48	Crustacea	>74.16mg/L	2
	EC50	96	Algae or other aquatic plants	3.616mg/L	3
	NOEC	96	Fish	1-mg/L	2
ethyl propionate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	4.77mg/L	2
	EC50	48	Crustacea	25.5mg/L	2
	EC50	96	Algae or other aquatic plants	2.644mg/L	3
	NOEC	504	Crustacea	1.3mg/L	4
vinylidene fluoride homopolymer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	39.014mg/L	3
	EC50	96	Algae or other aquatic plants	149.630mg/L	3
copper	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-0.09mg/L	2
	EC50	48	Crustacea	0.001mg/L	2
	EC50	72	Algae or other aquatic plants	0.013335mg/L	4
	BCF	960	Fish	200mg/L	4
	EC25	6	Algae or other aquatic plants	0.00150495mg/L	4
	NOEC	96	Crustacea	0.0008mg/L	4
aluminium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-0.134mg/L	2
	EC50	48	Crustacea	0.7364mg/L	2
	EC50	72	Algae or other aquatic plants	0.001-0.799mg/L	2
	BCF	360	Algae or other aquatic plants	9mg/L	4
	NOEC	168	Crustacea	0.001-mg/L	2
lithium cobaltate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-0.406mg/L	2
	EC50	48	Crustacea	0.002-0.618mg/L	2
	EC50	96	Algae or other aquatic plants	0.071-0.314mg/L	2
	NOEC	96	Crustacea	0.001-0.2819mg/L	2
graphite	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>100mg/L	2
	EC50	48	Crustacea	>100mg/L	2
	EC50	72	Algae or other aquatic plants	>100mg/L	2
	NOEC	72	Algae or other aquatic plants	>=100mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene carbonate	HIGH	HIGH

Continued...

propylene carbonate	HIGH	HIGH
diethyl carbonate	HIGH	HIGH
ethyl propionate	LOW	LOW
vinylidene fluoride homopolymer	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene carbonate	LOW (LogKOW = -0.3388)
propylene carbonate	LOW (LogKOW = -0.41)
diethyl carbonate	LOW (LogKOW = 1.21)
ethyl propionate	LOW (LogKOW = 1.21)
vinylidene fluoride homopolymer	LOW (LogKOW = 1.24)



Mobility in soil

Ingredient	Mobility
ethylene carbonate	LOW (KOC = 9.168)
propylene carbonate	LOW (KOC = 14.85)
diethyl carbonate	LOW (KOC = 28.08)
ethyl propionate	LOW (KOC = 11.85)
vinylidene fluoride homopolymer	LOW (KOC = 35.04)

SECTION 13 DISPOSAL CONSIDERATIONS**Waste treatment methods**

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
-------------------------------------	--

SECTION 14 TRANSPORT INFORMATION**Labels Required**

	
Marine Pollutant	
HAZCHEM	4W

Land transport (ADG)

UN number	3480				
UN proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)				
Transport hazard class(es)	<table border="0"> <tr> <td>Class</td> <td>9</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table>	Class	9	Subrisk	Not Applicable
Class	9				
Subrisk	Not Applicable				
Packing group	Not Applicable				
Environmental hazard	Environmentally hazardous				
Special precautions for user	<table border="0"> <tr> <td>Special provisions</td> <td>188 230 310 348 376 377 384 387</td> </tr> <tr> <td>Limited quantity</td> <td>Not Applicable</td> </tr> </table>	Special provisions	188 230 310 348 376 377 384 387	Limited quantity	Not Applicable
Special provisions	188 230 310 348 376 377 384 387				
Limited quantity	Not Applicable				

Air transport (ICAO-IATA / DGR)

UN number	3480						
UN proper shipping name	Lithium ion batteries (including lithium ion polymer batteries)						
Transport hazard class(es)	<table border="0"> <tr> <td>ICAO/IATA Class</td> <td>9</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> <tr> <td>ERG Code</td> <td>9F</td> </tr> </table>	ICAO/IATA Class	9	ICAO / IATA Subrisk	Not Applicable	ERG Code	9F
ICAO/IATA Class	9						
ICAO / IATA Subrisk	Not Applicable						
ERG Code	9F						

Packing group	Not Applicable	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	A88 A99 A154 A164 A183 A201 A206 A331
	Cargo Only Packing Instructions	See 965
	Cargo Only Maximum Qty / Pack	See 965
	Passenger and Cargo Packing Instructions	Forbidden
	Passenger and Cargo Maximum Qty / Pack	Forbidden
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	3480	
UN proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	
Transport hazard class(es)	IMDG Class	9
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-A , S-I
	Special provisions	188 230 310 348 376 377 384 387
	Limited Quantities	0

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION**Safety, health and environmental regulations / legislation specific for the substance or mixture****LITHIUM FLUOROPHOSPHATE(21324-40-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Chinese)
Australia Inventory of Chemical Substances (AICS)	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)
International Air Transport Association (IATA) Dangerous Goods Regulations	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)

ETHYLENE CARBONATE(96-49-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)	IMO IBC Code Chapter 18: List of products to which the Code does not apply
GESAMP/EHS Composite List - GESAMP Hazard Profiles	IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
IMO IBC Code Chapter 17: Summary of minimum requirements	

PROPYLENE CARBONATE(108-32-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	IMO IBC Code Chapter 17: Summary of minimum requirements
Australia Inventory of Chemical Substances (AICS)	IMO IBC Code Chapter 18: List of products to which the Code does not apply
GESAMP/EHS Composite List - GESAMP Hazard Profiles	

DIETHYL CARBONATE(105-58-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Inventory of Chemical Substances (AICS)	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Chinese)
GESAMP/EHS Composite List - GESAMP Hazard Profiles	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)
IMO IBC Code Chapter 17: Summary of minimum requirements	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)

ETHYL PROPIONATE(105-37-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Inventory of Chemical Substances (AICS)	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Chinese)
GESAMP/EHS Composite List - GESAMP Hazard Profiles	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)
IMO IBC Code Chapter 17: Summary of minimum requirements	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)

VINYLDENE FLUORIDE HOMOPOLYMER(24937-79-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

COPPER(7440-50-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List

Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes

Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Chinese)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)

LITHIUM COBALTATE(12190-79-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

GRAPHITE(7782-42-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

National Inventory Status

National Inventory	Status
Australia - AICS	No (electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Canada - DSL	No (lithium fluorophosphate; electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Canada - NDSL	No (diethyl carbonate; vinylidene fluoride homopolymer; copper; graphite; ethyl propionate; ethylene carbonate; aluminium; lithium cobaltate; propylene carbonate; electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
China - IECSC	No (electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Europe - EINEC / ELINCS / NLP	No (vinylidene fluoride homopolymer; electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Japan - ENCS	No (copper; graphite; ethyl propionate; aluminium; lithium fluorophosphate; electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Korea - KECI	No (electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
New Zealand - NZIoC	No (lithium fluorophosphate; electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Philippines - PICCS	No (lithium cobaltate; electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
USA - TSCA	No (electrolyte salt and solvents.; steel, nickel and inert components.) Non-disclosed ingredients
Legend:	Yes = All ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	29/11/2018
Initial Date	27/11/2018

Other information**Ingredients with multiple cas numbers**

Name	CAS No
propylene carbonate	108-32-7, 51260-39-0, 16606-55-6
copper	7440-50-8, 133353-46-5, 133353-47-6, 195161-80-9, 65555-90-0, 72514-83-1
aluminium	7429-90-5, 91728-14-2

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.