



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

BONDALL MONOCEL GOLD SPRAY-PAK

REVISED: MAY 2004

DESCRIPTION

Monocel Gold is a high performance single pack, clear finish for timber used in marine or harsh exterior situations and is suitable for interior and exterior applications. It provides maximum exterior durability and colour retention.

Monocel Gold is suitable for plywood, outdoor furniture, timber paneling, architraves, marine trim and most other timber surfaces, but is not recommended for use on rough sawn timbers. Some cork surfaces may also be unsuitable and should be tested first.

FEATURES AND BENEFITS

- Convenient aerosol pack
- Ready to use
- Abrasion and yellowing resistant
- Added Nano Z protection

SURFACE PREPARATION

Surface preparation is important. All surfaces should be free from grease, grime, dust and other contaminants and fine sanded. All sharp corners and edges should be rounded off and then thoroughly dusted.

All previous paint, varnishes, shellac or lacquer must be totally removed before coating with Monocel Gold. A wood stain can be applied at this stage if required.

Allow to dry for 24 hours before lightly sanding and proceeding with subsequent coats.

APPLICATION

- Shake the can for one full minute after you hear the pellet rattling. Adjust the fan jet on the can as required.
- Keep the can approximately 25cm from the surface at all times while spraying.
- Spray with slow, even strokes, beginning and ending each stroke beyond the surface being coated.
- Apply light coats. Recoat between 5 and 50 minutes, or for optimum build leave for 8 hours, then lightly sand and recoat.

COVERAGE

Approximately 2.2 square metres per can contents, depending on texture and porosity of surface.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

THINNING

Not applicable

GLOSS LEVEL

Satin & Gloss Finishes

DRYING TIME

8 hours under normal drying conditions (20°C, 50% humidity). Do not use below 10°C or if temperature exceeds 35°C.

CLEAN UP

Wash all equipment in mineral turps. After use, turn the can upside down and depress nozzle for one second to clear the fan jet.

COLOUR

Clear

SIZES

Available in 300 gram

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation

If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass of water to drink and do not induce vomiting. A Material Safety Data Sheet is available on request.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

