

Technical Data Sheet



LiquidStone Colours

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description

Diamondcoat LiquidStone is a unique natural stone effect coating for interior and exterior use. suited to wide variety of surfaces LiquidStone will quickly transform old garden ornaments and small areas of concrete into a contemporary stone finish.

Features and Benefits

- | | |
|--|---|
| <ul style="list-style-type: none"> • Attractive stone finish • Water based / easy to use | <ul style="list-style-type: none"> • Available in 4 colours and finishes • Long lasting |
|--|---|

Area of Use

- | | |
|--|--|
| <ul style="list-style-type: none"> • Small paved areas / Patios / Courtyards • Statues | <ul style="list-style-type: none"> • Pots • Decorative walls |
|--|--|

Technical Data

Number of Coats:	2	Curing time:	7 days
Spreading Rate Per Coat:		Colour:	Basalt, Sandstone, Limestone, Terracotta
1 st Coat	2-4m ² /L	Shelf Life:	12 months
2 nd Coat	2-4m ² /L		
Wet Film Per Coat:	200-400 microns		
Recoat (@25°C):	2 hours		

Application Guide

Surface Preparation

- On newly paved areas remove all loose material with a dry stiff bristle broom.
- Any Algal mould or moss growth should be removed with diluted Chlorine or Bleach.
- Where necessary remove any grease or oil stains with DiamondCoat Paving Cleaner. Rinse clean with fresh water.

Application Procedure and Equipment

- Prior to application s small test area should be carried out to ensure the desired finish will be achieved.
- All surfaces should be thoroughly dry before application.
- Porous surfaces should be properly primed with LiquidStone Surface Primer prior to application.
- Each coat should be applied achieving a solid coating providing complete coverage, however excessively thick coats should be avoided.
- LiquidStone is best applied using either a medium bristle brush or small nap roller.

Technical Data Sheet



LiquidStone Colours

7 Day Technical Support 1800 655 711

Precautions

- Do not apply if humidity is above 85% or if rain or dew is imminent.
- Do not apply if temperature is over 35°C or under 5°C. Where hot windy conditions occur, apply in the morning.

Cleaning

- Application equipment and tools can be cleaned up with fresh water before the product dries.

Health and Safety

Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- Wear eye protection.
- Wear PVC or neoprene gloves. Avoid contact with skin.
- If product is splashed on skin it should be washed off with water before it can dry.
- Keep out of the reach of children.

First Aid

- Swallowed: If poisoning occurs contact a doctor or Poisons Information Centre. Do not induce vomiting. Risk of aspiration into lungs. Give water to drink.
- Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.
- Skin: Remove contaminated clothing and gently flush affected areas with soap and water. Seek medical attention if irritation develops. Launder clothing before re-use.
- Inhalation: Remove patient from exposure, into fresh air. Apply artificial respiration if patient has stopped breathing. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin. In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	1L	Flash Point:	0
Weights:	1Kg	UN Number:	0
Dangerous Goods Class:	0	Poisons Schedule:	0
Hazchem Code:	0		

Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.