

# AUSTRALIAN BUILDERS™

## MORTAR MIX



**Building  
Products  
Supplies**



Australian Builders Mortar Mix is a premium quality - Australian Made DRY MIX blend of Cement Sand & Lime. Conveniently packed to ensure the correct amount of product for the job at hand. Just add water! Conforms to AS 3700.

### APPLICATIONS:

Australian Builders Mortar Mix is ideally suited for many home maintenance & renovation requirements such as:

- BUILDING BRICK WALLS
- BUILDING A BRICK BARBECUE
- CEMENTING BLOCKS
- RENDERING OVER BRICK OR CONCRETE AND MASONRY SURFACES
- SETTING ROCK AND STONE BORDERS
- BEDDING IN OF PAVING SLABS
- DRY SWEPT PAVING JOINT FILLING



### PRODUCT FEATURES:

- Premium Quality
- Australian Made
- Conforms to AS 3700
- Professional Finish
- High Performance Product
- Ready-to-use just add water
- Interior & Exterior Usage
- Hard Wearing & Durable

### DON'T FORGET:

- Excess water will decrease strength & workability of mortar and render mixes
- Always follow Safety, Usage & Handling Directions
- Avoid creating & breathing in dry mix mortar dust
- Clean tools immediately after use with water

### AVAILABLE IN

20, 30 & 40kg bags

### DIRECTIONS FOR USE:

Empty contents into a wheel barrow or onto a smooth non-porous clean surface.

Mix thoroughly using the least amount of water to obtain the correct workability, (excess water will decrease strength of mortar & render mixes).

Use immediately after mixing.

Always compact your mortar thoroughly.

Fully cure your finished mortar by keeping it moist and/or covered for a least 7 days before using it.



BUILDING PRODUCTS SUPPLIES - AUSTRALIAN BUILDERS MORTAR MIX

Building Products Supplies Pty Ltd

750 Lorimer Street Port Melbourne, Victoria, Australia. 3207. ABN 95 006 150 036

Telephone: 03 9676 0060 Facsimile: 03 9646 4954 info@bpsaust.com [www.bpsaust.com](http://www.bpsaust.com)

# AUSTRALIAN BUILDERS™ MORTAR MIX



Building  
Products  
Supplies



**Important Consumer Information:** Please read safe handling & usage advice before opening bag.

## SAFE STORAGE:

Portland Cement products should be stored in a dry dark environment, away from child access, preferably in a locked storage area.

Portland Cement when damp becomes Alkaline and exposure to it may be harmful to your skin and cause eye irritation. Always read safety directions on packaging prior to opening bag and using product.

## PRODUCT LIFE:

Portland Cement products when stored correctly will last up to 6 months from date of manufacture. Once opened the contents should be used the same day.

## HANDY HINT:

For best results only use clean water. Add water to mixture not mixture to water.

Avoid working in excessive heat or cold temperatures. Optimum working temperature is between 15-30° Celsius.

## HAZARDOUS: Portland and Blended Cements.

**Contents:** Portland Cement chemicals >60%. Calcium Hydroxide 10-30%. Crystalline Silica <1%. Non-hazardous ingredients to 100%.

**Note:** Crystalline Silica, (quartz), is present as an impurity.

**Risk:** Cement dust may cause respiratory, skin and eye irritation.

Wet cements can be irritating and corrosive to the eyes and skin; and may cause skin sensitisation (dermatitis). Repeated inhalation of dust containing crystalline silica may cause bronchitis, silicosis (scarring of the lung) and lung cancer, & increases the risk of Scleroderma.

**Safety:** Avoid contact with eyes and skin from both wet and dry cement. Do not breathe in dust. Wear suitable protective clothing, including gloves or barrier cream, foot wear and eye protection. Wear a P1 or P2 dust mask suitable for particulates when exposed to dust. When cutting or abrading concrete keep it wet with water to avoid creation of hazardous dust. Always wear suitable protective clothing and respiratory protection. Wash thoroughly after handling. Wash work clothes regularly.

**First Aid:** Irrigate eyes with plenty of water for 15 minutes and seek medical attention. If inhaled remove from dusty area. Seek medical attention if symptoms persist. Wash skin with water.

**Spills/Leaks:** Keep out of sewers and storm water.

**Disposal:** Follow above safety instructions and collect in containers for disposal as trade waste in accordance with local authority guidelines.

**Manual Handling:** Cement bags (16-40kg) are heavy, lifting them without due care and attention can result in personal injury. Unless you are trained in manual handling of heavy loads, it is best you share the load with another person.

**DISCLAIMER:** Building Products Supplies Pty Ltd products are premium quality and when used in accordance with directions, will produce consistent excellent results. However Building Products Supplies Pty Ltd accepts no responsibility for end-users inappropriate usage or faulty workmanship.



**PROUDLY AUSTRALIAN MADE**

Additional consumer information is listed in the material data sheet for this product, available from the manufacturer:

Building Products Supplies Pty Ltd

750 Lorimer Street Port Melbourne, Victoria, Australia. 3207. ABN 95 006 150 036

Telephone: 03 9676 0060 Facsimile: 03 9646 4954 info@bpsaust.com [www.bpsaust.com](http://www.bpsaust.com)