

# Dulux®

# RENOVATION

RANGE TRANSFORMATION MADE EASY

## FLOORS

EASY HOW-TO PROJECT GUIDE



Dulux  
Malay Grey



# FLOORS

Dulux® Renovation Range Floors is a revolutionary, water based interior coating that is perfect for transforming your floor in your kitchen, bathroom or laundry.

## Shopping List

- ✓ Dulux® Renovation Range Floors in your chosen colour
- ✓ Dulux® Renovation Range Clear Coat
- ✓ 38–50mm high quality angled sash cutter
- ✓ 4mm nap 100mm wide microfibre roller
- ✓ Paint stirrer and drop sheet
- ✓ Painters tape
- ✓ P400 sanding paper
- ✓ Selleys® Sugar Soap
- ✓ Selleys® Silicone Remover
- ✓ Selleys® Rapid Mould Killer™

### EXPERT TIP

Floor polishes containing wax or silicone additives MUST be completely removed prior to using Dulux Renovation Range.

## Preparation

Dulux Renovation Range Floors, requires a clean surface to adhere. All grease and dirt contamination MUST be removed, or the paint will not adhere and will peel or flake off.

### Previously Painted Surfaces:

On ALL surfaces cleaning is the most important step.

- Scrub down all areas with Selleys® Sugar Soap and rinse with clean water to remove any dirt, oil or grease. Use a plastic scouring pad on heavily contaminated surfaces.
- Repeat this process using clean water, at least twice.

IMPORTANT: Do not use abrasive cleaning detergents.

- Completely remove any loose and flaking paint. Fill any cracks or holes with a suitable hard epoxy based filler such as Selleys® Knead-IT® Aqua.
- Sand glossy and semi gloss finishes to a dull flat finish using p400 paper before coating.
- Use a clean damp cloth to remove any dust.

### Floor Tiles:

- For grout lines ensure to remove all grease and oil.
- Thoroughly clean surface using Selleys® Rapid Mould Killer™. Remove all silicone sealant from joints using Selleys® Silicone Remover.

- Wash down well with water.
- Sand with p400 paper all areas where silicone has been removed.
- Clean again with Selleys® Rapid Mould Killer™ and wash with Selleys® Sugar Soap. Use a scrubbing brush or a toothbrush to properly clean grout lines.
- Rinse with clean water and dry with a clean cloth.
- Allow grout lines to dry for a minimum 2 hours before painting. Mask using a good quality painters tape.

## Mixing:

Add all of the Additive found underneath the blue lid to the paint.

Stir well for approximately 2-5 minutes with a broad flat paddle, using an up and down scooping action until the additive is completely mixed into the paint.

Once mixed the product is suitable to use for up to 10 days.



Sand surface



Add the additive and mix together

## Application

### Topcoat

After the additive has been added and stirred, apply at least two coats of *Dulux Renovation Range Floors* ensuring that the previous coat is left for a minimum of 8 hours before recoating.

1. Cut in as necessary using a 38–50mm high quality angled sash cutter brush.
2. Coat surface using a 4mm nap 100mm wide microfibre roller.
3. Lay off. Once each section is coated, gently go over the surface in the same direction with an unloaded roller using minimal pressure. This will give a smooth consistent finish.

Note: Some colours may require more than 2 coats, especially when painting over dark colours.

When applying to tiles the grout lines will be covered as well. To refresh or re-whiten grout lines, use the *Dulux Renovation Range Grout Pen*.



Scrub tiles before applying topcoat



Roll on topcoat

# THE PERFECT RENOVATION SYSTEM

This revolutionary range works as a three step system. For the best possible result, ensure you always follow all three steps.\*

## 1. CLEAN & PREP



### Cleaning

Clean with Selley's®  
Sugar Soap.

## 2. TOPCOAT



### Topcoat

Floors.

## 3. FINAL TOUCHES



### Clear Coat

Available in satin and  
gloss clear coat.

## NEED HELP & ADVICE?



CALL: Aust 13 25 25  
NZ 0800 800 424



ONLINE & LIVE CHAT:  
[dulux.com.au](http://dulux.com.au), [dulux.co.nz](http://dulux.co.nz)



For 'How To' videos,  
helpful tips and more,  
scan here!

FRONT COVER: Floors: **Dulux Renovation Range Floors** in *Dulux Malay Grey*.

Disclaimers: Colours shown are as close as possible to actual paint colours. Please note, due to limitations of the printing process, photographic and printed images may not represent the true colour. Always confirm your choice with a *Dulux* Sample Pot.

\*For full use instructions please see the *Dulux* website and review the Data Sheet, Application and FAQ information. †The *Dulux* Renovation Range Floor product does not require a clear coat as it will reduce the non-slip performance.

Registered trade mark information: Dulux, Worth doing, worth Dulux, Selley's and Knead-IT are registered trademarks and Rapid Mould Killer is a trade mark of DuluxGroup (Australia) Pty Ltd.