



RBC254SESO / RPP254JO / RLT254CDSO / RLT254SDSO


⚠ WARNING: This procedure sheet is not a substitute for reading the operator's manual. To reduce the risk of injury, the user must read and understand the operator's manual before using the product.


TO START A COLD ENGINE:

1  50:1 Ratio = Mix 20 mL of synthetic 2-stroke oil per litre of petrol. Ensure the fuel is fresh and is correctly mixed before pouring into the fuel tank.

2  Slowly press the primer bulb 10 times or until the fuel appears.

3  Set the choke lever to "full" choke position.


4  Hold down the throttle lock, and then squeeze the throttle trigger.


5  Using manual operation:
Pull the starter grip and rope (4x maximum) until the engine attempts to start.


or

Using ONE+ EASYSTART Module:



Set the ONE+ EASYSTART Module to  , insert into the starter housing, and then press the ONE+ EASYSTART's power button until the engine attempts to start (**4 seconds maximum**).


6  Set the choke lever to "half" choke position.

7  Using manual operation:
Pull the starter grip and rope (6x maximum) until the engine starts.


or

Using ONE+ EASYSTART Module:





Set the ONE+ EASYSTART Module to  , insert into the starter housing, and then press the ONE+ EASYSTART's power button until the engine starts (**4 seconds maximum**).


NOTE: If the engine does not start, repeat the procedure from step 3 until the engine starts.


8  Allow the engine to warm for 10 seconds. Set the choke lever to "run" position.

TO START A WARM ENGINE:

1  Slowly press the primer bulb 10 times or until the fuel appears.

2  Set the choke lever to "run" position.


3  Hold down the throttle lock and then squeeze the throttle trigger.

4  Pull the starter grip and rope until the engine runs. Do not pull the starter grip more than six times.

or

Using ONE+ EASYSTART Module:



Set the ONE+ EASYSTART Module to  , insert into the starter housing, and then press the ONE+ EASYSTART's power button (**4 seconds maximum**).

TO STOP THE PRODUCT:

9  Push the on/off switch to the "off" position.

