

# POT & ORNAMENT SEALER

REVISED OCT 2001

#### DESCRIPTION

OC0003

Bondall Pot & Ornament Sealer is an easy to use masonry sealer. This versatile sealer is the ideal choice for sealing pots and ornaments, after they have been suitably prepared with Bondall Pot & Ornament Cleaner. It will seal, bind, protect and waterproof most vertical masonry surfaces while still retaining a clear natural look. Bondall Pot and Ornament Sealer increases surface hardness; reduces staining and soiling; resists algal and fungal growth; and offers outstanding exterior durability.

TEST AREA - Always test on a small inconspicuous area, to ensure that the product achieves the desired result, prior to application over the entire area.

#### FEATURES AND BENEFITS

- Easy to use
- Seals pots and ornaments
- Seals, binds, protects and waterproofs most vertical masonry surfaces
- · Provides a clear natural finish
- · Increases surface hardness
- Prevents staining and soiling
- Resists algal and fungal growth
- Very durable

#### **SURFACE PREPARATION**

Surface should be thoroughly clean, using Bondall Pot & Ornament Cleaner, as any stains will become more apparent once sealed.

Bore & Rust Stains, Efflorescence Stains and Moss & Mould growth should be treated prior to sealing.

Please refer to Bondall range of appropriate cleaners to prepare the surface.

#### **APPLICATION**

Stir well before use. DO NOT SHAKE contents, as shaking can induce bubbles, which can be trapped on the surface.

Apply all coats undiluted and allow a minimum of 24 hours between coats.

Proper penetration of the first coating is very important.

Care should be taken to apply evenly and not too heavily on pitted surfaces.

It is important not to apply Bondall Pot & Ornament Sealer externally if rain is expected within 48 hours. Do not use in temperatures below 10 \( \text{IC}.







bondal@bondal.com



## **COVERAGE**

On extremely porous surfaces Bondall Pot & Ornament Sealer will cover approximately 6 square metres per litre. On dense surfaces, coverage will be approximately 10 – 12 square metres per litre. Cover age rate is very much dependant on porosity and texture of the surface.

## **THINNING**

Not Applicable

## **GLOSS LEVEL**

Not applicable

#### **DRYING TIME**

Allow a minimum of 24 hours drying time between coats.

## **CLEAN UP**

Wash brushes out whilst wet with water and detergent. Do not pour washings down sink or drains. Dispose of all containers in accordance with local council regulations.

## **COLOUR**

Clear

#### **SIZES**

1 Litre and 4 Litre

## PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed.

If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give water to drink and do not induce vomiting.









113 Belmont Ave Belmont WA 6104

PO Box 111

P: 08 9277 6844 F: 08 9277 4068

bondal@bondal.com



## **DISCLAIMER**

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for anyloss, consequential or otherwise, arising from the use of this product. Should the product befound defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844





