



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

TERRACOTTA SEALER

REVISED: OCTOBER 2004

DESCRIPTION

Tileguard Terracotta Sealer is a clear penetrating solution that waterproofs terracotta tiles without leaving a slippery film coating. It is suitable for most unglazed surfaces.

TEST AREA. Always test on a small inconspicuous area, to ensure that the product is achieving the desired result, or that it does not discolour the tiles prior to application over the entire area.

FEATURES AND BENEFITS

- Water resistant
- User friendly
- Resilient to household chemicals
- Latest technology
- Non-slip

SURFACE PREPARATION

- Clean tiles and grout using Tileguard Tile & Grout Cleaner. Rinse thoroughly with water after cleaning.
- Remove and patch all loose or missing tile grout. For improved quality use Bondall Hydrocrete as an additive in the grout.
- Application area should be dry for approximately 12-24 hours before applying Terracotta Sealer.

APPLICATION

- Stir well before use, DO NOT SHAKE. Use a 25mm broad timber or metal paddle and stir with a lifting motion to incorporate the entire product.
- Apply one coat of Terracotta Sealer as an initial sealer coat and allow to dry for 4 to 6 hours. Apply a final coat of Terracotta Sealer to the entire surface.
- Apply Terracotta Sealer with a good quality paintbrush, applicator pad or spray.
- Do not apply if the temperature is below 10°C or if rain is expected within 24 hours.
- Ensure adequate ventilation during use.

COVERAGE

Terracotta Sealer will treat approximately 5 square metres per litre depending on the texture, porosity and method of application.

THINNING

Not recommended



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

GLOSS LEVEL

Not applicable.

DRYING TIME

Terracotta Sealer will be touch-dry in 2 hours. Drying times are a guide only. Longer drying times may be required in cooler or humid conditions.

Allow drying for as long as possible before full use, light foot traffic is permissible after 4-6 hours depending on weather conditions at the time. Allow at least 24 hours before allowing heavy traffic. Optimum coating properties achieved after 7 days.

CLEAN UP

Clean all equipment up with water. Do not pour contents or washings down drains or sinks. Dispose as per your local council regulations.

COLOUR

Slightly yellow

SIZES

Available in 1 Litre and 4 Litre containers

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation. Use a suitable respirator if spray application is employed. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass of water to drink and do not induce vomiting.

DISCLAIMER

The performance of this product is dependant upon its correct preparation, application onto sound surfaces and attention to the instructions on the label. The wide variety of surface conditions make it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specification and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Advisory Service on 1800 810 123 or (08) 9277 6844. See Web Site: www.bondall.com



Wholly Australian Owned & Manufactured

the solution  bondall

