bondall@bondall.com



GP PRIMER SEALER

REVISED MAY 2007

DESCRIPTION

WC 0009

Bondall TimberEffects GP Primer Sealer is a WATERBASED coating designed for application to fibre cement and similar stable substrates prior to application of Bondall TimberEffects. It is based on a blend of resins specially chosen for their substrate binding characteristics and provides an excellent key for Bondall TimberEffects.

FEATURES AND BENEFITS

- Excellent adhesion to fibre cement, MDF and other similar stable substrates.
- Promotes excellent inter-coat adhesion.
- Provides a neutral background.
- Assists to overcome substrate colour variations.
- Easy to use, easy clean up and non toxic.

SURFACE PREPARATION

All surfaces to be coated must be clean, dry and free of oil, grease and dirt. Any existing coating must be checked for good adhesion. Any loosely adhered coating must be removed and bare surfaces must be prepared, clean and dry. All nail holes should be filled with a water based filler. Sand the filler back prior to coating.

APPLICATION

Bondall TimberEffects GP Primer Sealer is ready to use. No thinning is required. Stir well before use with a broad flat paddle. Apply one coat with a good quality dry brush. Brisk, uniform application is essential to maintain a wet edge, especially in hot weather. Re-Coating time is 1hr. Do not apply in temperatures below 10°C.

COVERAGE

The approximate coverage is 6 - 8 m /L

THINNING

Not Applicable

DRYING TIME

Bondall TimberEffects GP Primer Sealer is quick drying. Drying time is 1hr depending on temperature, humidity and other weather conditions







F: 08 9277 4068



CLEAN UP

Cleans easily. Wash brushes out whilst wet with water and detergent. Do not pour washings down sink or drains. Dispose of all containers in accordance with local council regulations.

COLOUR

Light grey

SIZES

1 Litre & 4 Litre Containers

PRECAUTION/FIRST AID

Avoid contact with skin and eyes. Should contact occur to the eyes, flush with plenty of water and seek medical attention should irritation take place. If ingested, DO NOT induce vomiting. Give plenty of water to drink. Seek medical advice immediately.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for anyloss, consequential or otherwise, arising from the use of this product. Should the product befound defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844





