

Retract Away Mounting Options

Wall to Wall

Products required

- ✓ 1x Retract Away 40 or 50 Cabinet

Fittings supplied

- ✓ **Cabinet:** Catch (Hook), 2x ZP washers

You will require

- ✓ **For masonry walls:** 4x 8x75mm screws, 4x 10x75mm plugs
- ✓ **For timber walls:** 8x75mm screws, 10mm drill bit

Wall to Post

Products required

- ✓ 1x Retract Away 40 or 50 Cabinet, 1x Post, Ground Socket optional

Fittings supplied

- ✓ **Cabinet:** Catch (Hook), 2x ZP washers
- ✓ **Post:** 2 x M8x65mm Hex head bolts, 2 x M8 Hex nuts, Post Cap

You will require

- ✓ **For masonry walls:** 2 x 8x75mm screws, 2x 10x75mm plugs, 10mm drill bit
- ✓ **For timber walls:** 2 x 8x75mm screws
- ✓ **For Post:** Concrete mix, gravel, 2x 13mm spanners/shifters
- ✓ **For Plated Post:** 4 x M6 Galvanised masonry screws/screw bolts (per post)

Post to Wall

Products required

- ✓ 1x Retract Away 40 or 50 Cabinet, 1x Post, 1x Mounting Bar, Ground Socket optional

Fittings supplied

- ✓ **Cabinet:** Catch (Hook), 2x ZP washers
- ✓ **Post:** 2x M8x65mm Hex head bolts, 2x M8 Hex nuts and Post Cap
- ✓ **Mounting Bar:** 2x 8x90 Hex bolts and nuts, 2x M8x40 Hex bolts and nuts, 4x washers

You will require

- ✓ **For masonry walls:** 2x 8x75mm screws, 2x 10x75mm plugs, 10mm drill bit
- ✓ **For timber walls:** 2x 8x75mm screws
- ✓ **For Post:** Concrete mix, gravel, 2x 13mm spanners/shifters
- ✓ **For Plated Post:** 4 x M6 Galvanised masonry screws/screw bolts (per post)

Post to Post

Products required

- ✓ 1x Retract Away 40 or 50 Cabinet, 2x Posts, 1x Mounting Bar, Ground Socket optional

Fittings supplied

- ✓ **Cabinet:** Catch (Hook), 2x ZP washers
- ✓ **Post:** 2x M8x65mm Hex head bolts, 2x M8 Hex nuts and Post Cap.
- ✓ **Mounting Bar:** 2x 8x90 Hex bolts and nuts, 2x M8x40 Hex bolts and nuts, 4x washers

You will require


- ✓ **For Posts:** Concrete mix, gravel, 2x 13mm spanners/shifters
- ✓ **For Plated Posts:** 4 x M6 Galvanised masonry screws/screw bolts (per post)



↑ Retract Away 40 or 50 Cabinet



← Retract Away Catch
Galvanised finish



Welded Plate Base:
100mmW x 150mmD x 6mmH
Each plate requires 4 x M6 Galu.
masonry screws/screw bolts.
Min. embedment 45mm

← Retract Away Post and
Retract Away Plated Post



← **Ground Socket**
with galvanised
Pin and Cap

The galvanised Pin is punched through the side of the Ground Socket, to set the height of Retract Away Posts and Fold Away Columns



↑ Mounting Bar



Woodland Grey models shown