



How to enhance and protect slate

CROMMELIN SLATE SEALER & WATER BASED SLATE SEALER are penetrating treatments to protect and lift natural colours on old and new slate surfaces.

How to enhance & protect slate

Both SLATE SEALER & WATER BASED SLATE SEALER are ideal for use on all slate surfaces and most terracotta surfaces. They enhance the natural colours and leave a high gloss finish that is easy to clean.



YOU WILL NEED

1 litre of each product will coat approximately 6-7m² of slate.



EQUIPMENT

Both SLATE SEALERS are easily applied by brush or roller.



NUMBER OF COATS

2 coats are required to give a hardwearing finish to your slate.



DRYING TIME

Allow 30 minutes between coats.

Leave for 4 hours to cure before walking on the floor.



CLEAN UP

Please refer to the specific product label for the most effective method of clean up.



TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

Freecall Technical Advice 7 days: 1800 655 711
www.crommelin.com.au

 **Crommelin**

SOLUTIONS FOR CONSTRUCTION



Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is proven defective, our liability is limited to the replacement of the product.