

© CrommelinSealers



# How to seal & protect pavers

**CROMMELIN CONCRETE PAVING SEALER, WATER BASED PAVING SEALER & POOL PAVING SEALER** provide durable and long lasting protection to a wide variety of paving and stencilled/patterned concrete surfaces.

# How to seal & protect pavers

Ideal for all your paving sealing requirements, the Crommelin range of sealers will resist staining and protect your pavers to keep them looking like new.



## YOU WILL NEED

1 litre of each of these products will cover approximately 3-5m<sup>2</sup> depending on the porosity of the paved area.



## EQUIPMENT

These products are easily applied by brush, roller or spray.



## NUMBER OF COATS

2 coats are required to give a good stain and water repellent seal to paved surfaces.



## DRYING TIME

Allow 30 minutes drying time between coats.  
Allow 2 hours before walking on the surface.



## CLEAN UP

Please refer to the specific product label for the most effective method of clean up.



## TIPS

Apply to a dry surface. To test for moisture, tape down a clear plastic sheet over a small section of the surface to be treated in direct sunlight and leave for 2 hours. If moisture appears on the underside of the sheet the area is too damp.

For detailed instructions on suitability, surface preparation and application steps, please refer to the product label.

Should you have any project specific questions or require further product information please do not hesitate to contact us.

**Freecall Technical Advice 7 days: 1800 655 711**  
**[www.crommelin.com.au](http://www.crommelin.com.au)**



SOLUTIONS FOR CONSTRUCTION



Customers are advised to undertake their own assessment to determine suitability of a product for the particular use intended. Due to the performance of any product being subject to a wide variety of field and surface conditions we are unable to assume liability for any loss, consequential or otherwise that may arise from the use of our products. Where a product is proven defective, our liability is limited to the replacement of the product.