

## Technical Data Sheet

# Water Based Paving Sealer

Sealers

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

### Description

**Water Based Paving Sealer** provides a clear, transparent, non-silicone water repellent coating that will enhance and protect the appearance of low and medium porosity building materials. The hard film is resistive to water damage, disfigurement by airborne pollutants and its water repellent properties are supplemented by a highly effective biocide to inhibit the growth of fungi, algae and lichens. **Water Based Paving Sealer** is both trafficable and highly resistant to UV light. The use of **Water Based Paving Sealer** under other waterborne finishes will improve their performance and durability. **Water Based Paving Sealer** can be applied over cured decorative coatings that do not show signs of chalking.

### Features and Benefits

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Clear satin to gloss finish</li> <li>• Hard wearing</li> <li>• Resists stains and damage to substrate</li> <li>• Resists algal and other growth</li> </ul> | <ul style="list-style-type: none"> <li>• UV stable</li> <li>• Safe and easy to use</li> <li>• Highly water repellent</li> </ul> |
|---|---|

### Area of Use

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Concrete pavers</li> <li>• Reconstituted stone pavers</li> <li>• Stencilled concrete</li> </ul> | <ul style="list-style-type: none"> <li>• Clay pavers</li> <li>• Natural stone</li> </ul> |
|--|--|

### Technical Data

Number of Coats:	2 or more	Curing time:	7 days
Spreading Rate Per Coat:	10-12m <sup>2</sup> /L	Colour:	Clear (satin to gloss)
Wet Film Per Coat:	85-100 microns	Thinner:	Water
Recoat (@25°C):	1 hour	Shelf Life:	12 months

### Application Guide

#### Surface Preparation

- Clean surfaces of all contaminants such as efflorescence, mould, lichen, etc. Remove all grease, dust or dirt. Wash surface with water and scrubbing brush, rinse and allow to dry thoroughly.

#### Application Procedure and Equipment

- May be applied by brush, roller or spray depending on surface to be treated.
- For best protection results apply two coats.
- For the 1<sup>st</sup> coat, mix 2 parts **Water Based Paving Sealer** to 1 part water (2:1).
- Apply a thin but even wet coat (do not try to achieve too high a build).
- Allow to dry for approximately 15 minutes.
- When dry apply a 2<sup>nd</sup> coat of unthinned **Water Based Paving Sealer**.  
Gloss (from satin to gloss) will vary with porosity and amount of **Water Based Paving Sealer** applied. For a higher gloss, apply further coats.

## Technical Data Sheet

# Water Based Paving Sealer

Sealers

7 Day Technical Support 1800 655 711

### Precautions

- Do not apply if air or surface temperature is below 10°C, if relative humidity is above 85% or if rain is imminent.
- Not recommended for use on glazed/glassy surfaces such as some ceramic tiles.
- Must be applied to a dry substrate.
- Take care in wet, oily or other extreme conditions as the surface can become slippery.

### Cleaning

- Clean all equipment with water before product dries.

### Health and Safety

#### Safety Precautions

- Provide good ventilation – open windows and doors and use circulating fans.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear gloves and eye protection during application.

#### First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.

Eye: Gently flush with running water, holding eyelids open for 15 mins. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin.

In the case of an emergency please call the Poisons Information Centre on 13 11 26

### Transport and Storage

Sizes:	1L, 4L, 15L	Flash Point:	N/A
Weights:	1Kg, 4.5Kg, 16Kg	UN Number:	N/A
Dangerous Goods Class:	N/A		

### Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.