

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 615-LINE DULUX CEILING PAINT

**Recommended Use:** Surface coating. Applied by brush, roller or spray.

Supplier: Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd

**ABN:** 67 000 049 427

Street Address: 1956 Dandenong Road,

Clayton, Victoria

Australia

**Telephone Number:** +61 3 9263 5678 **Facsimile:** +61 3 9263 5777

Emergency Telephone: 1 800 033 111 (ALL HOURS)

### 2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail: NON-DANGEROUS GOODS.

Poisons Schedule: None allocated.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Pigments	-	30-60%	-
Water	7732-18-5	30-60%	-
Synthetic polymer(s)	-	30-60%	-
Ingredients determined not to be hazardous	-	to 100%	-

## 4. FIRST AID MEASURES

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

#### **Skin Contact:**

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

#### **Eve Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

### Ingestion:

Substance No: 000014542708

Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical advice.

Product Name: 615-LINE DULUX CEILING PAINT Issued: 13/04/2010

Version: 4



#### Medical attention and special treatment:

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES

### Hazards from combustion products:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes.

### Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

### Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

# 6. ACCIDENTAL RELEASE MEASURES

### **Emergency procedures:**

If contamination of sewers or waterways has occurred advise local emergency services.

### Methods and materials for containment and clean up:

SMALL SPILLS: Slippery when wet. Avoid accidents, clean up immediately. Collect in a container for disposal via special chemical waste collection.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

### Conditions for safe storage:

Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

### Precautions for safe handling:

Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the National Occupational Health and Safety Commission.

### **Engineering controls:**

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

### **Personal Protective Equipment:**

Substance No: 000014542708

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: B - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Product Name: 615-LINE DULUX CEILING PAINT Issued: 13/04/2010

Version: 4









MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: If there is a risk of eye contact and repeated or prolonged skin contact wear gloves and safety glasses. Wash hands after use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous liquid Colour: Coloured Bland

Solubility: Miscible with water. 1.0-1.7 @20°C **Specific Gravity:** Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): Not available Flash Point (°C): Not applicable Flammability Limits (%): Not applicable **Autoignition Temperature (°C):** Not applicable % Volatile by Weight: Not available Solubility in water (g/L): Miscible Not applicable Melting Point/Range (°C): Boiling Point/Range (°C): 100 (water) **Decomposition Point (°C):** Not available

**pH**: 8-10

Viscosity:Not availableEvaporation Rate:Not available

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions of use.

**Conditions to avoid:** Avoid contact with foodstuffs.

**Incompatible materials:** Incompatible with oxidising agents.

Hazardous decomposition

products:

Oxides of carbon.

Hazardous reactions: None known.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:**No adverse effects expected, however, large amounts may cause nausea and vomiting.

Product Name: 615-LINE DULUX CEILING PAINT

Substance No: 000014542708

Issued: 13/04/2010 Version: 4



**Eye contact:** May be an eye irritant.

**Skin contact:** Contact with skin may result in irritation.

**Inhalation:** Where this material is used in a poorly ventilated area, at elevated temperatures or in

confined spaces, vapour may cause irritation to mucous membranes of the respiratory

tract, headache and nausea.

**Long Term Effects:** 

No information available for the product.

**Toxicological Data:** No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

### 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

For large quantities: Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

### 14. TRANSPORT INFORMATION

### **Road and Rail Transport**

Substance No: 000014542708

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

#### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

#### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

Classification: Based on available information, not classified as hazardous according to criteria of Safe

Work Australia: NON-HAZARDOUS SUBSTANCE.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Product Name: 615-LINF DULUX CEILING PAINT Issued: 13/04/2010

Version: 4



# **16. OTHER INFORMATION**

Reason(s) for Issue:

Revised Primary SDS Change to supplier information Change in address details

This safety data sheet has been prepared by SH&E Shared Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: 615-LINE DULUX CEILING PAINT

Substance No: 000014542708

Issued: 13/04/2010 Version: 4