

Petrol Pressure Washer Cold Water

PETROL PRESSURE WASHER - COLD WATER

Product Warranty	2 Years	Coupler Size	3/8" (10mm)
Engine Warranty	3 Years	Cart	35mm push-down style steel cart
Ship Weight	72.6kg	Max Inlet Water Temp	60°C
Pressure	4000 PSI	Max Output Water Temp	60°C
Flow	13.2 lpm	Chemical Injector	Yes
Engine	Honda GX390	Adjustable Pressure	Yes
Engine Displacement	389cc	Fuel Tank Capacity	6.05L
Gross Torque	25 Nm	Fuel Type	Unleaded Petrol
Pump	Comet AWD	Engine Oil Type	SAE 30
Drive	Direct	Pump Oil Type	15W-50
Gun	Industrial Rear Entry w/ 900mm lance	Engine Oil Included	No
Nozzle Type	Quick Connect	Pump Oil Included	Yes
Orifice (Hole Size)	4.0 (0.52"/1.3mm)	Low Oil Shutdown	Yes
Hose	15.24m	Thermal Protector	Yes
Dimensions	86 x 53.5 x 96.5cm		



Long Life

Comet Pump

4000 PSI



 Part No
 NS15781520

 Fineline
 6270783

 Barcode
 9312753036818

- Premium Honda GX390 (389cc) engine for quiet, reliable performance
- 3 Year Australia wide engine warranty with full dealer network support
- Engineered and assembled in the USA using only high quality components delivering reliability
- Long-life Comet direct drive triplex pump
- Vibration isolation system for smooth operation
- Professional duty, quick coupler rear entry 90cm (36") high pressure spray gun
- Includes grey non-marking 15m x 1cm steel braided quick coupler high-pressure anti-kink hose
- Professional 0°, 15°, 25° and 40° quick coupler nozzles and detergent nozzle
- Includes convenient 2-in-1 belt clip nozzle holder
 Push-down style, roll cage welded steel cart with extended handle for smooth, balanced manuevering and protection
- and protection
 All-terrain 38cm (15") easy move pneumatic tyres
 Downstream detergent injector helps prevent
- Downstream detergent injector helps prevent chemicals from entering and corroding the pump

Distributed by



www.kincrome.com.au







Images displayed are for illustration purposes only. Products, product specifications and pricing are subject to change without notice.