

# Safety Data Sheet

## Australian Builders Off-White Cement

### Section 1: Material and Supplier Information

<b>Product Name:</b>	Australian Builders Off White Cement
<b>Applicable In:</b>	Australia
<b>Other Names:</b>	GP Cement, High early age strength cement, off white cement
<b>Recommended Use:</b>	General Purpose Cement may be used as a binder in structural concrete, concrete masonry, mortar and Grouts. It may also be used in the manufacture of fibre cement products, in soil stabilization, civil engineering constructions and mining applications.
<b>Company Details:</b>	Independent Cement & Lime Pty Ltd 750 Lorimer Street Port Melbourne, VIC 3207 ABN 49 005 829 550
<b>Emergency Contact:</b>	Contact Person: Technical Manager Office hours 03 9676 0060 or Poison information center 13 11 26
<b>Phone:</b>	VIC 03 9676 0000
<b>Fax:</b>	VIC 03 9646 4954

This Safety Data Sheet (SDS) is issued by Building Product Supplies Pty Ltd in accordance with the Code and guidelines from the Australian Safety and Compensation Council (ASCC). The information in it must not be altered, deleted or added to. Building Product Supplies Pty Ltd will not accept any responsibility for any changes made to its SDS by any other person or organization. Building Product Supplies Pty Ltd will issue a new SDS when there is a change in product specifications and/ or ASCC standards, guidelines or regulations.

### Section 2: Hazards Identification

**Statement of** This product is classified as HAZARDOUS according to Safe Work Australia criteria. Not Classified as a dangerous good by the criteria of the ADG code, IMDG or IATA.

#### GHS Classifications

Skin Corrosion/ Irritation	Criteria 2
Serious Eye Damage/Eye Irritation:	Criteria 1
Specific Target Organ Systematic Toxicity (Repeated Exposure):	Category 2

**SIGNAL WORD** DANGER

**Pictograms**



**Independent  
Cement**

Independent Cement & Lime Pty Ltd  
ABN 83 803 695 714  
independentcement.com.au  
E info@independentcement.com.au

Victoria (Head Office)  
750 Lorimer St Port Melbourne VIC 3207  
PO Box 523 Port Melbourne VIC 3207  
T 03 9676 0000  
F 03 9646 4954  
Bulk Cement Orders 1300 137 611

New South Wales  
200 Power St Glendenning NSW 2761  
T 02 9625 8999  
F 02 9625 0470  
Bulk Cement Orders 1300 440 072



### Hazard Statements

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H373	May cause damage to lungs and respiratory tract through prolonged or repeated exposure.

### Prevention Statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection

### Response Statements

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs get medical advice/attention.

### Disposal Statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	------------------------------------------------------------------------

<b>UN No</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>Pkg Group</b>	None Allocated
<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated	<b>EPG</b>	None Allocated

## Section 3: Composition / Information on Ingredients

Ingredient	Formula	Proportion	CAS Number
Portland cement clinker	Not available	<60%	65997-15-1
Slag	Not available	<60%	65996-69-2
Lime stone	CaCO <sub>3</sub>	0-5%	1317-65-3



Gypsum	CaSO <sub>4</sub> .2H <sub>2</sub> O	2-5%	10101-41-4
Clinker Kiln dust	Not available	0-1%	68475-76-3

Off-white cement contains chromium hexavalent (18540-29-9) in trace amount.

Off-white cement contains less than 1% crystalline silica (14808-60-7)

## Section 4: First Aid Measures

<b>Eye:</b>	If wet cement is splashed in to the eyes flush thoroughly with flowing water until advised to stop by a poisons Information Centre or a doctor.
<b>Inhalation:</b>	Remove from dusty area to fresh air. If symptoms persist, seek medical attention.
<b>Skin:</b>	Remove heavily contaminated clothing immediately. Wash off skin thoroughly with water. A shower may be required. Seek medical attention for persistent irritation or burning of the skin.
<b>Ingestion:</b>	Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute stomach contents. If symptoms persist, seek medical attention.
<b>Advice to Doctor:</b>	Treat symptomatically.

**First Aid Facilities** Eye wash station.

## Additional Information Aggravated Medical Conditions

<b>Inhalation</b>	Over exposure resulting from prolonged and repeated inhalation of dust containing crystalline silica can cause bronchitis, silicosis (scarring of the lung). It may also increase the risk of scleroderma (a disease affecting the connective tissue of the skin. Joints, blood vessels and internal organs) and lung cancer. Epidemiological studies have shown that smoking increases the risk of bronchitis, silicosis (scarring of the lung) and lung cancer in persons exposed to crystalline silica.
<b>Skin</b>	Prolonged and repeated skin contact with cement in wet concrete, mortars and slurries may result in irritant dermatitis or alkaline burns.
<b>Eye</b>	Irritating to the eye. If wet cement is splashed in to the eye, alkaline burns can cause permanent damage.

## Section 5: Fire Fighting

<b>Flammability:</b>	Not flammable. Does not support combustion of other materials.
<b>Fire and Explosion:</b>	No fire or explosion hazard exists.
<b>Extinguishing:</b>	Non-flammable; use suitable extinguishing agent for surrounding fire



**Hazchem Code:** None Allocated

## **Section 6: Accidental Release Measures**

**Spillage:** If spill (bulk), contact emergency services if appropriate. Wear dust-proof goggles/safety glasses, PVC rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating dust.

**Emergency Procedure:** Follow safety requirements for personal protection under Section 8 Exposure Controls/Personal Protection.

## **Section 7: Handling and Storage**

**Handling:** Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**Storage:** Store off the floor in the original bags in a cool, dry, well ventilated area, removed from excessive moisture and heat. Ensure packages are adequately labelled, protected from physical damage and store in sealed condition when not in use.

**Property/Environmental** Refer to Section 13.

## **Section 8: Exposure Controls / Personal Protection**

**Ventilation** Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation hazard exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

**Exposure Standards**

Lime stone (calcium carbonate) (1317-65-3)  
ES-TWA: 10 mg/m<sup>3</sup> (Respirable Dust)

Chromium (VI) hexavalent (18540-29-9)  
ES-TWA: 0.05 mg/m<sup>3</sup> (Chromium VI compounds)

Gypsum (10101-41-4)  
ES-TWA: 10 mg/m<sup>3</sup> (Respirable Dust)

Portland Cement (65997-15-1)  
ES-TWA: 10 mg/m<sup>3</sup> (Respirable Dust)

Crystalline Silica (Quartz) (14808-60-7)  
ES-TWA: 0.1 mg/m<sup>3</sup> (Respirable Dust)

**PPE** Wear dust-proof goggles/safety glasses and rubber or PVC gloves. Where an inhalation risk exists, wear clear P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear long sleeve shirt and full-length trouser or similar cloth like overall. At high dust levels, wear



a Class P3 respirator or a Powered Air Purifying Respirator (PAPR) with class P3 filter. Check site's specific risk assessment.



## Section 9: Physical and Chemical Properties

<b>Appearance</b>	Off-white powder	<b>Solubility (water)</b>	Slight, hardens when mixing with water.
<b>Odor</b>	Odorless	<b>Specific Gravity</b>	3.0 to 3.2
<b>pH</b>	Approximately 12	<b>% Volatiles</b>	Not Available
<b>Vapor Pressure</b>	Not Available	<b>Flammability</b>	Non-Flammable
<b>Vapor Density</b>	Not Available	<b>Flash Point</b>	Not Relevant
<b>Boiling Point</b>	Not Available	<b>Upper Explosion Limit</b>	Not Relevant
<b>Melting Point</b>	> 1200°C	<b>Lower Explosion Limit</b>	Not Relevant
<b>Evaporation Rate</b>	Not Available	<b>Autoignition Temperature</b>	Not Available
<b>Bulk Density</b>	1200 – 1600 kg/m <sup>3</sup>		
<b>Particle Size</b>	20 – 40% of particles are <7 µm (Respirable Range)		

## Section 10: Stability and Reactivity

<b>Chemical Stability:</b>	Chemically Stable
<b>Conditions to Avoid:</b>	Keep free of moisture
<b>Incompatible Materials</b>	Incompatible with oxidizing agents (e.g. hypochlorite), ethanol, acids (e.g. hydrofluoric acid) and Interhalogens (e.g. chlorine trifluoride). Water contact may increase the temperature (2-3°C) of the product.
<b>Decomposition Products:</b>	Unlikely to evolve toxic gases when heated to decomposition.
<b>Hazardous Reactions:</b>	None

## Section 11: Toxicological Information

<b>Acute Toxicity</b>	No known toxicity data for this product.
<b>Eyes</b>	Irritant upon contact with powder/dust. Over exposure may result in pain, redness, corneal burns and ulceration with possible permanent damage.



**Inhalation** Slightly corrosive. Irritating to the respiratory system, causing coughing and sneezing. Prolong exposure may result in severe mucous membrane irritation and bronchitis. Hexavalent chromium is reported to cause respiratory sensitisation, however due to the trace amount present, a hazard is not anticipated under normal conditions of use. Crystalline silica can cause silicosis (lung disease) with chronic over exposure, however due to low levels percentage and product application, adverse health effects are not anticipated.

**Skin** Irritating to the skin. Prolonged and repeated contact with powder or wetted form may result in skin rash, dermatitis and sensitisation.

**Ingestion** Slightly corrosive. Ingestion may result in burns to the mouth and throat, with vomiting and abdominal pain. Due to product form, ingestion is not considered a likely exposure route.

**Mutagenicity** Insufficient data available for this product to classify as a mutagen.

**Carcinogenicity** Brightonlite cement is not classified as a carcinogen by NOHSC. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1), however due to low levels present and product application, the criteria for classification is not met.

## Section 12: Ecological Information

**Toxicity** Product forms an alkaline slurry when mixed with water. This product is nontoxic to aquatic life forms when present in cured solid form.

**Persistence and Degradability** Product is persistent and would have a low degradability.

**Mobility in Soil** A low mobility would be expected in a landfill situation.

## Section 13: Disposal Considerations

**Waste Disposal** Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer for additional information.

**Legislation** Dispose of in accordance with relevant local legislation. Keep out of sewer stormwater drains.

## Section 14: Transport Information

Not classified as a dangerous good by the criteria of the ADG code.

Transport is by rail or road in bulk or bag form.



Drivers of trucks transporting bagged products should ensure that the bags are properly restrained.

<b>Shipping Name</b>	None Allocated				
<b>UN No</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>Pkg Group</b>	None Allocated
<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated	<b>EPG</b>	None Allocated

## Section 15: Regulatory Information

**Poison Schedule AICS** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP). All chemicals listed on the Australian Inventory of Chemical Standards (AICS).

## Section 16: Other Information

### Additional Information

**CEMENT CONTACT DERMATITIS:** Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitization. The dermatitis is due to the presence of soluble (hexavalent) chromium.

**IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN.** This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

**RESPIRATORS:** In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:** The Recommendation for protective equipment contained within this SDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:** It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an SDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**ABBREVIATIONS:**

mg/m<sup>3</sup> – Milligrams per cubic metre



ppm – Parts Per Million

ES-TWA – Exposure Standard - Time Weighted Average

CNS – Central Nervous System

NOS – Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service Number – used to uniquely identify chemical compounds.

IARC – International Agency for Research on Cancer.

### Report Status

This document has been compiled by Building Product Supplies the manufacturer of the product and serves as the manufacturer's Safety Data Sheet.

While the information in this Safety Data Sheet has been prepared in good faith, Building Product Supplies does not warrant that the information is accurate, complete or up to date.

### Contact Point

For further information on this product contact:

Telephone: Office hours 03 9676 0060

Facsimile: 03 9646 4954

Web site: [www.bpsaust.com](http://www.bpsaust.com)

### Advice Note

The information in this document is believed to be accurate. Please check the currency of this SDS by contacting:

03 9676 0000

Or

[www.bpsaust.com](http://www.bpsaust.com)

Each user of any information, or any product referred to, in this Safety Data Sheet must:

- determine whether the information or product is suitable for their purpose;
- assess and control any risks associated with the information or product; and
- obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Building Product Supplies:

- excludes all representations, warranties and guarantees in relation to any information in this Safety Data Sheet; and
- will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Safety Data Sheet.

